

FOUNDATION SHALL BE:
1. ALL CONCRETE SHALL BE 3,000 PSI (AT 28 DAYS) AIR ENTRAINED, U.N.O. (REF. DETAIL 6/10/00) FOR WALL REINFORCEMENT SCHEDULE, PER GROUP.
2. C&G SHALL BE TIEED TO REINFORCEMENT WHERE INDICATED ON PLANS. MORTAR SHALL BE TYPE S FOR ALL BRICK AND BLOCK APPLICATIONS.
3. BLOCKED WALL AND FOUNDATION CUTS DO NOT BACKFILL WALLS UNTIL BASEMENT SLAB IS POURED.
4. ALL REINFORCING AND BRACING SYSTEM SHALL BE PROTECTED AS INDICATED AND DRAINAGE SHALL REMAIN AT A SUITABLE SUMP FOR DAYLIGHT CONDITION AS REQUIRED PER CODE.
5. DO NOT CUT DRAIN OR NOTCH FOUNDATION WALLS WITHOUT APPROVED DETAILS FROM THE ENGINEER OF RECORD.
6. FOUNDATION CONSTRUCTION SHALL BE RESPONSIBLE FOR ALL SLOPE CUTS AND SOIL STABILIZATION IN ACCORDANCE WITH COUNTY REQUIREMENTS.

1. FOLLOW DOWN ALL INSTALLATIONS FOR CUTTING HOLES IN WWT-1/05/11, ILL. OR FOR PRODUCTS. DO NOT CUT HOLES OR NOTCH WITHOUT PROPER SIGNING AND PLACEMENT.
2. ALL MULTI-DRY HANGERS SHALL BE ATTACHED WITH 3-INCHES OR 180 NAILS AT 12" O.C. (N/A)
3. (MAILED FROM BOTH SIDES OF BEAM ASSEMBLY. FILL LENGTH) 400 FILLER BETWEEN DOUBLE 1-1/2" (305) PER HANG. (SIZES)
4. ALL HANGERS SHALL BE NEW OR #2 & ALL STUDS SFG #2 (N/A).
5. ALL LOADERS EXPOSED TO ELEMENTS OR IN CONTACT WITH CONCRETE SHALL BE PRESSURE TREATED (ACO) SFG #2 OR EQUIVALENT TREATMENT APPROVED FOR GROUND CONTACT.
6. USED ONLY APPROVED NON-CORROSIVE FASTENERS AND HARDWARE FOR ALL ATTACHMENTS IN PRESSURE. IN-PAID LUBRIC.
7. FOLLOW ALL MANUFACTURERS' RECOMMENDATIONS FOR INSTALLED HARDWARE (TILL ALL NAILS IN STUDS AND HANGERS)
8. PROVIDE CROWN BLOCKS UNDER ALL POSTS ABOVE (OF EQUAL WIDTH AND MATERIAL, AS POST)
9. ALL INTERIOR 2X6 BEARING WALLS @ 16" O.C. (N/A)

90 MPH (3-SECOND GUST) - BRACED WALL SCHEDULE

BRACED WALL SCHEDULE - SEE ARCHITECTURAL COVERSHEET FOR CODE REFERENCE

MARK	TYPE	LENGTH	DESCRIPTION	DETAIL
CS-805	PERCEIVED BAND 100 (CS-805)	LENGTH 250 YARD WIDTH 50 YD (THICK 50 YD)	1/16" OSS STRAINING ATTACHED TO STOPS (ROCKED) W/ 1/16" TIE-INS W/ 1/8" W/ 1/8" TIE-INS W/ 1/8" TIE-INS SPRIG STRAINING ATTACHED TO STOPS (ROCKED)	
MS-7	PERCEIVED BAND 100 (BAND 100)	LENGTH 250 YARD WIDTH 50 YD (THICK 50 YD)	1/16" OSS STRAINING ATTACHED TO STOPS (ROCKED) W/ 1/16" TIE-INS W/ 1/8" W/ 1/8" TIE-INS W/ 1/8" TIE-INS SPRIG STRAINING ATTACHED TO STOPS (ROCKED)	
CS-57	PERCEIVED BAND 100 (CS-57)	LENGTH 250 YARD WIDTH 50 YD (THICK 50 YD)	1/16" OSS STRAINING ATTACHED TO STOPS (ROCKED) W/ 1/16" TIE-INS W/ 1/8" W/ 1/8" TIE-INS W/ 1/8" TIE-INS SPRIG STRAINING ATTACHED TO STOPS (ROCKED)	
CS-57	PERCEIVED BAND 100 (CS-57)	LENGTH 250 YARD WIDTH 50 YD (THICK 50 YD)	1/16" OSS STRAINING ATTACHED TO STOPS (ROCKED) W/ 1/16" TIE-INS W/ 1/8" W/ 1/8" TIE-INS W/ 1/8" TIE-INS SPRIG STRAINING ATTACHED TO STOPS (ROCKED)	

SHEAR WALL SCHEDULE - 2001 WOOD FRAMED CONSTRUCTION MANUAL (WFCM)


[illegible]

1. ALL BRACED WALLS AND SHEAR WALLS ASSUME A CONTINUOUSLY SHEATHED STRUCTURE ACCORDANCE WITH RC SECTION 602.10.5
2. ALL WALLS SHOWN HAVE BEEN REDUCED TO REFLECT A 5.0-60.43 FOR STUD FRAMING
3. ALL HARDWARE SHALL BE INSTALLED IN ACCORDANCE WITH THE MANUFACTURERS INSTRUCTIONS
4. REFERENCE ATTACHED DETAILS FOR PORTAL WALL FRAMING
5. FIELD WALLING SHALL BE AT 12" O/C, U.N.O.
6. BRICK ALL EGGS AT BRACED WALL PANELS ONLY

ALL HANGERS SHALL BE AS SPECIFIED BY TRUSS OR JOIST MFG., U.N.O.
(ALL HARDWARE SHALL BE AS MANUFACTURED BY SIMPSON STRONG TIE)

SINGLE FAMILY HOUSE

BUILDING CODE SUMMARY



- 1) WINDOWS TO BE 2' OVER 2' WOOD WINDOWS
- 2) 8 FOOT SHAKER DOORS

REVISION DATE:

REVISION DATE:

REVISION DATE:

ANCHOR BOLT	CONT.	CONTINUOUS	ELEV.	EQU.
ABOVE FINISH FLOOR	CONST.	CONSTRUCTION	EQ.	EQU.
ADJACENT	CRK.	CONCRETE	EQUIP.	EQUIP.
ADJUSTABLE	C.O.	CASED OPENING	EXP.	EXP.
AGRE FINISH TRED	CANT.	COUNTERFEY	EXT.	EXT.
ALUMINUM	C.T.	CERAMIC TILE	EE.	EE.
ANCHOR	C.L.	CEILING	F/C	FLO.
ANGLE	C.M.	CROWN MOULD	F.O.	F.O.
ARCHITECTURAL	C.K.	CORR RAIL	F.M.	F.M.
AT	D	DARTER	F.R.	F.R.
BOLD	D	DESK	P	P
BUILDING	DEL.	DOUBLE	F.R.	F.R.
BEAM	DIA.	DIMETER	F.M.	F.M.
BOTTOM	DIR.	DIRECTION	FT.	FT.
BLOCKING	DN.	DOWN	FTG	FTG
BOLG	DR.	DOOR	GA.	GA.
BREK	DW	DISH WASHER	GALT.	GALT.
BASEMENT	DWS.	DEWING	G.C.	G.C.
C.J.	DOWN	DOWN SPOUT	GRN.	GRN.
CENTER JUNT	DZ.	DEAIL	GP.	GP.
CONCRETE MASONRY UNIT	EACH	EACH	GL.	GL.
COLUMN	E.C.	EXPANSION JOINT	HDR.	HDR.
CONC.	E.L.	ELECTRICAL	HA	HA
CONDITION				

D	M.O.	MASONRY OPENING	QUAD.	QUADKUTFL

"THE OWNER OF THESE PLANS REDUX PROPERTIES, LLC, EXPRESSLY RESERVES THE COMMON LAW COPYRIGHT AND OTHER RIGHTS IN THESE PLANS. THE PLANS MAY NOT BE COPIED, REPRODUCED OR CHANGED IN ANY MANNER WITHOUT THE EXPRESSED WRITTEN CONSENT OF REDUX PROPERTIES, LLC" COPYRIGHT 2015

**REDUX
PROPERTIES
LLC**

Board of Zoning Adjustment
District of Columbia
CASE NO.19207
EXHIBIT NO.4B

FIRE PROTECTION REQUIREMENTS			
	EXISTING ELEMENT	ADDITIONAL REQUIREMENTS	DESIGN FOR EXISTING ADDITIONAL
BRACING WALLS	0	0	-
BRACING TRIMS	0	0	-
BRACING STUDS	1	1	UL-2055
INTERIOR	0	0	-
NON-BRACING WALLS	0	0	-
CATEGORIES	0	0	-
INTERIOR	0	0	-
FLOOR CONSTRUCTION	0	0	-
ROOF CONSTRUCTION	0	0	-
SWIMTS	-	-	-
CONCRETE SITUATION	-	-	-
WOODEN SITUATION	-	-	-
PAINT THE WALL SITUATION	1	1	UL-2055
SMALL SITUATION	-	-	-
STAIR SITUATION	-	-	-
STAIR SITUATION - WOOD	-	-	-

OCUPANCY SEPARATION	-	-
---------------------	---	---

Kr. Kijulnikov 25 str.
Sofia, Bulgaria
Tel: +359 886 880083
e-mail: cmustrach@...

©gmail.com

OS

"STRUCTURAL PLANS CERTIFIED AS PROVIDED
SECTION 106.1.4.1 OF THE DC CONSTRUCTION
CODES SUPPLEMENT AS AMENDED TO DATE"

FINISHED SQUARE FEET:

$$\begin{aligned}\text{BASEMENT} &= 781.33 \text{ S.F.} \\ \text{1ST FLOOR} &= 781.33 \text{ S.F.} \\ \text{2ND FLOOR} &= 781.33 \text{ S.F.} \\ \text{3RD FLOOR} &= 488.50 \text{ S.F.} \\ \text{TOTAL} &= 2,832.49 \text{ S.F.}\end{aligned}$$


PROPERTY ADDRESS:

518 SIXTH STREET
WASHINGTON, DC 20002



[illegible]

SHEET TITLE	Cover Sheet
DATE:	04/23/2015
	REDUX PROPERTIES, LLC

**REDUX
PROPERTIES
LLC**

[illegible]


PROJECT ADDRESS	
518 Sixth Street	
WASHINGTON D.C. 20002	
SHEET TITLE	
Existing Basement & First Floor Plans	
REDUX PROPERTIES, LLC	
DATE:	06/28/15
PROJECT NUMBER	06
SHEET NUMBER	
A1.1	



Structural Engr. Section

Structural Eng. Section

**REDUX
PROPERTIES
LLC**



Kr. Kiriakov 25 str.
Sofia, Bulgaria
tel: +359 886 880089
e-mail: constracelab@gmail.com

[illegible]

PROJECT ADDRESS

518 Sixth Street

WASHINGTON D.C. 20002

SHEET TITLE

Existing Second & Third Floor Plans


MEDUX PROPERTIES LLC

DATE: 06/28/15


SHEET NUMBER

1.2

2 EXISTING THIRD FLOOR PLAN
3/8" = 1'-0"



1
EXISTING SECOND FLOOR PLAN
3/8" = 1'-0"




INDIRECT OF COLUMBIA
ERMIT PROCESSING DIVISION
STRUCTURAL WORK IN GENERAL
APPROVED SUBJECT TO THE
FURTHER APPROVAL OF CONSTRUCTION

Structural Engr. Section

LEGEND:

 INDICATES EXISTING WALL

 INDICATES WALLS WHICH WILL BE DEMOLISHED

PROJECT ADDRESS

WASHINGTON D.C. 20002

SHEET TITLE

REDUX PROPERTIES LLC

15/04/23

123

90

Architectural floor plan of a residential unit. The overall dimensions are 14' - 0" wide by 53' - 8" deep. The plan includes the following rooms and features:

- KITCHEN: Located at the top of the plan.**
- POWDER:** A small bathroom located between the kitchen and the living room.
- UTILITY:** A room located to the right of the powder room.
- ENTRANCE:** Located on the left side of the plan.
- LIVING ROOM:** A large room occupying the bottom half of the plan.
- Staircase:** A circular staircase with an "UP" arrow, located in the center of the plan.
- Handwritten Note:** "N/C SEE PLANS" with an arrow pointing to a specific location in the living room.
- Dimensions:**
 - Overall width: 14' - 0"
 - Overall depth: 53' - 8"
 - Room widths: 5' - 9", 3' - 0", 5' - 4", 6' - 0", 2' - 8"
 - Room depths: 3' - 0", 20' - 2", 13' - 6"

Architectural floor plan of the basement level. The plan shows a large rectangular room with a thick perimeter wall. Dimensions are provided for the overall footprint and specific sections. A door is indicated with its opening dimensions. A label identifies the level and area. A note points to the thick wall, indicating it is existing concrete footing.

Overall dimensions: 14'-0" (width) x 34'-6" (depth). A smaller section on the right is 19'-2" wide.

Door dimensions: 2'-4" (width) x 3'-0" (height).

Label: BASEMENT 1, 410 SF.

Note: EXISTING CONCR. CONC. FTG. (pointing to the thick perimeter wall).


DEMOLITION FIRST FLOOR PLAN

DEMOLITION BASEMENT FLOOR

LEGEND:

 INDICATES EXISTING WALL

 INDICATES WALLS WHICH WILL BE DEMOLISHED

[illegible]

ISSUE DESCRIPTION

WASHINGTON D.C. 20002

Second & Third Floor Demolition Plans

DATE: 04/23/15

PROJECT NUMBER	06
----------------	----

A2.2

20' - 11"

32' - 9"

ROOF TOP DECK
11
293 SF

LIVING ROOM
53
360 SF

POWDER
10
21 SF

NIC
BE C
PAGES
MD

5' - 0"

6' - 0"

2' - 8"

Architectural floor plan of a residential unit, oriented vertically. The plan includes the following rooms and features:

- BEDROOM:** Located at the top of the plan.
- BATHROOM:** Located below the bedroom.
- CLOSET:** Located below the bathroom.
- ENTRANCE:** Located below the closet.
- LIVING ROOM:** Located at the bottom of the plan.
- UP:** A circular feature, likely a well or a small pool, located between the closet and the living room.

Dimensions:

- Overall width: 13' - 6"
- Overall height: 8' - 0"
- Overall height (including porch): 7' - 0"
- Overall height (including porch): 18' - 10"
- Overall width (including porch): 53' - 8"
- Overall width (including porch): 5' - 4"
- Overall width (including porch): 6' - 0"
- Overall width (including porch): 2' - 8"
- Overall width (including porch): 5' - 0"

Handwritten Notes:

- "4" x 12" O.C. BRACKET IN KNOB IS HOLD"
- "N/C SEE 'C' PREP"

DISTRICT OF COLUMBIA
MAYOR
PERMIT PROCESSING DIVISION
GENERAL
STRUCTURAL WORK IN
APPROVED SUBJECT TO THE
FURTHER APPROVAL OF CONSTRUCTION

Structural Engr. Section

e-mail: constructahy@gmail.com

[illegible]


WASHINGTON D.C. 20002

Notes


THE UNIVERSITY OF CHICAGO

PROJECT NUMBER

C-S.02



**REDUX
PROPERTIES
LLC**



Kr. Kyulievkov 25 str.
Sofia, Bulgaria
tel: +359 886 880089
e-mail: constrctady@gmail.com

[illegible]

PROJECT ADDRESS

518 Sixth Street

WASHINGTON D.C. 20002

SHEET TITLE

Proposed Basement & First Floor Plans

REDUX PROPERTIES LLC

DATE:
15/04/23


15/04/23

PROJECT NUMBER	06
----------------	----


SHEET NUMBER

A3.1

2
PROPOSED FIRST FLOOR PLAN
3/8" = 1'-0"



PROPOSED BASEMENT FLOOR
PLAN
1
3/8" = 1'-0"




NOTES:

- 1) WINDOWS TO BE 2' OVER 2' WOOD WINDOWS
- 2) 8 FOOT SHAKER DOORS

DISTRICT OF COLUMBIA
PERMIT PROCESSING DIVISION
STRUCTURAL WORK TO THE
APPROVED SUBJECT OF CONSTRUCTION
FURTHER APPROVAL

~~Structural Engr Section~~

**REDUX
PROPERTIES
LLC**



Kr. Kyuliakov 25 str.
Sofia, Bulgaria
tel: +359 886 880069
e-mail: constrctady@gmail.com

[illegible]

PROJECT ADDRESS

518 Sixth Street

WASHINGTON D.C. 20002

SHEET TITLE

Proposed Second & Third Floor Plans

REDUX PROPERTIES LLC


DATE: 04/23/15

SUBJECT NUMBER

SHEET NUMBER

A3.2


PROPOSED THIRD FLOOR PLAN

$$3/8" = 1'-0"$$


NOTES:

- 1) WINDOWS TO BE 2' OVER 2' WOOD WINDOWS
- 2) 8 FOOT SHAKER DOORS

PROPOSED SECOND FLOOR PLAN

$$\underline{3/8" = 1'-0"}$$


NOTES:


- 1) WINDOWS TO BE 2' OVER 2' WOOD WINDOWS
- 2) 8 FOOT SHAKER DOORS

DISTRICT OF COLUMBIA
COURT OF COMMON PLEAS
CRIMINAL DIVISION
CLERK OF COURT
JAMES H. HARRIS
1000 PENNSYLVANIA AVENUE, N.E.
WASHINGTON, D.C. 20002
202-544-2000
202-544-2001
202-544-2002
202-544-2003
202-544-2004
202-544-2005
202-544-2006
202-544-2007
202-544-2008
202-544-2009
202-544-2010
202-544-2011
202-544-2012
202-544-2013
202-544-2014
202-544-2015
202-544-2016
202-544-2017
202-544-2018
202-544-2019
202-544-2020
202-544-2021
202-544-2022
202-544-2023
202-544-2024
202-544-2025
202-544-2026
202-544-2027
202-544-2028
202-544-2029
202-544-2030
202-544-2031
202-544-2032
202-544-2033
202-544-2034
202-544-2035
202-544-2036
202-544-2037
202-544-2038
202-544-2039
202-544-2040
202-544-2041
202-544-2042
202-544-2043
202-544-2044
202-544-2045
202-544-2046
202-544-2047
202-544-2048
202-544-2049
202-544-2050
202-544-2051
202-544-2052
202-544-2053
202-544-2054
202-544-2055
202-544-2056
202-544-2057
202-544-2058
202-544-2059
202-544-2060
202-544-2061
202-544-2062
202-544-2063
202-544-2064
202-544-2065
202-544-2066
202-544-2067
202-544-2068
202-544-2069
202-544-2070
202-544-2071
202-544-2072
202-544-2073
202-544-2074
202-544-2075
202-544-2076
202-544-2077
202-544-2078
202-544-2079
202-544-2080
202-544-2081
202-544-2082
202-544-2083
202-544-2084
202-544-2085
202-544-2086
202-544-2087
202-544-2088
202-544-2089
202-544-2090
202-544-2091
202-544-2092
202-544-2093
202-544-2094
202-544-2095
202-544-2096
202-544-2097
202-544-2098
202-544-2099
202-544-2100
202-544-2101
202-544-2102
202-544-2103
202-544-2104
202-544-2105
202-544-2106
202-544-2107
202-544-2108
202-544-2109
202-544-2110
202-544-2111
202-544-2112
202-544-2113
202-544-2114
202-544-2115
202-544-2116
202-544-2117
202-544-2118
202-544-2119
202-544-2120
202-544-2121
202-544-2122
202-544-2123
202-544-2124
202-544-2125
202-544-2126
202-544-2127
202-544-2128
202-544-2129
202-544-2130
202-544-2131
202-544-2132
202-544-2133
202-544-2134
202-544-2135
202-544-2136
202-544-2137
202-544-2138
202-544-2139
202-544-2140
202-544-2141
202-544-2142
202-544-2143
202-544-2144
202-544-2145
202-544-2146
202-544-2147
202-544-2148
202-544-2149
202-544-2150
202-544-2151
202-544-2152
202-544-2153
202-544-2154
202-544-2155
202-544-2156
202-544-2157
202-544-2158
202-544-2159
202-544-2160
202-544-2161
202-544-2162
202-544-2163
202-544-2164
202-544-2165
202-544-2166
202-544-2167
202-544-2168
202-544-2169
202-544-2170
202-544-2171
202-544-2172
202-544-2173
202-544-2174
202-544-2175
202-544-2176
202-544-2177
202-544-2178
202-544-2179
202-544-2180
202-544-2181
202-544-2182
202-544-2183
202-544-2184
202-544-2185
202-544-2186
202-544-2187
202-544-2188
202-544-2189
202-544-2190
202-544-2191
202-544-2192
202-544-2193
202-544-2194
202-544-2195
202-544-2196
202-544-2197
202-544-2198
202-544-2199
202-544-2200
202-544-2201
202-544-2202
202-544-2203
202-544-2204
202-544-2205
202-544-2206
202-544-2207
202-544-2208
202-544-2209
202-544-2210
202-544-2211
202-544-2212
202-544-2213
202-544-2214
202-544-2215
202-544-2216
202-544-2217
202-544-2218
202-544-2219
202-544-2220
202-544-2221
202-544-2222
202-544-2223
202-544-2224
202-544-2225
202-544-2226
202-544-2227
202-544-2228
202-544-2229
202-544-2230
202-544-2231
202-544-2232
202-544-2233
202-544-2234
202-544-2235
202-544-2236
202-544-2237
202-544-2238
202-544-2239
202-544-2240
202-544-2241
202-544-2242
202-544-2243
202-544-2244
202-544-2245
202-544-2246
202-544-2247
202-544-2248
202-544-2249
202-544-2250
202-544-2251
202-544-2252
202-544-2253
202-544-2254
202-544-2255
202-544-2256
202-544-2257
202-544-2258
202-544-2259
202-544-2260
202-544-2261
202-544-2262
202-544-2263
202-544-2264
202-544-2265
202-544-2266
202-544-2267
202-544-2268
202-544-2269
202-544-2270
202-544-2271
202-544-2272
202-544-2273
202-544-2274
202-544-2275
202-544-2276
202-544-2277
202-544-2278
202-544-2279
202-544-2280
202-544-2281
202-544-2282
202-544-2283
202-544-2284
202-544-2285
202-544-2286
202-5

PERMITS PROCESSING IN GENERAL
STRUCTURAL WORK TO THE
APPROVED SUBJECT OF CONSTRUCTION
FURTHER APPROVAL

Date _____
Structural Engg. Section _____

**REDUX
PROPERTIES
LLC**



Kr. Kiyankov 25 str.
Sofia, Bulgaria
tel: +359 886 880089
e-mail: constrctady@gmail.com

[illegible]

PROJECT ADDRESS

518 Sixth Street

WASHINGTON D.C. 20002

SHEET TITLE

*First Floor – Existing,
Demolition & Proposed Joists
Plan*

REDUX PROPERTIES LLC

DATE: _____

Acknowledgements

26

SHEET NUMBER

C-1.1

LEGEND:

INDICATES EXISTING WALLS

INDICATES EXISTING ELEMENTS TO BE DEMOLISHED


INDICATES EXISTING JOISTS

INDICATES EXISTING JOISTS TO BE REPLACED

INDICATES NEW JOISTS

INDICATES PROPOSED WALLS

2 First Floor Existing Joist Plan
3/8" = 1'-0"




EXISTING STAIRS TO BE
DEMOLISHED

EXISTING EXT.
WALLS, TYP.

EXISTING STAIRS TO
BE DEMOLISHED

EXISTING WALLS TO BE
DEMOLISHED, TYP.

NEW OPENING INTO
THE EXISTING EXT.
WALL -




EXISTING DOOR TO
BE DEMOLISHED,
TYP.

REPLACE EXISTING 2x10 JOISTS AT STAIRS.
WRAP END OF JOISTS AND FILL BRICK
POCKET SOLID AROUND JOISTS

3 First Floor Demolition Joist Plan
3/8" = 1'-0"

NEW JOISTS
2X10 SYP JOISTS @ 16" O.C. HUNG FROM LVL
WITH LUS210. END BEARING ON BRICK TO BE
WRAPPED AND POCKET FILLED SOLID WITH MORTAR



(2) 9 7/8" LVL

INT. WELLS TYP.

POWDER	7
--------	---

PROPOSED	NEW
----------	-----

DISTRICT OF COLUMBIA
PERMIT PROCESSING DIVISION
STRUCTURAL WORK IN GENERAL
APPROVED SUBJECT TO THE
FURTHER APPROVAL OF CONSTRUCTION




Structural Exam Section

Date

Historic Preservation Clearance for Exterior Work. Scope of approved exterior work is restricted only to drawings with this stamp. Signature and date  7/2/11.

1 First Floor Proposed Joist Plan
3/8" = 1'-0"

REDUX
PROPERTIES
LLC



THE GENERAL LAYOUT OF GAS, PIPING AND/OR PLUMBING SYSTEMS (Water, Sanitary and Storm) SHOWN ON THESE DRAWINGS HAS BEEN REVIEWED FOR COMPLIANCE WITH THE APPLICABLE PROVISIONS OF THE D.C. CONSTRUCTION CODES AND IS APPROVED.

Date: 04/24/15

CONSTRUCTION


Mechanical Engineering Section

ALL MECHANICAL EQUIPMENT AND/OR APPLIANCES SHALL BE FOR THE USE OF AN APPROVED AGENCY SHALL BE APPROVED FOR THE PROPOSED USE AND LOCATION AND SHALL BE INSTALLED IN ACCORDANCE WITH THE MANUFACTURER'S INSTALLATION INSTRUCTIONS.

SEPARATE ELECTRICAL, PLUMBING AND MECHANICAL INSTALLATION PERMITS ARE REQUIRED.

PROJECT ADDRESS	
518 6TH STREET	
WASHINGTON D.C. 20002	
SHEET TITLE	
Building Domestic water supply plans and risers	
DATE:	PROJECT NUMBER
04/24/15	
SHEET NUMBER	
P1	

REDUX
PROPERTIES
LLC




3RD floor water

3RD FLOOR

2ND FLOOR

1ST FLOOR

BASEMENT FLOOR



THE GENERAL LAYOUT OF GAS PIPING AND/OR PLUMBING SYSTEMS (Water, Sanitary and Storm) SHOWN ON THESE DRAWINGS HAS BEEN REVIEWED FOR COMPLIANCE WITH THE APPLICABLE PROVISIONS OF THE D.C. CONSTRUCTION CODES AND IS APPROVED.
Date: JUN 25 2015
Mechanical Engineering Section

ALL MECHANICAL EQUIPMENT AND/OR APPLIANCES SHALL BEING THE LABEL OF APPROVED AGENCY SHALL BE APPROVED FOR THE PROPOSED USE AND LOCATION AND SHALL BE INSTALLED IN ACCORDANCE WITH THE MANUFACTURER'S INSTALLATION INSTRUCTIONS

ISSUE DESCRIPTION

PROJECT ADDRESS

518 6TH STREET

WASHINGTON D.C. 20002

SHEET TITLE

Building
Domestic water supply plans
and risers

DATE: 04/24/15


PROJECT NUMBER

SHEET NUMBER

P2

Water riser diagram

**REDUX
PROPERTIES
LLC**



THE GENERAL LAYOUT OF GAS PIPING AND/OR PLUMBING SYSTEMS (Water, Sanitary and Storm) SHOWN ON THESE DRAWINGS HAS BEEN REVIEWED FOR COMPLIANCE WITH THE APPLICABLE PROVISIONS OF THE D.C. CONSTRUCTION CODE AND IS APPROVED.

Date APR 25 2015



Mechanical Engineering Section

ALL MECHANICAL EQUIPMENT AND/OR APPLIANCES SHALL BEAR THE LABEL OF AN APPROVED AGENCY SHALL BE APPROVED FOR THE PROPOSED USE AND LOCATION AND SHALL BE INSTALLED IN ACCORDANCE WITH THE MANUFACTURER'S INSTRUCTIONS AND THE INSTALLED INSTRUCTIONS.

APARTE ELECTRICAL, PLUMBING AND MECHANICAL
SPECIALTY SERVICES ARE AVAILABLE

PROJECT ADDRESS	
518 6TH STREET	
WASHINGTON D.C. 20002	
SHEET TITLE	
Domestic WASTE/VENT plans and risers	
DATE:	
04/24/15	
SHEET NUMBER	PROJECT NUMBER
P3	

ROOFTOP DECK
19
293 SF




Mechanical Engineering Section

SEPARATE ELECTRICAL, PLUMBING AND MECHANICAL
INSTALLATION POINTS ARE REQUIRED.

P4

**REDUX
PROPERTIES
LLC**



Mr. Kulshakar 25 str.
Sofia, Bulgaria
tel. +359 896 000000
e-mail: condor@abg.gmail.com

[illegible]

PROJECT ADDRESS

518 Sixth Street

WASHINGTON D.C. 20002

SHEET TITLE

Electrical Layout Basement & First Floor


REDUX PROPERTIES LLC

DATE: 15/04/23

PROJECT NUMBER	06
----------------	----


SHEET NUMBER

EO 1



MAIN PANEL BOARD

2 PROPOSED FIRST FLOOR PLAN
3/8" = 1'-0"



ELECTRICAL FIXTURES	
SYMBOL	DESCRIPTION
	15 AMPS DUPLEX RECEPTACLE
	15 AMPS GFCI DUPLEX
	HEAVY DUTY OUTLET 220V
	SWITCH
	2 WAY SWITCH
	EXHAUST FAN
	6" RECESSED DOWN LIGHT
	PENDANT/HANGING LIGHT
	3" RECESSED DOWN LIGHT
	DISTRIBUTION BOARD
	SMOKE/CARBON MONOXIDE DETECTOR
	OUTDOOR LIGHT

ELECTRICAL NOTES

1. SMOKE/CARBON MONOXIDE DETECTOR WILL BE HARD WIRED
2. ALL OUTLETS WILL BE AFCI - ARC FAULT INTERRUPT

PROPOSED BASEMENT FLOOR

PLAN

$$3/8'' = 1'-0''$$



JUN 30 2015

1000

Mr. Hristov 25 str.
Sofia, Bulgaria
tel: +359 884 888888
e-mail: custres@lyon-gmail.com

[illegible]

PROJECT ADDRESS	518 Sixth Street WASHINGTON D.C. 20002		
SHEET TITLE	Electrical Layout Second & Third Floor		
DATE:	04/23/15		
	PROJECT NUMBER	E02	
	06		
	REDUX PROPERTIES LLC		



ELECTRICAL FIXTURES	
SYMBOL	DESCRIPTION
	15 AMPS DUPLEX RECEPTACLE
	15 AMPS GFCI DUPLEX
	HEAVY DUTY OUTLET 220V
	SWITCH
	2 WAY SWITCH
	EXHAUST FAN
	6" RECESSED DOWN LIGHT
	PENDANT/HANGING LIGHT
	3" RECESSED DOWN LIGHT
	DISTRIBUTION BOARD
	SMOKE/CARBON MONOXIDE DETECTOR
	OUTDOOR LIGHT

ELECTRICAL NOTES

1. SMOKE/CARBON MONOXIDE DETECTOR WILL BE HARD WIRED
2. ALL OUTLETS WILL BE AFCI - ARC FAULT INTERRUPT

PROPOSED SECOND FLOOR PLAN

DEPARTMENT OF THE ARMY
 OFFICE OF THE SECRETARY
 WASHINGTON, D. C. 20315
 JUN 30 2015

PROJECT: 6TH STREET
LOAD DISTRIBUTION SCHEDULE

Type: Surface Mounted
Main Breaker: 200 Amps
Volts: 120/208 V

Rating of Incomer	Sr. No.	Circuit Ref. No.	MCB Rating in Amps	CCT Wire Size sq.mm	ECC Wire Size sq.mm	Connected Load / Points				Total Load (Watts)	Load in Watts Each			Sr. No.	Circuit Ref. No.	MCB Rating in Amps	CCT Wire Size sq.mm	ECC Wire Size sq.mm	Connected Load / Points				Total Load (Watts)	Load in Watts Each		
						Lighting	15 Amps Duplex Outlet	15 Amps gfcI Outlet	Heavy duty Outlet		L1	L2	L3						Lighting	15 Amps Duplex Outlet	15 Amps gfcI Outlet	Heavy duty Outlet		L1	L2	L3
200 Amp TP MCCB	1	1C1	10	2.5	2.5	1				1100	1100			25	2P10	20	4	4			2		1	4000	4000	
	2	1C2	10	2.5	2.5	1				900		900		26	2P11	20	4	4					2500		2500	
	3	1P1	20	4	4		3			6000				27	3C1	10	2.5	2.5	1				900			900
	4	1P2	20	4	4		4			8000	8000			28	3C2	10	2.5	2.5	1				1000	1000		
	5	1P3	20	4	4		3			6000		6000		29	3C3	10	2.5	2.5		1			700		700	
	6	1P4	20	4	4				1	3000		3000		30	3P1	20	4	4			3		6000	6000		6000
	7	1P5	20	4	4			2		5000	5000			31	3P2	20	4	4			3		6000	6000		
	8	1P6	20	4	4			1		2500		2500		32	3P3	20	4	4				1	2500		2500	
	9	1P7	20	4	4			1		2500			2500	33	3P4	20	4	4			2		4000			4000
	10	1P8	20	4	4			1		2500	2500			34	3P5	20	4	4			5		10000			10000
	11	1P9	20	4	4		4			8000		8000		35	3P6	20	4	4			3		6000	6000		
	12	1P10	20	4	4			1		2500			2500	36	3P7	20	4	4			4		8000	8000		8000
	13	1P11	20	4	4		2			4000		4000		37	4C1	10	2.5	2.5	1				700		700	
	14	2C1	10	2.5	2.5	1				600	600		1600	38	4C2	10	2.5	2.5			3		6000			6000
	15	2C2	10	2.5	2.5					1600				40	4P2	20	4	4			2		4000		4000	
	16	2P1	20	4	4		3			6000	6000			41	4P3	20	4	4				1	2500	2500		
	17	2P2	20	4	4		2			4000		4000		42	4P4	20	4	4					2500			2500
	18	2P3	20	4	4				1	3000		3000		43	4P5	20	4	4			1		2000	2000		
	19	2P4	20	4	4			2		5000	5000			44	Spare	10	-	-								
	20	2P5	20	4	4			1		2500		2500		45	Spare	10	-	-								
	21	2P6	20	4	4		2			4000			4000	45	Spare	20	-	-								
	22	2P7	20	4	4		1			4500			4500	44	Spare	20	-	-								
	23	2P8	20	4	4			1		2500		2500		45	Spare	20	-	-								
	24	2P9	20	4	4			1		2500	2500			46	Spare	20	-	-								

L1 = 53000 WATTS = 147.12 AMPS
L2 = 50800 WATTS = 141.01 AMPS
L3 = 54500 WATTS = 151.28 AMPS

RECEIVED
JUN 5 @ 2015

FOUNDATION NOTES:
1. ALL CONCRETE SHALL BE 3,000 PSI (AT 28 DAYS) AIR ENTRAINED, U.N.O. (REF: DETAIL B/PNO 1) FOR WALL REINFORCEMENT SCHEDULE. (7/9)
2. CUR SHALL BE FILLED WITH 3,000 PSI GROUT WHERE INDICATED ON PLANS. MORTAR SHALL BE TYPE "S" FOR ALL BELOW GRADE APPLICATIONS.
3. BACKFILL WALLS IN COAL LIFTS, DO NOT BACKFILL WALLS UNTIL BASEMENT SLAB IS POURED

AND 1ST FLOOR DECK IS INSTALLED AND TILLY SHEATED.
4. WATERPROOFING AND DRAINAGE SYSTEM SHALL BE PROVIDED AS INDICATED AND DRAINAGE SHALL TERMINATE AT A SUITABLE SUMP OR DAYLIGHT CONDITION AS REQUIRED PER CODE.
5. DO NOT CUT DRILL OR NOTCH FOUNDATION WALLS WITHOUT APPROVED DETAILS FROM THE ENGINEER OF RECORD.
6. FOUNDATION CONTRACTORS SHALL BE RESPONSIBLE FOR ALL SLOPE CUTS AND SOIL STABILIZATION IN ACCORDANCE WITH COUNTY REQUIREMENTS.

1. FOLLOW MANUFACTURER'S INSTRUCTIONS FOR CUTTING HOLES IN AIR-1100, TUL OR PSL PRODUCTS. DO NOT CUT HOLES OR NOTCH WITHOUT PROPER SKILL AND PLACEMENT.
2. ALL HOUL-747, VENTURUS, AND AIR-1100 SHALL BE ATTACHED WITH 3-5006S AT 12" O/C (MAILED FROM BOTH SIDES OF BEAM ASSEMBLY. FILL LENGTH=1000 FILLER BETWEEN DOUBLE L-BOOTS PER MAINT. SHEET)
3. ALL HEADERS SHALL BE ROW FOR #2 & ALL STOPS SP# #2 (U.M.O.)
4. ALL LUGS EXPOSED TO ELEMENTS OR IN CONTACT WITH CONCRETE SHALL BE PRESSURE TREATED (ACO SP# #2) OR EQUIVALENT TREATMENT APPROVED FOR CORROSION CONTACT.
5. USE ONLY APPROVED NON-CORROSIVE FASTENERS AND HARDWARE FOR ALL ATTACHMENTS IN PRESSURE TREATED LUGS.
6. FOLLOW ALL MANUFACTURER'S RECOMMENDATIONS FOR INSTALLED HARDWARE. FILL ALL WAKES WITH ANCHORS AND WADERS.
7. PROVIDE CUSHION LUGS UNDER ALL POSTS ABOVE (OR EQUAL WIDTH AND MATERIAL AS POST)
8. ALL INTERIOR 2X4 BEARING WALLS @ 16" O.C. (U.M.O.)

90 MPH (3-SECOND GUST) -- BRACED WALL SCHEDULE

MARK	TYPE	LENGTH	DESCRIPTION	DETAIL
------	------	--------	-------------	--------

CS-1992	1/16th 65% S&P S&P 10% (CS-1992)	1/16th 65% S&P S&P 10% (CS-1992)	1/16th 65% S&P S&P 10% (CS-1992)	1/16th 65% S&P S&P 10% (CS-1992)	1/16th 65% S&P S&P 10% (CS-1992)	1/16th 65% S&P S&P 10% (CS-1992)	1/16th 65% S&P S&P 10% (CS-1992)	1/16th 65% S&P S&P 10% (CS-1992)	1/16th 65% S&P S&P 10% (CS-1992)	1/16th 65% S&P S&P 10% (CS-1992)	1/16th 65% S&P S&P 10% (CS-1992)	1/16th 65% S&P S&P 10% (CS-1992)	1/16th 65% S&P S&P 10% (CS-1992)	1/16th 65% S&P S&P 10% (CS-1992)	1/16th 65% S&P S&P 10% (CS-1992)	1/16th 65% S&P S&P 10% (CS-1992)	1/16th 65% S&P S&P 10% (CS-1992)	1/16th 65% S&P S&P 10% (CS-1992)	1/16th 65% S&P S&P 10% (CS-1992)	1/16th 65% S&P S&P 10% (CS-1992)	1/16th 65% S&P S&P 10% (CS-1992)	1/16th 65% S&P S&P 10% (CS-1992)	1/16th 65% S&P S&P 10% (CS-1992)	1/16th 65% S&P S&P 10% (CS-1992)	1/16th 65% S&P S&P 10% (CS-1992)	1/16th 65% S&P S&P 10% (CS-1992)	1/16th 65% S&P S&P 10% (CS-1992)	1/16th 65% S&P S&P 10% (CS-1992)	1/16th 65% S&P S&P 10% (CS-1992)	1/16th 65% S&P S&P 10% (CS-1992)	1/16th 65% S&P S&P 10% (CS-1992)	1/16th 65% S&P S&P 10% (CS-1992)	1/16th 65% S&P S&P 10% (CS-1992)	1/16th 65% S&P S&P 10% (CS-1992)	1/16th 65% S&P S&P 10% (CS-1992)	1/16th 65% S&P S&P 10% (CS-1992)	1/16th 65% S&P S&P 10% (CS-1992)	1/16th 65% S&P S&P 10% (CS-1992)	1/16th 65% S&P S&P 10% (CS-1992)	1/16th 65% S&P S&P 10% (CS-1992)	1/16th 65% S&P S&P 10% (CS-1992)	1/16th 65% S&P S&P 10% (CS-1992)	1/16th 65% S&P S&P 10% (CS-1992)	1/16th 65% S&P S&P 10% (CS-1992)	1/16th 65% S&P S&P 10% (CS-1992)	1/16th 65% S&P S&P 10% (CS-1992)	1/16th 65% S&P S&P 10% (CS-1992)	1/16th 65% S&P S&P 10% (CS-1992)	1/16th 65% S&P S&P 10% (CS-1992)	1/16th 65% S&P S&P 10% (CS-1992)	1/16th 65% S&P S&P 10% (CS-1992)	1/16th 65% S&P S&P 10% (CS-1992)	1/16th 65% S&P S&P 10% (CS-1992)	1/16th 65% S&P S&P 10% (CS-1992)	1/16th 65% S&P S&P 10% (CS-1992)	1/16th 65% S&P S&P 10% (CS-1992)	1/16th 65% S&P S&P 10% (CS-1992)	1/16th 65% S&P S&P 10% (CS-1992)	1/16th 65% S&P S&P 10% (CS-1992)	1/16th 65% S&P S&P 10% (CS-1992)	1/16th 65% S&P S&P 10% (CS-1992)	1/16th 65% S&P S&P 10% (CS-1992)	1/16th 65% S&P S&P 10% (CS-1992)	1/16th 65% S&P S&P 10% (CS-1992)	1/16th 65% S&P S&P 10% (CS-1992)	1/16th 65% S&P S&P 10% (CS-1992)	1/16th 65% S&P S&P 10% (CS-1992)	1/16th 65% S&P S&P 10% (CS-1992)	1/16th 65% S&P S&P 10% (CS-1992)	1/16th 65% S&P S&P 10% (CS-1992)	1/16th 65% S&P S&P 10% (CS-1992)	1/16th 65% S&P S&P 10% (CS-1992)	1/16th 65% S&P S&P 10% (CS-1992)	1/16th 65% S&P S&P 10% (CS-1992)	1/16th 65% S&P S&P 10% (CS-1992)	1/16th 65% S&P S&P 10% (CS-1992)	1/16th 65% S&P S&P 10% (CS-1992)	1/16th 65% S&P S&P 10% (CS-1992)	1/16th 65% S&P S&P 10% (CS-1992)	1/16th 65% S&P S&P 10% (CS-1992)	1/16th 65% S&P S&P 10% (CS-1992)	1/16th 65% S&P S&P 10% (CS-1992)	1/16th 65% S&P S&P 10% (CS-1992)	1/16th 65% S&P S&P 10% (CS-1992)	1/16th 65% S&P S&P 10% (CS-1992)	1/16th 65% S&P S&P 10% (CS-1992)	1/16th 65% S&P S&P 10% (CS-1992)	1/16th 65% S&P S&P 10% (CS-1992)	1/16th 65% S&P S&P 10% (CS-1992)	1/16th 65% S&P S&P 10% (CS-1992)	1/16th 65% S&P S&P 10% (CS-1992)	1/16th 65% S&P S&P 10% (CS-1992)	1/16th 65% S&P S&P 10% (CS-1992)	1/16th 65% S&P S&P 10% (CS-1992)	1/16th 65% S&P S&P 10% (CS-1992)	1/16th 65% S&P S&P 10% (CS-1992)	1/16th 65% S&P S&P 10% (CS-1992)	1/16th 65% S&P S&P 10% (CS-1992)	1/16th 65% S&P S&P 10% (CS-1992)	1/16th 65% S&P S&P 10% (CS-1992)	1/16th 65% S&P S&P 10% (CS-1992)	1/16th 65% S&P S&P 10% (CS-1992)	1/16th 65% S&P S&P 10% (CS-1992)	1/16th 65% S&P S&P 10% (CS-1992)	1/16th 65% S&P S&P 10% (CS-1992)	1/16th 65% S&P S&P 10% (CS-1992)	1/16th 65% S&P S&P 10% (CS-1992)	1/16th 65% S&P S&P 10% (CS-1992)	1/16th 65% S&P S&P 10% (CS-1992)	1/16th 65% S&P S&P 10% (CS-1992)	1/16th 65% S&P S&P 10% (CS-1992)	1/16th 65% S&P S&P 10% (CS-1992)	1/16th 65% S&P S&P 10% (CS-1992)	1/16th 65% S&P S&P 10% (CS-1992)	1/16th 65% S&P S&P 10% (CS-1992)	1/16th 65% S&P S&P 10% (CS-1992)	1/16th 65% S&P S&P 10% (CS-1992)	1/16th 65% S&P S&P 10% (CS-1992)	1/16th 65% S&P S&P 10% (CS-1992)	1/16th 65% S&P S&P 10% (CS-1992)	1/16th 65% S&P S&P 10% (CS-1992)	1/16th 65% S&P S&P 10% (CS-1992)	1/16th 65% S&P S&P 10% (CS-1992)	1/16th 65% S&P S&P 10% (CS-1992)	1/16th 65% S&P S&P 10% (CS-1992)	1/16th 65% S&P S&P 10% (CS-1992)	1/16th 65% S&P S&P 10% (CS-1992)	1/16th 65% S&P S&P 10% (CS-1992)	1/16th 65% S&P S&P 10% (CS-1992)	1/16th 65% S&P S&P 10% (CS-1992)	1/16th 65% S&P S&P 10% (CS-1992)	1/16th 65% S&P S&P 10% (CS-1992)	1/16th 65% S&P S&P 10% (CS-1992)	1/16th 65% S&P S&P 10% (CS-1992)	1/16th 65% S&P S&P 10% (CS-1992)	1/16th 65% S&P S&P 10% (CS-1992)	1/16th 65% S&P S&P 10% (CS-1992)	1/16th 65% S&P S&P 10% (CS-1992)	1/16th 65% S&P S&P 10% (CS-1992)	1/16th 65% S&P S&P 10% (CS-1992)	1/16th 65% S&P S&P 10% (CS-1992)	1/16th 65% S&P S&P 10% (CS-1992)	1/16th 65% S&P S&P 10% (CS-1992)	1/16th 65% S&P S&P 10% (CS-1992)	1/16th 65% S&P S&P 10% (CS-1992)	1/16th 65% S&P S&P 10% (CS-1992)	1/16th 65% S&P S&P 10% (CS-1992)	1/16th 65% S&P S&P 10% (CS-1992)	1/16th 65% S&P S&P 10% (CS-1992)	1/16th 65% S&P S&P 10% (CS-1992)	1/16th 65% S&P S&P 10% (CS-1992)	1/16th 65% S&P S&P 10% (CS-1992)	1/16th 65% S&P S&P 10% (CS-1992)	1/16th 65% S&P S&P 10% (CS-1992)	1/16th 65% S&P S&P 10% (CS-1992)	1/16th 65% S&P S&P 10% (CS-1992)	1/16th 65% S&P S&P 10% (CS-1992)	1/16th 65% S&P S&P 10% (CS-1992)	1/16th 65% S&P S&P 10% (CS-1992)	1/16th 65% S&P S&P 10% (CS-1992)	1/16th 65% S&P S&P 10% (CS-1992)	1/16th 65% S&P S&P 10% (CS-1992)	1/16th 65% S&P S&P 10% (CS-1992)	1/16th 65% S&P S&P 10% (CS-1992)	1/16th 65% S&P S&P 10% (CS-1992)	1/16th 65% S&P S&P 10% (CS-1992)	1/16th 65% S&P S&P 10% (CS-1992)	1/16th 65% S&P S&P 10% (CS-1992)	1/16th 65% S&P S&P 10% (CS-1992)	1/16th 65% S&P S&P 10% (CS-1992)	1/16th 65% S&P S&P 10% (CS-1992)	1/16th 65% S&P S&P 10% (CS-1992)	1/16th 65% S&P S&P 10% (CS-1992)	1/16th 65% S&P S&P 10% (CS-1992)	1/16th 65% S&P S&P 10% (CS-1992)	1/16th 65% S&P S&P 10% (CS-1992)	1/16th 65% S&P S&P 10% (CS-1992)	1/16th 65% S&P S&P 10% (CS-1992)	1/16th 65% S&P S&P 10% (CS-1992)	1/16th 65% S&P S&P 10% (CS-1992)	1/16th 65% S&P S&P 10% (CS-1992)	1/16th 65% S&P S&P 10% (CS-1992)	1/16th 65% S&P S&P 10% (CS-1992)	1/16th 65% S&P S&P 10% (CS-1992)	1/16th 65% S&P S&P 10% (CS-1992)	1/16th 65% S&P S&P 10% (CS-1992)	1/16th 65% S&P S&P 10% (CS-1992)	1/16th 65% S&P S&P 10% (CS-1992)	1/16th 65% S&P S&P 10% (CS-1992)	1/16th 65% S&P S&P 10% (CS-1992)	1/16th 65% S&P S&P 10% (CS-1992)	1/16th 65% S&P S&P 10% (CS-1992)	1/16th 65% S&P S&P 10% (CS-1992)	1/16th 65% S&P S&P 10% (CS-1992)	1/16th 65% S&P S&P 10% (CS-1992)	1/16th 65% S&P S&P 10% (CS-1992)	1/16th 65% S&P S&P 10% (CS-1992)	1/16th 65% S&P S&P 10% (CS-1992)	1/16th 65% S&P S&P 10% (CS-1992)	1/16th 65% S&P S&P 10% (CS-1992)	1/16th 65% S&P S&P 10% (CS-1992)	1/16th 65% S&P S&P 10% (CS-1992)	1/16th 65% S&P S&P 10% (CS-1992)	1/16th 65% S&P S&P 10% (CS-1992)	1/16th 65% S&P S&P 10% (CS-1992)	1/16th 65% S&P S&P 10% (CS-1992)	1/16th 65% S&P S&P 10% (CS-1992)	1/16th 65% S&P S&P 10% (CS-1992)	1/16th 65% S&P S&P 10% (CS-1992)	1/16th 65% S&P S&P 10% (CS-1992)	1/16th 65% S&P S&P 10% (CS-1992)	1/16th 65% S&P S&P 10% (CS-1992)	1/16th 65% S&P S&P 10% (CS-1992)	1/16th 65% S&P S&P 10% (CS-1992)	1/16th 65% S&P S&P 10% (CS-1992)	1/16th 65% S&P
---------	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--------------------

SHEAR WALL SCHEDULE - 2001 WOOD FRAMED CONSTRUCTION MANUAL (WFCM)


MARK	TYPE	CAPACITY	DESCRIPTION
SP-1	ALUM. STRAIN BELL, 1/2 IN. DIA. (2.5 IN.)	448 BT	1/16" RSS STRAINING ATTACHED TO TUBES (RIGID) WITH 0.13 IN. Δ - Δ - Δ MILES & 6" OF 0.10 IN. 200 STRAIN. MESHES IN ALL BENDERS RIGID. SIZES: (0.01-1/16" 176.53) & 0.2 IN. 41.00S, 12' 0/16"
SP-2	ALUM. STRAIN BELL, 1/2 IN. DIA. (2.5 IN.)	560 BT	1/16" RSS STRAINING ATTACHED TO TUBES (RIGID) WITH 0.13 IN. Δ - Δ - Δ MILES & 0.10 IN. 200 STRAIN. MESHES IN ALL BENDERS RIGID. SIZES: (0.01-1/16" 176.53) & 0.2 IN. 41.00S, 12' 0/16"
SP-3	ALUM. STRAIN BELL, 1/2 IN. DIA. (2.5 IN.)	255 BT	1/16" RSS STRAINING ATTACHED TO TUBES (RIGID) WITH 0.13 IN. Δ - Δ - Δ MILES & 0.10 IN. 200 STRAIN. MESHES IN ALL BENDERS RIGID. SIZES: (0.01-1/16" 176.53) & 0.2 IN. 41.00S, 12' 0/16"
SP-4	STAIN. WELDED BELL, 1/2 IN. DIA. (2.5 IN.)	100 BT	1/2" STAIN. DOW. ATTACHED TO TUBES ONE SET (CONNECTED) WITH DOWN. SIZES: (0.01-1/16" 176.53) & 0.2 IN. 41.00S, 12' 0/16" AT INTERMEDIATE SUPPORTS AND END SUPPORTS. MESHING MESHES

1. ALL BRACED WALLS AND SHEAR WALLS ASSUME A CONTINUOUSLY SHEATHED STRUCTURE IN ACCORDANCE WITH REG. SECTION 602.10.5
2. ALL WALLS SHOWN HAVE BEEN REDUCED TO REFLECT A S.F.=0.43 FOR STUD FRAMING.
3. ALL HARDWARE SHALL BE INSTALLED IN ACCORDANCE WITH THE MANUFACTURERS INSTRUCTIONS.
4. REFERENCES ATTACHED DETAILS FOR PORTAL WALL FRAMING
5. FIELD WALLING SHALL BE AT 12" O.C. U.N.O.
6. BLOCK AT EDGES AT BRACED WALL PANELS ONLY

ALL HANGERS SHALL BE AS SPECIFIED BY TRUSS OR JOIST MFG., U.N.O.
(ALL HARDWARE SHALL BE AS MANUFACTURED BY SIMPSON STRONG TIE)

SINGLE FAMILY HOUSE

BUILDING CODE SUMMARY



1) WINDOWS TO BE 1 OVER 1 WOOD WINDOWS

NOTES

[illegible]

G LOADS

FINE PROTECTION REQUIREMENTS				
BUILDING ELEMENT	DRAINAGE		ROOF / FLOOR	
	REQUIRED	PROVIDED	YES	NO / FLOOR ASSEMBLY
STRUCTURAL FRAME	0	0	-	
BEARING WALLS	1	1	1	UL-1805
EXTENSION WALLS	0	0	-	
NON-BEARING WALLS	0	0	-	
CEILING	0	0	-	
INTERIOR	0	0	-	
CEILING CONSTRUCTION	0	0	-	
ROOF CONSTRUCTION	0	0	-	
SHUTS	-	-	-	
CONCRETE SEPARATION	-	-	-	
OCCUPANCY SEPARATION	-	-	-	
PLAY AREA WALL SEPARATION	1 OR 2	1	1	UL-1805 (INTERIOR) UL-1805 (EXTENSION)
SMOKE BARRIER SEPARATION	-	-	-	
ELEVATOR SEPARATION - HOIST	1	1	1	UL-2571

LIFE SAFETY SYSTEM REQUIREMENTS				
EMERGENCY ILLUMINANCE	YES	NO	YES	NO
EXIT SIGNS	YES	NO	YES	NO
EXIT ALARMS	YES	NO	YES	NO
SMOKE DETECTION SYSTEMS	YES	NO	YES	NO
SMOKE ALARMS	YES	NO	YES	NO

"STRUCTURAL PLANS CERTIFIED AS PROVIDED IN SECTION 106.1.4.1 OF THE DC CONSTRUCTION CODES SUPPLEMENT AS AMENDED TO DATE"


FINISHED SQUARE FEET:

BASEMENT = 781.33 S.F.
1ST FLOOR = 781.33 S.F.
2ND FLOOR = 781.33 S.F.
3RD FLOOR = 488.50 S.F.
TOTAL = 2,832.49 S.F.

PROPERTY ADDRESS

518 SIXTH STREET
WASHINGTON, DC 20002

**REDUX
PROPERTIES
LLC**



Mr. Kyubakov 25 str.
 Sofia, Bulgaria
 tel: +359 886 880069
 e-mail: construalbg@gmail.com


INITIAL DETAIL PRINT	15-02-0

[illegible]

PROJECT ADDRESS	518 Sixth Street WASHINGTON D.C. 20002
SHEET TITLE	Cover Sheet
DATE:	04/23/2015
PROJECT NUMBER	06
REDUX PROPERTIES LLC	

C-S.01

PROPOSED THIRD FLOOR PLAN
3/8" = 1'-0"




- 1) WINDOWS TO BE 2' OVER 2' WOOD WINDOWS
- 2) 8 FOOT SHAKER DOORS

PROPOSED SECOND FLOOR PLAN
3/8" = 1'-0"

10\" return 8x12
SURR UP 8x8 Return up
4\" up
4\" up

- NOTES:
- 1) WINDOWS TO BE 2' OVER 2' WOOD WINDOWS
 - 2) 8 FOOT SHAKER DOORS

53-84




PROPOSED FIRST FLOOR PLAN

SEPARATE ELECTRICAL, PLUMBING AND MECHANICAL
INSTALLATION PERMITS ARE REQUIRED.

THE GENERAL LAYOUT OF THE MECHANICAL SYSTEMS
AND/OR THE MECHANICAL EQUIPMENT SHOWN ON
THESE DRAWINGS HAS BEEN REVIEWED FOR
COMPLIANCE WITH THE APPLICABLE PROVISIONS OF
THE D.C. CONSTRUCTION CODES AND IS APPROVED.

5/17/20
Date
Mechanical Engineering Section

ALL MECHANICAL APPLIANCES SHALL
BE APPROVED BY THE AGENCY AND SHALL
BEAR THE LABEL OF AN APPROVED AGENCY AND LOCATION AND
SHALL BE INSTALLED IN ACCORDANCE WITH THE
MANUFACTURER'S INSTALLATION INSTRUCTIONS



NOTES

- 1) WINDOWS TO BE 2" OVER 2" WOOD WINDOWS
- 2) 8 FOOT SHAKER DOORS

PROPOSED BASEMENT FLOOR

PLAN

3/8" = 1'-0"

Multi-Port Packless

HP-1 - 4065AB09	.75 ton
HP-2 - 4065AB12	1 ton
Carrier	
OD-1 - 3865AD24	2 ton