


SATELLITE IMAGERY



SITE NAME:

OTIS

SITE NUMBER:

DC0002

SITE ADDRESS:

**1800 PERRY STREET NE
DISTRICT OF COLUMBIA, DC 20018**

STRUCTURE:

100 FT MONOPOLE

INDEX OF SHEETS		
SHEET	DESCRIPTION	REV
T-1	TITLE SHEET	1
N-1	PROJECT NOTES	0
N-2	INSPECTION NOTES	0
S-1	TOWER ELEVATION & MODIFICATION SCHEDULE	1
S-2	CONSTRUCTION DETAILS	0
S-3	CONSTRUCTION DETAILS	0
S-4	CONSTRUCTION DETAILS	0

PROJECT INFORMATION		
STRUCTURE TYPE:	MONOPOLE	
STRUCTURE HEIGHT:	100 FT	
LATITUDE:	N 38.935498	
LONGITUDE:	W 76.977808	
COUNTY:	DISTRICT OF COLUMBIA COUNTY	
CODE JURISDICTION:	DISTRICT OF COLUMBIA	
CONSTRUCTION SCOPE:	EXTENSION DESIGN DRAWINGS	

BUILDING CODE CRITERIA		
BUILDING CODE:	2017 DISTRICT OF COLUMBIA BUILDING CODE	
ULTIMATE WIND SPEED, Vult:	113 MPH	
RISK CATEGORY:	II	
EXPOSURE CATEGORY:	C	
TOPOGRAPHIC CATEGORY:	1	
SEISMIC DESIGN PARAMETERS:	Ss = 0.133g S1 = 0.043g SITE CLASS: D SDC: B	
CORRESPONDING STRUCTURAL ANALYSIS REPORT:		
KIMLEY-HORN, JOB #012628109 / KHRAL-20552, DATED 10/16/24		

SCOPE OF WORK		
1. COMPLETE STRUCTURAL DESIGN DETAILS CAN BE FOUND ON THE FOLLOWING S-SHEETS.		
2. THE CONTRACTOR IS RESPONSIBLE FOR CONFIRMING ALL EXISTING STRUCTURE DIMENSIONS, SITE CONSTRAINTS, POTENTIAL INSTALLATION INTERFERENCES, FACILITY UTILITIES, AND ALL OTHER INFORMATION NECESSARY TO COMPLETE THE INSTALLATION OF THE STRUCTURE DETAILED IN THESE DRAWINGS. THE CONTRACTOR SHALL NOT BEGIN FABRICATION OR CONSTRUCTION PRIOR TO PERFORMING THIS SITE VISIT AND ENSURING THE INSTALLATION CAN BE COMPLETED AS SHOWN.		
3. ALL INTERFERENCES OR DEFICIENCIES OBSERVED PRIOR TO OR DURING CONSTRUCTION SHALL BE REPORTED TO THE CUSTOMER AND ENGINEER OF RECORD IMMEDIATELY FOR EVALUATION OF IMPACTS TO THE PROPOSED DESIGN.		
4. UPON COMPLETION OF THE INSTALLATION, THE ENGINEER OF RECORD SHALL BE NOTIFIED IN ORDER TO PERFORM A POST-INSTALLATION INSPECTION (PII).		






PROJECT INFORMATION:

OTIS
DC0002

1800 PERRY STREET NE
DISTRICT OF COLUMBIA, DC 20018
DISTRICT OF COLUMBIA COUNTY

PLANS PREPARED BY:

Kimley-Horn | DC
421 FAYETTEVILLE STREET, SUITE 600
RALEIGH, NC 27601
PHONE: 919-677-2000
WWW.KIMLEY-HORN.COM
DC COA #N/A



1.00 GENERAL NOTES

- ALL MATERIALS AND WORKMANSHIP SHALL CONFORM TO THE DRAWINGS AND SPECIFICATIONS. ALL WORK SHALL BE DONE IN ACCORDANCE WITH THE LATEST EDITION OF THE STATE, LOCAL AND NATIONAL CODES, ORDINANCES AND OR REGULATIONS APPLICABLE TO THIS PROJECT. SEE SHEET T-1 FOR APPLICABLE BUILDING CODES.
- THE CONTRACTOR SHALL BE RESPONSIBLE FOR COORDINATING WITH WORK OF ALL TRADES AND SHALL CHECK ALL DIMENSIONS. ALL DISCREPANCIES SHALL BE CALLED TO THE ATTENTION OF THE PROJECT MANAGER AND/OR ENGINEER AND BE RESOLVED BEFORE PROCEEDING WITH WORK WHERE THERE IS A CONFLICT BETWEEN DRAWING AND SPECIFICATIONS.
- ALL INFORMATION SHOWN ON THE DRAWINGS RELATIVE TO EXISTING CONDITIONS IS GIVEN AS THE BEST PRESENT KNOWLEDGE, BUT WITHOUT GUARANTEE OF ACCURACY. WHERE ACTUAL CONDITIONS CONFLICT WITH THE DRAWINGS, THEY SHALL BE REPORTED TO THE PROJECT MANAGER AND/OR ENGINEER OF RECORD SO THAT PROPER REVISIONS MAY BE MADE. MODIFICATION OF DETAILS OR CONSTRUCTION SHALL NOT BE MADE WITHOUT WRITTEN APPROVAL OF THE PROJECT MANAGER AND/OR ENGINEER OF RECORD.
- CONTRACTOR SHALL REVIEW AND BE FAMILIAR WITH SITE CONDITIONS AS SHOWN ON THE ATTACHED SITE PLAN AND/OR SURVEY DRAWINGS.
- CONTRACTOR TO PROVIDE DUMPSTER AND PORTABLE TOILET FACILITY DURING CONSTRUCTION.
- CONSTRUCTION WASTE MAY NEITHER BE BURNED NOR BURIED AND MUST BE TAKEN TO AN APPROVED LANDFILL.
- SECURITY TO THE SITE SHALL BE MAINTAINED AT ALL TIMES.

2.00 STRUCTURAL STEEL NOTES

- STRUCTURAL STEEL SHALL COMPLY WITH THE FOLLOWING MATERIAL SPECIFICATIONS, AT MINIMUM (UNLESS NOTED OTHERWISE - U.N.O.):

- A. STRUCTURAL STEEL SHAPES:
W-SHAPES: ASTM A992 (Fy=50 KSI)
ALL OTHERS ASTM A36 (Fy=36 KSI)
- B. PIPES: ASTM A53, GRADE B (Fy=35 KSI)
- C. HSS-SHAPES: ASTM A500, GRADE B
(ROUND - Fy = 42 KSI)
(RECTANGULAR - Fy = 46 KSI)
- D. ANCHOR & ALL THREAD RODS: ASTM F1554 GR 55 (Fy = 55 KSI)
- E. STRUCTURAL BOLTS $\frac{1}{2}$ " AND LARGER: ASTM F3125 GR A325
- F. STRUCTURAL BOLTS SMALLER THAN $\frac{1}{2}$ "
DIMENSIONS: ASME B18.2.1
MATERIAL: SAE J429 GRADE 5
THREADING: ASME B1.1, UNC, CLASS 2A
FINISH: H.D.G. OR ZINC-PLATE
- G. STRUCTURAL U-BOLTS $\frac{3}{4}$ " AND SMALLER: ASTM A307 GRADE A
- H. NUTS FOR BOLTS/ALL-THREAD: ASTM A563
(THREADING TO MATCH BOLT)
- I. WASHERS FOR BOLTS/ALL THREADS: ASTM F436

- ALL PROPOSED STEEL MEMBERS, PLATES AND ASSEMBLIES SHALL BE HOT DIP GALVANIZED (H.D.G) IN ACCORDANCE WITH ASTM A123, UNLESS NOTED OTHERWISE.

- STRUCTURAL BOLTS SHALL CONFORM TO THIS NOTE. ALL BOLT HOLES SHALL BE STANDARD SIZE BOLT HOLES PER AISC 360, UNLESS NOTED OTHERWISE. ALL HOLES SHALL BE SHOP DRILLED OR SUB-PUNCHED AND REAMED. BURNING OF HOLES IS NOT PERMITTED, WHERE SLOTTED OR OVERRSIZE HOLES ARE SPECIFIED ON THE DRAWINGS, EXTRA-THICK ASTM F436 PLATE WASHERS SHALL BE USED ($\frac{5}{16}$ " MINIMUM THICKNESS) WITH A DIAMETER SUITABLE TO COVER THE EXTENTS OF THE SLOT OF HOLE. BOLTS SHALL BE HEAVY-HEX WHERE AVAILABLE IN THE SIZE AND GRADE SPECIFIED. ALL BOLT ASSEMBLIES SHALL BE TIGHTENED PER AISC "TURN-OF-THE-NUT" METHOD. SEE SECTION 5.00.

- ALL STEEL HARDWARE, INCLUDING ADHESIVE OR EMBEDDED ANCHOR BOLTS AND THEIR ACCESSORIES, SHALL BE HOT-DIP GALVANIZED IN ACCORDANCE WITH ASTM A153 (EXCEPT A490 SPECIFICATIONS WHICH SHALL CONFORM TO ASTM F2833, AND BOLTS SMALLER THAN $\frac{1}{2}$ " WHICH SHALL CONFORM TO FE/ZN 3 AS PER ASTM F1941, AND HOT-DIP GALVANIZED IN ACCORDANCE WITH ASTM A123). REPAIR ALL DAMAGE DUE TO TRANSPORTATION, CUTTING, OR WELDING WITH GALVANIZED COATINGS USING ASTM A780 PROCEDURES WITH ZINC RICH PAINT (SUCH AS ZRC GALVILITE). CALL OUT HOLES REQUIRED FOR HOT-DIP GALVANIZING ON SHOP DRAWINGS.

- WELDING SHALL BE IN ACCORDANCE WITH AWS D1.1 "STRUCTURAL WELDING CODE - STEEL". UNLESS NOTED OTHERWISE, WELD ELECTRODES SHALL BE 70 KSI. UNLESS NOTED OTHERWISE, PROVIDE CONTINUOUS FILLET WELDS WITH MINIMUM SIZE OF $\frac{3}{16}$ " OR OF A SIZE EQUAL TO THE THICKNESS OF THE THINNER MATERIAL. WELD LEG SIZE SHALL BE ADJUSTED AS REQUIRED TO MAINTAIN THE EFFECTIVE THROAT OF A $\frac{3}{16}$ " FILLET WELD IN A 90° JOINT. ALL WELD SIZES SHOWN IN INCHES.

- PRIOR TO WELDING, THE CONTRACTOR SHALL SUBMIT CERTIFICATION FOR EACH WELDER STATING THE TYPE OF WELDING AND POSITIONS QUALIFIED FOR, THE CODE AND PROCEDURE QUALIFIED UNDER, STATE QUALIFIED, AND THE FIRM AND INDIVIDUAL CERTIFYING THE QUALIFICATION TESTS. THIS INFORMATION SHALL BE SUBMITTED TO THE MODIFICATION INSPECTOR (SEE SHEET N-2 "CONSTRUCTION INSPECTION CHECKLIST") AS WELL AS ANY THIRD-PARTY CERTIFIED WELD INSPECTOR (CW).

- ALL PROPOSED PARTS AND MEMBERS SHALL BE SHOP-FABRICATED AND WELDED TO THE EXTENT PRACTICABLE IN ORDER TO REDUCE FIELD INSTALLATION COSTS.

3.00 MODIFICATION NOTES

- THESE MODIFICATIONS HAVE BEEN DESIGNED IN ACCORDANCE WITH THE GOVERNING PROVISIONS OF TIA/EIA-222, ASCE 7, AWS, ACI, AND AISC. MATERIALS AND SERVICES PROVIDED BY THE CONTRACTOR SHALL CONFORM TO THE ABOVE MENTIONED CODES AND CONTRACT SPECIFICATIONS.
- ALL MATERIALS UTILIZED FOR THIS PROJECT MUST BE NEW AND FREE OF ANY DEFECTS.
- ALL PRODUCT OR MATERIAL SUBSTITUTIONS PROPOSED BY THE CONTRACTOR SHALL BE APPROVED IN WRITING BY THE ENGINEER OF RECORD. CONTRACTOR SHALL PROVIDE DOCUMENTATION TO ENGINEER SUITABLE TO DETERMINE IF THE SUBSTITUTE IS ACCEPTABLE FOR USE AND MEETS THE ORIGINAL DESIGN CRITERIA. DIFFERENCES FROM THE ORIGINAL DESIGN, INCLUDING MAINTENANCE, REPAIR, AND REPLACEMENT, SHALL BE NOTED. ESTIMATES OF COSTS/CREDITS ASSOCIATED WITH THE SUBSTITUTION (INCLUDING RE-DESIGN COSTS AND COSTS TO SUB-CONTRACTORS) SHALL BE PROVIDED TO THE ENGINEER. CONTRACTOR SHALL PROVIDE ADDITIONAL DOCUMENTATION AND/OR SPECIFICATION TO THE ENGINEER AS REQUESTED.
- PROVIDE STRUCTURAL STEEL SHOP DRAWINGS(S) TO THE ENGINEER OF RECORD FOR APPROVAL PRIOR TO FABRICATION.
- UNLESS NOTED OTHERWISE, ALL NEW MEMBERS AND REINFORCING SHALL MAINTAIN THE EXISTING MEMBER WORK AND NOT INTRODUCE ECCENTRICITIES INTO THE STRUCTURE.
- ANY CONTRACTOR-CAUSED DAMAGE TO PROPERTY OF THE LAND OWNER, PROPERTY OF THE CUSTOMER, SITE FENCING OR GATES, ANY AND ALL UTILITY AND/OR SERVICE LINES, SHOWN OR NOT SHOWN ON THE PLANS SHALL BE REPAIRED OR REPLACED AT THE SOLE COST OF THE CONTRACTOR AND SHALL BE ADDRESSED BY THE CONTRACTOR WITH THE COMPANIES THAT OWN THE DAMAGED ITEMS.

4.00 CONTRACTOR NOTES

- PRIOR TO BEGINNING CONSTRUCTION, ALL CONTRACTORS AND SUBCONTRACTORS MUST ACKNOWLEDGE IN WRITING TO STRUCTURE OWNER THAT THEY HAVE OBTAINED, UNDERSTAND, AND WILL FOLLOW STRUCTURE OWNER STANDARDS OF PRACTICE, CONSTRUCTION GUIDELINES, ALL SITE AND STRUCTURE SAFETY PROCEDURES, ALL PRODUCT LIMITATIONS AND INSTALLATION PROCEDURES USED ON SITE, AND PROPOSED MODIFICATION DESCRIBED RECEIPT OF ACKNOWLEDGEMENT MUST OCCUR PRIOR TO BEGINNING CONSTRUCTION OR CLIMBING. IT IS THE RESPONSIBILITY OF THE GENERAL CONTRACTOR TO PROVIDE THE DOCUMENTATION FOR STRUCTURE OWNER ON COMPANY LETTERHEAD AND THE RESPONSIBILITY OF THE GENERAL CONTRACTOR TO OBTAIN THIS DOCUMENTATION FROM ANY SUBCONTRACTORS (ON SUBCONTRACTOR LETTERHEAD) AND DELIVER IT TO THE STRUCTURE OWNER.
- IF THE CONTRACTOR DISCOVERS ANY EXISTING CONDITIONS THAT ARE NOT REPRESENTED ON THESE DRAWINGS, OR ANY CONDITIONS THAT WOULD INTERFERE WITH THE INSTALLATION OF THE MODIFICATIONS, THE ENGINEER OF RECORD SHALL BE CONTACTED IMMEDIATELY TO EVALUATE THE SIGNIFICANCE OF THE DEVIATION.
- THE CONTRACTOR SHALL SOLICIT AND HIRE THE SERVICES OF A QUALIFIED MODIFICATIONS INSPECTOR PRIOR TO BEGINNING CONSTRUCTION, THE MODIFICATION INSPECTOR MAY BE AN EMPLOYEE OF THE CONTRACTOR'S FIRM; HOWEVER, THE INSPECTOR'S ONLY DUTIES SHALL BE INSPECTION, TESTING, AND REPORT CREATION AS REQUIRED ON THE "MODIFICATION INSPECTION NOTES" SHEET. IT IS ALSO ACCEPTABLE FOR THE CONTRACTOR TO SUBCONTRACT THE MODIFICATION INSPECTOR DUTIES TO A THIRD PARTY FIRM MEETING THE ABOVE REQUIREMENTS.
- THE CONTRACTOR SHALL NOTIFY THE ENGINEER OF RECORD AND TOWER OWNER OF THE PLANNED CONSTRUCTION & INSPECTION SCHEDULE, AS WELL AS ANY CHANGES TO THE SCHEDULE, WITHIN TWO BUSINESS DAYS OF COMPLETION OF THE SCHEDULE REVISION BOTH PRIOR TO BEGINNING CONSTRUCTION AND DURING CONSTRUCTION AS THE SCHEDULE CHANGES. THE CONTRACTOR SHALL NOTIFY THE ENGINEER OF RECORD WHEN PHASES OF CONSTRUCTION HAVE BEEN MOVED UP AND SHALL GIVE THE ENGINEER ADEQUATE NOTICE SO THE ENGINEER OF RECORD MAY, AT THEIR DISCRETION, INSPECT PORTIONS OF THE WORK DEEMED CRITICAL TO THE INTEGRITY OF THE STRUCTURE. FAILURE TO PROVIDE THIS NOTICE MAY RESULT IN REJECTION OF THE CONTRACTOR'S WORK. THE CONTRACTOR SHALL ALSO NOTIFY THE ENGINEER OF RECORD AND THE STRUCTURE OWNER WHEN THE WORK HAS BEEN COMPLETED WITHIN 2 BUSINESS DAYS OF THE COMPLETION OF THE WORK AND ASSOCIATED MODIFICATION INSPECTIONS & TESTING.
- IT IS ASSUMED THAT ANY STRUCTURAL MODIFICATION WORK SPECIFIED IN THESE PLANS WILL BE ACCOMPLISHED BY KNOWLEDGEABLE WORKMEN WITH TOWER/BUILDING CONSTRUCTION EXPERIENCE. THIS INCLUDES PROVIDING THE NECESSARY CERTIFICATIONS TO THE STRUCTURE OWNER AND ENGINEER INCLUDING BUT NOT LIMITED TO QUALIFIED WELDER CERTIFICATES, CERTIFIED WELDING INSPECTOR CREDENTIALS, ET CETERA.
- THESE DRAWINGS DO NOT INDICATE THE METHOD OF CONSTRUCTION, THE CONTRACTOR SHALL SUPERVISE AND DIRECT THE WORK AND SHALL BE SOLELY RESPONSIBLE FOR ALL CONSTRUCTION METHODS, MEANS, TECHNIQUES, SEQUENCES AND PROCEDURES.
- CONTRACTOR SHALL WORK WITHIN THE LIMITS OF THE STRUCTURE OWNER'S PROPERTY OF LEASE AREA AND APPROVED EASEMENT. IT IS THE RESPONSIBILITY OF THE CONTRACTOR TO VERIFY WORK IS WITHIN THESE BOUNDARIES. CONTRACTOR SHALL EMPLOY A SURVEYOR AS REQUIRED. ANY WORK OUTSIDE THESE BOUNDARIES SHALL BE APPROVED IN WRITING BY THE LAND OWNER PRIOR TO MOBILIZATION. CONSTRUCTION STAKING AND BOUNDARY MARKING IS THE RESPONSIBILITY OF THE CONTRACTOR.
- DO NOT SCALE DRAWINGS. CONTRACTOR SHALL VERIFY ALL PLANS, EXISTING DIMENSIONS, CONDITIONS ON THE JOB SITE AND SHALL IMMEDIATELY NOTIFY THE ARCHITECT OR ENGINEER IN WRITING OF ANY DISCREPANCIES BEFORE PROCEEDING WITH THE WORK OR BE RESPONSIBLE FOR THE SAME.

5.00 BOLT TIGHTENING PROCEDURE


- TIGHTEN BOLTS PER AISC - "TURN OF THE NUT" METHOD, USING THE CHART BELOW:

BOLT LENGTHS UP TO & INCLUDING 4 ϕ	+1/3 TURN BEYOND SNUG TIGHT
$\frac{5}{8}$ " BOLTS UP TO & INCLUDING 2 $\frac{1}{2}$ " LENGTH	+1/3 TURN BEYOND SNUG TIGHT
$\frac{3}{4}$ " BOLTS UP TO & INCLUDING 3" LENGTH	+1/3 TURN BEYOND SNUG TIGHT
$\frac{7}{8}$ " BOLTS UP TO & INCLUDING 3 $\frac{1}{2}$ " LENGTH	+1/3 TURN BEYOND SNUG TIGHT
1" BOLTS UP TO & INCLUDING 4" LENGTH	+1/3 TURN BEYOND SNUG TIGHT
$1\frac{1}{8}$ " BOLTS UP TO & INCLUDING 4 $\frac{1}{2}$ " LENGTH	+1/3 TURN BEYOND SNUG TIGHT
$1\frac{1}{4}$ " BOLTS UP TO & INCLUDING 5" LENGTH	+1/3 TURN BEYOND SNUG TIGHT
$1\frac{1}{2}$ " BOLTS UP TO & INCLUDING 6" LENGTH	+1/3 TURN BEYOND SNUG TIGHT

BOLT LENGTH OVER 4 ϕ BUT NOT EXCEEDING 8 ϕ	+1/2 TURN BEYOND SNUG TIGHT
$\frac{3}{4}$ " BOLTS 4.25" TO 6.0" LENGTH	+1/2 TURN BEYOND SNUG TIGHT
$\frac{7}{8}$ " BOLTS 3.75" TO 7.0" LENGTH	+1/2 TURN BEYOND SNUG TIGHT
1" BOLTS 4.25" TO 8.0" LENGTH	+1/2 TURN BEYOND SNUG TIGHT
$1\frac{1}{8}$ " BOLTS 4.75" TO 9.0" LENGTH	+1/2 TURN BEYOND SNUG TIGHT
$1\frac{1}{4}$ " BOLTS 5.25" TO 10.0" LENGTH	+1/2 TURN BEYOND SNUG TIGHT
$1\frac{1}{2}$ " BOLTS 6.25" TO 12.0" LENGTH	+1/2 TURN BEYOND SNUG TIGHT



BEFORE 1/3 TURN



AFTER 1/3 TURN


- SPICE BOLTS SUBJECT TO DIRECT TENSION SHALL BE INSTALLED AND TIGHTENED AS PER SECTION 8(d)(1) OF THE AISC MANUAL OF STEEL CONSTRUCTION. THE INSTALLATION PROCEDURE IS PARAPHRASED AS FOLLOWS:

"FASTENERS SHALL BE INSTALLED IN PROPER ALIGNED HOLES AND BE TIGHTENED BY ONE OF THE METHODS DESCRIBED IN SUBSECTION 8(d)(1) THROUGH 8(d)(4)."

8(d)(1) TURN-OF-THE-NUT TIGHTENING

BOLTS SHALL BE INSTALLED IN ALL HOLES OF THE CONNECTION AND BROUGHT TO A SNUG TIGHT CONDITION. SNUG TIGHT IS DEFINED AS THE TIGHTNESS THAT EXISTS WHEN THE PLIES OF A JOINT ARE IN FIRM CONTACT. THIS MAY BE OBTAINED BY A FEW IMPACTS OF AN IMPACT WRENCH OR THE FULL EFFORT OF A MAN USING AN ORDINARY SPUD WRENCH. SNUG TIGHTENING SHALL PROGRESS SYSTEMATICALLY UNTIL ALL THE BOLTS ARE SIMULTANEOUSLY SNUG TIGHT AND THE CONNECTION IS FULLY COMPACTED. FOLLOW THIS INITIAL OPERATION ALL BOLTS IN THE CONNECTION SHALL BE TIGHTENED FURTHER BY THE APPLICABLE AMOUNT OF ROTATION OF THE PART NOT TURNED BY THE WRENCH. TIGHTENING SHALL PROGRESS SYSTEMATICALLY

SPACER PLATE



WORKABLE GAGES


LEG WIDTH	4	3 1/2	3	1/2	2	1 1/4
GAGE	2 1/2	2	1 3/4	1 1/8	1 1/8	1

- WORKABLE GAGES
GIVEN IN INCHES
- MATCH EXISTING
WHEN APPLICABLE

NOMINAL HOLE DIMS

BOLT ϕ	STANDARD HOLE ϕ	SHORT SLOT
$\frac{1}{2}$ "	$\frac{9}{16}$ "	$\frac{9}{16}$ " x $\frac{1}{16}$ "
$\frac{5}{8}$ "	$\frac{13}{16}$ "	$\frac{13}{16}$ " x $\frac{1}{16}$ "
$\frac{3}{4}$ "	$\frac{13}{16}$ "	$\frac{13}{16}$ " x 1"
$\frac{7}{8}$ "	$\frac{15}{16}$ "	$\frac{15}{16}$ " x $\frac{1}{16}$ "
1"	$\frac{1}{2}$ "	$\frac{1}{2}$ " x $\frac{1}{16}$ "
$1\frac{1}{8}$ "	$\frac{1}{4}$ "	$\frac{1}{4}$ " x $\frac{1}{2}$ "
$1\frac{1}{4}$ "	$\frac{13}{16}$ "	$\frac{13}{16}$ " x $\frac{1}{16}$ "

ALLOWABLE ANGLE COPE



BOLT EDGE & SPACING (UNO)

BOLT ϕ	EDGE DISTANCE	SPACING
$\frac{1}{2}$ "	$\frac{7}{8}$ "	$\frac{1}{2}$ "
$\frac{5}{8}$ "	$\frac{1}{2}$ "	$\frac{1}{2}$ "
$\frac{3}{4}$ "	$\frac{1}{4}$ "	$\frac{2}{3}$ "
$\frac{7}{8}$ "	$\frac{1}{2}$ "	$\frac{2}{3}$ "
1"	$\frac{13}{16}$ "	3"



1.00 GENERAL INSPECTION NOTES

1.01 THE POST-MODIFICATION INSPECTION IS A VISUAL EXAMINATION OF STRUCTURE MODIFICATIONS AND A REVIEW OF ANY REQUIRED CONSTRUCTION INSPECTIONS, TESTING, AND OTHER DATA TO VERIFY THAT THE MODIFICATIONS ARE INSTALLED IN ACCORDANCE WITH THE CONTRACT DOCUMENTS AS DESIGNED BY THE ENGINEER OF RECORD. THE CONTRACTOR DOCUMENTS INCLUDE THESE MODIFICATION DRAWINGS, ANY PROJECT SPECIFICATION REFERENCED TO IN THE PROJECT NOTES OR OTHERWISE PROVIDED WITH THE DRAWINGS, AND OTHER DOCUMENTS OR DRAWINGS PROVIDED WITH THE MODIFICATION DRAWINGS WITH THE INTENT THEY BE USED AS A DESIGN AID OR GUIDELINE FOR CONSTRUCTION.

1.02 THE POST-MODIFICATION INSPECTION SHALL CONFIRM INSTALLATION CONFIGURATION AND WORKMANSHIP ONLY AND IS NOT A QUALITATIVE REVIEW OF THE ENGINEERING ASPECTS OF THE DESIGN OR THE DESIGN DRAWINGS. THE MODIFICATION INSPECTOR IS NOT TAKING OWNERSHIP OF THE MODIFICATION DESIGN IN THE PERFORMANCE OF THEIR DUTIES. OWNERSHIP OF THE MODIFICATION DESIGN'S EFFECTIVENESS AND INTENT, AS WELL AS ALL ASSOCIATED RISK, LIES WITH THE ENGINEER OF RECORD AT ALL TIMES.

1.03 TO ENSURE THE REQUIREMENTS OF THE POST-MODIFICATION INSPECTION ARE MET, IT IS ESSENTIAL COORDINATION BETWEEN THE PRIME CONTRACTOR AND THE MODIFICATION INSPECTOR BEING AS SOON AS THE PROJECT IS FUNDED AND WORK ENTERS THE PLANNING STAGE. THE PRIME CONTRACTOR AND MODIFICATION INSPECTOR SHALL BE PROACTIVE IN IDENTIFYING CONSTRUCTION ISSUES AND COMMUNICATE THESE ISSUES TO EACH OTHER AND THE ENGINEER OF RECORD AND STRUCTURE OWNER & CUSTOMER, AS REQUIRED.

2.00 INSPECTION & REPORT RECOM'S

2.01 THE FOLLOWING ARE PROVIDED WITH THE INTENT OF ENHANCING THE EFFECTIVENESS OF THE MODIFICATION INSPECTIONS AND IMPROVING THE EFFICIENCY OF THE PROCESS OF COLLECTING AND COMPILED THE INFORMATION INTO A USEABLE REPORT:

- IT IS RECOMMENDED THE PRIME CONTRACTOR PROVIDE THE MODIFICATION INSPECTOR AT LEAST 5 BUSINESS DAYS NOTICE FOR WHEN THE SITE WILL BE READY FOR THE MODIFICATION INSPECTION.
- THE PRIME CONTRACTOR AND THE MODIFICATION INSPECTOR SHALL COORDINATE CLOSELY THROUGHOUT THE ENTIRE PROJECT.
- THE PRIME CONTRACTOR AND MODIFICATION INSPECTOR SHALL BOTH BE PRESENT DURING THE INITIAL INSPECTIONS IN ORDER TO ALLOW FOR THE REMEDIATION OF DEFICIENCIES DURING THE INSPECTIONS, AS PRACTICABLE. IT MAY BE PREFERABLE TO KEEP WORK CREWS AND THEIR EQUIPMENT ON-SITE TO REMEDIATE DEFICIENCIES DURING INSPECTIONS.

3.00 INSPECTION RESCHEDULE & CANCEL

3.01 IF THE PRIME CONTRACTOR AND MODIFICATION INSPECTOR HAVE AGREED UPON A TIME AND DATE FOR A GIVEN INSPECTION AND EITHER PARTY RESCHEDULES OR CANCELS THE INSPECTION, THE STRUCTURE OWNER SHALL NOT BE RESPONSIBLE FOR COSTS, FEES, LOST DEPOSITS, OR OTHER EXPENSES INCURRED BY THE PRIME CONTRACTOR, THEIR SUBCONTRACTOR(S), OR THE MODIFICATION INSPECTOR DUE TO THESE SCHEDULING CHANGES. EXCEPTIONS MAY BE MADE IN THE EVENT OF UNCONTROLLABLE SITUATIONS SUCH AS NATURAL DISASTERS, SEVERE WEATHER, OR OTHER CONDITIONS THAT COMPROMISE THE SAFETY OF THE PARTIES INVOLVED.

4.00 REMEDIATION OF FAILING INSPECTION

4.01 IN THE EVENT ANY PORTION OF THE MODIFICATION WORK IS DETERMINED TO BE UNSATISFACTORY BY THE MODIFICATION INSPECTOR, THE PRIME CONTRACTOR SHALL WORK WITH THE MODIFICATION INSPECTOR TO CREATE A PLAN OF ACTION THAT WILL EITHER:

- REPAIR THE DEFICIENT WORK TO SATISFACTORY CONDITION AND INCLUDE A SUBSEQUENT RE-INSPECTION OF THE WORK TO VERIFY IT IS SATISFACTORY.
- OR, WITH THE PERMISSION OF THE STRUCTURE OWNER AND/OR CUSTOMER, THE PRIME CONTRACTOR MAY WORK WITH THE ENGINEER OF RECORD TO REVIEW THE AS-BUILT CONDITION OF THE MODIFICATION TO DETERMINE IF IT IS STRUCTURALLY ACCEPTABLE. IF THE ACTION IS NOT ACCEPTABLE TO ANY PARTY, THE PRIME CONTRACTOR SHALL PROCEED TO REPAIR THE DEFICIENT WORK TO A SATISFACTORY CONDITION.

5.00 OWNER INSPECTIONS

5.01 THE STRUCTURE OWNER MAY CONDUCT INSPECTIONS TO VERIFY THE QUALITY AND COMPLETENESS OF THE PREVIOUSLY COMPLETED MODIFICATION INSPECTIONS REPORTS OR THE MODIFICATION INSTALLATION WORK.

5.02 INSPECTIONS MAY BE COMPLETED BY A 3RD-PARTY FIRM OF THE STRUCTURE OWNER'S CHOOSING AFTER A MODIFICATION PROJECT IS COMPLETED AND A PASSING MODIFICATION INSPECTION REPORT IS ISSUED.

6.00 MOD INSPECTOR'S RESPONSIBILITIES

6.01 THE MODIFICATION INSPECTOR SHALL CONTACT THE PRIME CONTRACTOR AS SOON AS THEY HAVE RECEIVED A PURCHASE ORDER OR PAYMENT FOR THIS INSPECTION. THE MODIFICATION INSPECTOR SHALL REVIEW THE REQUIREMENTS OF THE INSPECTION CHECKLIST, SHALL WORK WITH THE PRIME CONTRACTOR TO DEVELOP A SCHEDULE OF NECESSARY ON-SITE INSPECTIONS, AND SHALL DISCUSS ANY SITE-SPECIFIC INSPECTION REQUIREMENTS OF OTHER CONCERN.

6.02 THE MODIFICATION INSPECTOR IS RESPONSIBLE FOR COLLECTION ALL PRIME CONTRACTOR INSPECTION AND TEST REPORTS (INCLUDING THOSE OF ASSIGNED SUB-CONTRACTORS), SHALL REVIEW THE REPORTS FOR COMPLIANCE WITH THE CONTRACT DOCUMENTS, SHALL CONDUCT THE NECESSARY ON-SITE INSPECTIONS, AND SHALL COMPILE AND SUBMIT THE MODIFICATION INSPECTION REPORT.

7.00 PRIME CONTRACTOR RESPONSIBILITIES

7.01 THE PRIME CONTRACTOR SHALL CONTACT THE MODIFICATION INSPECTOR AS SOON AS THEY HAVE RECEIVED A PURCHASE ORDER OR PAYMENT FOR THE MODIFICATION INSTALLATION. THE PRIME CONTRACTOR SHALL REVIEW THE REQUIREMENTS OF THE MODIFICATION INSPECTION CHECKLIST, SHALL WORK WITH THE MODIFICATION INSPECTOR TO DEVELOP A SCHEDULE TO CONDUCT ON-SITE INSPECTIONS, AND SHALL DISCUSS SPECIFIC INSPECTION AND TESTING REQUIREMENTS WITH THE MODIFICATION INSPECTOR IN DETAIL TO OBTAIN A FULL UNDERSTANDING OF THE REQUIRED INSPECTION AND TESTING.

7.02 THE PRIME CONTRACTOR SHALL PERFORM AND RECORD THE TESTING AND INSPECTION RESULTS IN ACCORDANCE WITH THE REQUIREMENTS OF THE MODIFICATION INSPECTION CHECKLIST.

8.00 PHOTOGRAPHY REQUIREMENTS

8.01 THE PRIME CONTRACTOR AND MODIFICATION INSPECTOR SHALL, BETWEEN THE EFFORTS OF BOTH PARTIES AND THEIR EMPLOYED PERSONNEL, PROVIDED PHOTOGRAPHS WITH THE INSPECTION REPORT TO INCLUDE THE FOLLOWING:

- GENERAL SITE PHOTOGRAPHS PRE-CONSTRUCTION
- MODIFICATION INSTALLATION PHOTOGRAPHS DURING CONSTRUCTION/ ERECTION OPERATIONS AND INSPECTIONS.
 - RAW MATERIALS
 - PHOTOS OF DETAILED WORK REQUIRED ON THE DRAWINGS (CONNECTIONS, WELDMENTS, FIELD/FABRICATED MEMBERS, ETC.)
 - WELD PREPARATION AND COMPLETED WELD INSPECTION (INCLUDING A FILLET WELD SIZE GAUGE, AS APPLICABLE)
 - BOLT INSTALLATION AND TORQUE/PRETENSION.
 - FINAL INSTALLED CONDITION (AFTER DEFICIENT CONDITIONS, IF ANY, ARE REMEDIATED).
 - REPAIR OF SURFACE COATINGS (INCLUDING GALVANIZING AND/OR PAINT COATING).
- POST-MODIFICATION PHOTOGRAPHS OF THE SITE & WORK.
- PHOTOGRAPHS OF THE FINAL STATE OF THE SITE AT CONCLUSION OF THE WORK BY THE PRIME CONTRACTOR, ASSOCIATED SUBCONTRACTORS, AND THE MODIFICATION INSPECTOR.
- OTHER PHOTOS MAY BE INCLUDED AT PRIME CONTRACTOR & MODIFICATION INSPECTOR'S DISCRETION.

NOTE: PHOTOS OF MODIFICATIONS INSTALLED ABOVE AN ELEVATION OF 20' SHALL REQUIRE PHOTOS BE TAKEN FROM THE STRUCTURE AS WELL AS OVERALL PHOTOGRAPHS OF THE MODIFICATIONS TAKEN FROM THE GROUND.

9.00 SPECIAL INSPECTIONS (PER IBC)

Section	Type of Special Inspection and Extent	Applicable	Continuous or Periodic
1705.1	General	NO	N/A
1705.2	Steel construction	YES	PERIODIC
1705.3	Concrete construction	NO	N/A
1705.4	Masonry construction	NO	N/A
1705.5	Wood construction	NO	N/A
1705.6	Soils	NO	N/A
1705.7	Driven deep foundations	NO	N/A
1705.8	Cast-in-place deep foundations	NO	N/A
1705.9	Helical pile foundations	NO	N/A
1705.10	Fabricated items	YES	PERIODIC
1705.11	Special inspections for wind resistance	NO	N/A
1705.12	Special inspections for seismic resistance	NO	N/A
1705.13	Testing for seismic resistance	NO	N/A
1705.14	Sprayed fire-resistant materials	NO	N/A
1705.15	Mastic and intumescent fire-resistant coatings	NO	N/A
1705.16	Exterior insulation and finish systems (EIFS)	NO	N/A
1705.17	Fire-resistant penetrations and joints	NO	N/A
1705.18	Testing for smoke control	NO	N/A
1705.19	Underpinning	NO	N/A

PRE-CONSTRUCTION INSPECTION CHECKLIST

CONSTRUCTION AND/OR INSTALLATION INSPECTIONS REQUIRED FOR REPORT?	INSPECTION REPORT ITEM
YES	MODIFICATION INSPECTION CHECKLIST
YES	SHOP DRAWINGS APPROVED BY EOR (LATEST REVISION)
YES	FABRICATION INSPECTION
YES	FABRICATOR'S CERTIFIED WELD INSPECTION (CWI)
YES	FABRICATOR'S QUALIFIED PERSONNEL FOR WELDING
YES	MATERIAL TEST REPORT(S) / MILL CERTIFICATE(S)
YES	FABRICATOR'S NON-DESTRUCTIVE TESTING (NDT) TECHNICIAN
YES	PACKING SLIPS FOR STRUCTURAL MATERIALS

CONSTRUCTION INSPECTION CHECKLIST

CONSTRUCTION AND/OR INSTALLATION INSPECTIONS REQUIRED FOR REPORT?	INSPECTION REPORT ITEM
YES	CONSTRUCTION INSPECTION
	FOUNDATION INSPECTION
	CONCRETE COMPRESSIVE STRENGTH AND SLUMP TESTING RESULTS/CERTIFICATES
	ADHESIVE ANCHOR ROD(S) INSTALLATION INSPECTION
	BASE PLATE GROUT INSPECTION
YES	THIRD-PARTY CERTIFIED WELD INSPECTION (INCLUDING IBC SPECIAL INSPECTIONS)
	SOIL EXCAVATION-DENSITY TESTING, COMPACTION INSPECTION/VERIFICATION, USE OF SUITABLE FILL
YES	GALVANIZING REPAIR MATERIAL PREPARATION, INSPECTION & PAINT APPLICATION
	GUY WIRE (RE-)TENSION REPORT AND INSPECTION
YES	PRIME CONTRACTOR'S AS-BUILT DOCUMENTS (SIGNED & DATED)

POST-CONS. INSPECTION CHECKLIST

CONSTRUCTION AND/OR INSTALLATION INSPECTIONS REQUIRED FOR REPORT?	INSPECTION REPORT ITEM
YES	MODIFICATION INSPECTOR'S ISSUE LIST (INCLUDING CORRECTIVE ACTIONS TAKEN) AND/OR REDLINED RECORD DRAWINGS.
	POST-INSTALLED ADHESIVE ANCHOR ROD PULL-OUT TESTING
YES	PHOTOGRAPHS OF MODIFICATIONS (INCLUDE PHOTOS OF BOTH SIDES OF WELDED OR BOLTED CONNECTIONS, OF OVERALL AND DETAIL VIEWS OF INSTALLED MODIFICATIONS, AND BEFORE/AFTER PHOTOS OF ANY ISSUES IDENTIFIED BY THE INSPECTOR)

TowerCo

5000 VALLEYSTONE COURT
CARY, NORTH CAROLINA 27519

PROJECT INFORMATION:

OTIS
DC0002


1800 PERRY STREET NE
DISTRICT OF COLUMBIA, DC 20018
DISTRICT OF COLUMBIA COUNTY

PLANS PREPARED BY:

Kimley-Horn | DC
421 FAYETTEVILLE STREET, SUITE 600
RALEIGH, NC 27601
PHONE: 919-677-2000
WWW.KIMLEY-HORN.COM
DC COA #N/A



8	
7	
6	
5	
4	
3	
2	
1	3/6/2025 CONSTRUCTION AVF
0	10/17/24 CONSTRUCTION AVF



012628109 / KHRAL-20552

DRAWN BY: CHECKED BY:

MRD AVF


SHEET TITLE:

INSPECTION NOTES

SHEET NUMBER:

N-2

NOTE: EXISTING APPURTENANCES AND TOWER EQUIPMENT NOT SHOWN FOR CLARITY.



1 TOWER ELEVATION
S-1 SCALE: N.T.S.

1 4

MODIFICATION SCHEDULE

NO.	ELEVATION	SCOPE	MATERIAL	NOTES
1	0.0-84.0'±	CONTRACTOR TO PERFORM PRE-MODIFICATION INSPECTION TO VERIFY MODIFICATIONS MAY BE INSTALLED AS SHOWN.	-	N-1 N-2
2	84.0-94.0'±	INSTALL 15-FT BOLT-ON EXTENSION, ALL BOLTS TO INCLUDE (2) WASHERS AND (1) NUT, AND SHALL BE TIGHTENED IN ACCORDANCE WITH SHEET N-1.	A53 GR. B P14STD	S-2 S-3 S-4
3	0.0-94.0'±	REPLACE EXISTING SAFETY CLIMB SYSTEM	SITE PRO 1 PSC-100-G	-
4	0.0-94.0'±	CONTRACTOR TO PROVIDE ALL NECESSARY MATERIAL CERTIFICATIONS, INSPECTION REPORTS, AND PHOTOS NECESSARY FOR KIMLEY-HORN TO COMPLETE A POST-MODIFICATION INSPECTION REPORT.	-	N-1 N-2

CONSTRUCTION NOTES

1. SCOPE OF WORK MUST BE COMPLETED AT WIND SPEEDS < 20 MPH.
2. ALL DIMENSIONS ARE APPROXIMATE, CONTRACTOR SHOULD FIELD VERIFY ALL DIMENSIONS BEFORE FABRICATION OF STEEL AND COMMENCEMENT OF WORK. FIELD CUT MEMBERS AS REQUIRED.

DO NOT SCALE DRAWINGS

CONTRACTOR SHALL VERIFY ALL PLANS, EXISTING DIMENSIONS, CONDITIONS ON THE JOB SITE AND SHALL IMMEDIATELY NOTIFY THE ENGINEER OF RECORD IN WRITING OF ANY DISCREPANCIES BEFORE PROCEEDING WITH THE WORK OR BE RESPONSIBLE FOR THE SAME.

 TowerCo

5000 VALLEYSTONE COURT
CARY, NORTH CAROLINA 27519

PROJECT INFORMATION:

OTIS
DC0002

1800 PERRY STREET NE
DISTRICT OF COLUMBIA, DC 20018
DISTRICT OF COLUMBIA COUNTY

PLANS PREPARED BY:

Kimley-Horn | DC


421 FAYETTEVILLE STREET, SUITE 600
RALEIGH, NC 27601
PHONE: 919-677-2000
WWW.KIMLEY-HORN.COM
DC COA/N/A



REV: ____ DATE: ____ ISSUED FOR: ____ BY: ____

8	
7	
6	
5	
4	
3	
2	
1	3/6/2025 CONSTRUCTION AVF
0	10/17/24 CONSTRUCTION AVF

LICENSER: ____



PROJECT NUMBER: 012628109 / KHLR-20552


DRAWN BY: ____ CHECKED BY: ____


MRD AVF

SHEET TITLE: TOWER ELEV.
& MODIFICATION
SCHEDULE



SHEET NUMBER: S-1

Copyright Kimley-Horn and Associates, Inc., 2025







NOTE: CONTRACTOR MAY SUBSTITUTE FABRICATION FOR ALL FASTENERS PART #14SBWC58.



1 HHR PLAN VIEW
S-3




3 STEP BOLT BRACKET DETAIL
S-3



4 STEP BOLT SPECIFICATION
S-3

5 HAND HOLE RIM (HHR) SPECIFICATION
S-3



2 STEP BOLT PLAN VIEW
S-3

6 TIE-OFF ANCHOR SPECIFICATION
S-3

TowerCo
5000 VALLEYSTONE COURT
CARY, NORTH CAROLINA 27519

PROJECT INFORMATION:

OTIS
DC0002

1800 PERRY STREET NE
DISTRICT OF COLUMBIA, DC 20018
DISTRICT OF COLUMBIA COUNTY

PLANS PREPARED BY:


Kimley-Horn | DC
421 FAYETTE STREET, SUITE 600
RALEIGH, NC 27601
PHONE: 919-677-2000
WWW.KIMLEY-HORN.COM
DC COA N/A



REV: DATE: ISSUED FOR: BY:

8
7
6
5
4
3
2
1 3/6/2025 CONSTRUCTION AVF
0 10/17/24 CONSTRUCTION AVF

LICENSER:



DRAWN BY: CHECKED BY:

MRD	AVF
-----	-----

SHEET TITLE:

CONSTRUCTION DETAILS

SHEET NUMBER:

S-3

PROJECT INFORMATION:

OTIS
DC0002

1800 PERRY STREET NE
DISTRICT OF COLUMBIA, DC 20018
DISTRICT OF COLUMBIA COUNTY

PLANS PREPARED BY:

Kimley-Horn | DC


421 FAYETTEVILLE STREET, SUITE 600
RALEIGH, NC 27601
PHONE: 919-677-2000
WWW.KIMLEY-HORN.COM
DC COA #N/A



REV: DATE: ISSUED FOR: BY:

8	
7	
6	
5	
4	
3	
2	
1	3/6/2025 CONSTRUCTION AVF
0	10/17/24 CONSTRUCTION AVF

LICENSER:



PROJECT NUMBER:

012628109 / KHLR-20552

DRAWN BY: CHECKED BY:


MRD AVF

SHEET TITLE:

CONSTRUCTION DETAILS

SHEET NUMBER:

S-4



1 BOLT ON FLANGE ATTACHMENT ELEVATION

SCALE: N.T.S.

03/06/25 10:24 AM by: Dynodocit

K:\RAI_Wireless\TowerCo\2020\DC0002\KHA-3747\PSAR\CAD\DC0002.MOD.R1.dwg



2 BOLT ON FLANGE ATTACHMENT PLAN

SCALE: N.T.S.

K:\RAI_Wireless\TowerCo\2020\DC0002\KHA-3747\PSAR\CAD\DC0002.MOD.R1.dwg

This document, together with the concepts and designs presented herein, as an instrument of service, is intended only for the specific purpose and client for which it was prepared. Reuse of and improper reliance on this document without written authorization and adaptation by Kimley-Horn and Associates, Inc. shall be without liability to Kimley-Horn and Associates, Inc.



4 BOLT ON FLANGE ASSEMBLY DETAIL PLAN

SCALE: N.T.S.

Copyright Kimley-Horn and Associates, Inc., 2025

T-Mobile – Colocation
Comprehensive Structural Analysis for



100' Self-Supporting Pole Structure (Monopole)
(Sabre Job #507253 w/ 15' Extension and 4' Lightning Rod)

March 6, 2025

Site Name: Otis
Site Number: DC0002
Carrier Site Number: 7WDC540A
Site Address: 1800 Perry Street NE
District of Columbia, DC 20018
District of Columbia County
Site Coordinates: 38.935498°, -76.977808°
Analysis Code: ANSI/TIA-222-H and 2017 DCBC

TowerCo Jira Ticket: [KHA-3747](#)

Kimley-Horn Project #: 012628109.20552
Kimley-Horn Jira Ticket: [KHAL-20552](#)

Analysis Results

Tower Usage	77%	PASS (with Modifications*)
Foundation Usage	34%	PASS

NOTE: For this analysis to be valid, the proposed extension shall be installed in accordance with the attached design drawings prior to the installation of the proposed carrier loading considered in this report.

Prepared by:
Ryan Doolittle

Signed by:
Avery V. Fann, PE
Lic. #PE40001630, Exp. 08/30/2026
Kimley-Horn of DC

Revision History:
0 – Initial Release
1 – Tower Height




TABLE OF CONTENTS

Supporting Documentation	3
Analysis Criteria	3
Appurtenance Listing	4
Results	5
Conclusions and Recommendations	5
Assumptions and Limitations	6
Appendix	7

SUPPORTING DOCUMENTATION

Information on the current tower geometry, member sizes, foundation dimensions, soil properties, and antenna loading was obtained from the sources listed in the attached project history (see appendix for details). It is assumed that all information provided to Kimley-Horn & Associates, Inc. is accurate. In the absence of information to the contrary, we assume the structure has been properly erected and maintained per the original design drawings and the capacity has not significantly changed from the “as new” condition.

ANALYSIS CRITERIA

The analysis utilizes *tnxTower v. 8.2*, an industry-standard finite element analysis program to create an elastic three-dimensional model and second-order effects per ANSI/TIA-222 requirements. The program calculates member stresses for various loading cases and the selected output from the analysis is included in the Appendix.

Code	ANSI/TIA-222-H / 2017 DCBC
Basic Wind Speed	113 mph (3-Second Gust, V_{ult})
Basic Wind Speed w/ Ice	40 mph (3-Second Gust) with 1.0" radial ice (ultimate)
Risk Category	II
Exposure Category	C
Topographic Factor	$K_{zt} = 1.0$
Elevation Factor	$K_e = 0.997$ (<i>Structure Base Elevation = ±77-ft AMSL</i>)
Seismic Design Criteria	$S_s = 0.133g$ / $S_1 = 0.043g$ / Site Class = D / SDC = B

Tower Owner	TowerCo 2013 LLC
FCC ASR #	N/A
Maintenance Program	Yes
Annex S Reductions	Included

APPURTEINANCE LISTING

The tables below will show the existing/reserved and proposed equipment, equipment to be removed, and the final equipment configuration considered in the analysis. If the existing/reserved equipment in the field deviates from the information shown below, Kimley-Horn & Associates, Inc. should be contacted to perform an analysis revision immediately.

Existing & Reserved Equipment:

Antenna RAD (ft)	Description	Feedlines ¹	Mount Type	Mount Elev (ft)	Carrier ²
82	(6) Commscope NNHH-65B-R4 (3) Nokia AEQK (3) Nokia AEQU (3) Nokia AHLBBA (3) Nokia AHFIB (3) Nokia AHCA (3) Nokia AHNA (3) Raycap DC9-48-60-24-8C-EV	(9) Power (3) Fiber	Site Pro 1 F3P-12W w/ F3P-HRK12	82	AT&T (E)
76	(4) 2'Ø Stadium Lights	(4) Power	Face Mount	76	
74	(4) 2'Ø Stadium Lights	(4) Power	Face Mount	74	--

1 – (E) Denotes existing loading. (R) Denotes reserved loading.

2 – AT&T loading per tenant lease dated 09/26/2022.

Existing & Reserved Equipment:

Antenna RAD (ft)	Description	Feedlines ¹	Mount Type	Mount Elev (ft)	Carrier ²
94	(3) RFS APXVAALL24_43-U-NA20 (3) Commscope VV-65A-R1 (3) Ericsson AIR 6419 B41 (3) Ericsson RADIO 4480 B71/B85 (3) Ericsson RADIO 4460 B25/B66	(3) 1.75" Hybrid	Site Pro 1 RMQP-496-KH	94	T-Mobile

1 – T-Mobile loading per tenant application dated 07/03/2024.

2 – Equipment shall be installed on proposed extension in accordance with attached design drawings.

RESULTS

The tables below provide a summary of maximum usages for each primary load carrying member of the structure. The usage is a ratio of the force in the member compared to its calculated capacity per code requirements. A more detailed report of member usages can be found in the appendix at the end of this report. Usages greater than 100% indicate where the force in the member exceeds its capacity. Usages up to 105% are considered acceptable per industry standard practice.

Serviceability Requirements:

Component	Controlling Usage	Result
Tower Twist	1%	Pass
Tower Sway	44%	Pass
Tower Deflection	53%	Pass

Structure Usages:

Component	Controlling Usage	Result
Extension Shaft	37%	Pass
Extension Bolts	54%	Pass
Extension Flange	34%	Pass
Shaft	77%	Pass
Anchor Rods	59%	Pass
Base Plate	58%	Pass

Foundation Usages:

Foundation Type	Controlling Usage	Result
Drilled Shaft	34%	Pass

CONCLUSIONS AND RECOMMENDATIONS

Per our Comprehensive Structural Analysis, in accordance with the structural strength requirements of ANSI/TIA-222-H and 2017 DCBC, the structure has been found to **PASS**, provided that the modifications detailed in the following attachments have been adequately installed.

ASSUMPTIONS AND LIMITATIONS

This report is not a condition assessment of the tower and foundation; It is an engineering analysis based upon the theoretical capacity of the structure. Unless told otherwise, we assume the structure and foundation to be in "like new" condition. It is the responsibility of our client and the structure owner to verify that the structure modeled and loading considered is accurate. If these assumptions are not accurate, Kimley-Horn & Associates, Inc. should be notified immediately to perform a revised analysis. This analysis assumes all antenna mounts are adequate to support the existing and proposed loads. It is the carrier's responsibility to ensure antenna mount meets the structural requirements of ANSI/TIA-222. Kimley-Horn & Associates, Inc. did not analyze antenna supporting mounts as part of this structural analysis report.

All services are performed, results obtained, and recommendation made in accordance with generally accepted engineering principles and practices. Kimley-Horn & Associates, Inc. is not responsible for the conclusions, opinions and recommendations made by others based on the information in this report.


Kimley-Horn makes no warranties, expressed or implied in connection with this report and disclaims any liability arising from original design, material, fabrication, and section deficiencies or corrosion of the tower.

APPENDIX

Client ID
DC0002

Client ID	DM #	Doc ID	Issued By	Issued To	Date	Description	Tenant	Tenant ID	Comment
DC0002	3038110	3038110_DC0002 Otis Geotechnical Report - Otis Street - 2-4-22.pdf	ECS	Entrex	2/4/2022	Geotech Report			
DC0002	3037551	3037551_DC0002 Sabre 22-4630-IDS Tower and Foundation Design 2022-02-17 signed.pdf	Sabre	Smartlink	2/27/2022	Tower and Foundation Design Calculations			85' Monopole
DC0002	3080300	3080300_DC0002 Sabre 507253 Tower Erection FINAL Drawings RO 2022-08-02.pdf	Sabre	TowerCo	44770	Tower and Foundation Design Drawings			85' Monopole
DC0002	3042741	3042741_DC0002 Otis - AT&T Site Lease Agreement 9-26-22.pdf	AT&T	TowerCo	9/26/2022	Tenant Lease Agreement	AT&T	10127906	82' Elevation
DC0002	3044764	3044764_DC0002 OTIS CD REV 13 S&S 10-03-22.pdf	Entrex	AT&T	9/30/2022	Construction Drawings	AT&T	10127906	Rev 13
DC0002	3045430	3045430_DC0002 Otis foundation - Certification for permanent casing.pdf	Sabre	TowerCo	10/27/2022	Foundation Casing Letter			Casing to 8.5' below grade / 6" larger diameter
DC0002	20240703	20240703_DC0002 Otis T-Mobile Colo (7WDC540A) Colo App updated RAD 2024-07-03.doc	T-Mobile	TowerCo	45476	Tenant Colocation Application	T-Mobile	7WDC540A	90' Elevation (Revised)
DC0002	3080190	3080190_DC0002 KHA Passing T-Mobile Colo Extension SA RO 2024-07-23 Signed.pdf	Kimley-Horn	TowerCo	45496	Structural Analysis Report	T-Mobile	7WDC540A	PASS (70%) - Feasibility w/ Extension

Section	3	2	1
Length (ft)	53.25	34.00	15.00
Number of Sides	18	18	1
Thickness (in)	0.3750	0.2500	0.2500
Socket Length (ft)			
Top Dia (in)	22.1100	14.0000	14.0000
Bot Dia (in)	37.0200	23.5200	
Grade	A500-42	A500-42	
Weight (K)	6.3	1.7	0.6




MATERIAL STRENGTH

GRADE	Fy	Fu	GRADE	Fy	Fu
A500-42	42 ksi	58 ksi	A572-65	65 ksi	80 ksi


TOWER DESIGN NOTES

1. Tower is located in District Of Columbia County, District Of Columbia.
2. Tower designed for Exposure C to the TIA-222-H Standard.
3. Tower designed for a 113 mph basic wind in accordance with the TIA-222-H Standard.
4. Tower is also designed for a 40 mph basic wind with 1.00 in ice. Ice is considered to increase in thickness with height.
5. Deflections are based upon a 60 mph wind.
6. Tower Risk Category II.
7. Topographic Category 1 with Crest Height of 0.00 ft
8. TOWER RATING: 77.1%

ALL REACTIONS
ARE FACORED




TORQUE 1 kip-ft
40 mph WIND - 1.0000 in ICE



TORQUE 5 kip-ft
REACTIONS - 113 mph WIND

Kimley-Horn and Associates, Inc.
421 Fayetteville Street, Suite 600
Raleigh, NC 27601
Phone: (919) 677-2000
FAX:

Job: DC0002-ERP+EDD	Project: KHA-3747 (77%)	Client: TowerCo	Drawn by: ryan.doolittle	App'd:
		Code: TIA-222-H	Date: 10/16/24	Scale: NTS
		Path: C:\Users\ryan.doolittle\OneDrive - KHD\Documents\LOCAL\20240415 - TCO Misc\DC0002\KHA-3747 (PSAR)\Models\ERP\DC0002-ERP.m3d		Dwg No. E-1



DESIGNED APPURTEINANCE LOADING

TYPE	ELEVATION	TYPE	ELEVATION
APXVAALL24_43-U-NA20 w/ MP (T-Mobile [P])	94	AEQK + AEQU (Stacked) w/ MP (ATT)	82
APXVAALL24_43-U-NA20 w/ MP (T-Mobile [P])	94	AHLBBA (ATT) (ATT)	82
APXVAALL24_43-U-NA20 w/ MP (T-Mobile [P])	94	AHLBBA (ATT) (ATT)	82
AIR 6419 B41 w/ MP (8') (T-Mobile [P])	94	AHFIB (ATT) (ATT)	82
AIR 6419 B41 w/ MP (8') (T-Mobile [P])	94	AHFIB (ATT) (ATT)	82
AIR 6419 B41 w/ MP (8') (T-Mobile [P])	94	AHCA (ATT) (ATT)	82
VV-65A-R1 w/ MP (T-Mobile [P])	94	AHCA (ATT) (ATT)	82
VV-65A-R1 w/ MP (T-Mobile [P])	94	AHNA (ATT) (ATT)	82
VV-65A-R1 w/ MP (T-Mobile [P])	94	AHNA (ATT) (ATT)	82
RADIO 4480 B71/B85 (TMO) (T-Mobile [P])	94	AHNA (ATT) (ATT)	82
RADIO 4480 B71/B85 (TMO) (T-Mobile [P])	94	DC9-48-60-24-8C-EV (ATT)	82
RADIO 4480 B71/B85 (TMO) (T-Mobile [P])	94	DC9-48-60-24-8C-EV (ATT)	82
RADIO 4480 B71/B85 (TMO) (T-Mobile [P])	94	DC9-48-60-24-8C-EV (ATT)	82
RADIO 4460 B25/B66 (TMO) (T-Mobile [P])	94	5' x 2" Pipe (ATT)	82
RADIO 4460 B25/B66 (TMO) (T-Mobile [P])	94	5' x 2" Pipe (ATT)	82
RADIO 4460 B25/B66 (TMO) (T-Mobile [P])	94	8' x 2" Mount Pipe (ATT)	82
RADIO 4460 B25/B66 (TMO) (T-Mobile [P])	94	8' x 2" Mount Pipe (ATT)	82
RADIO 4460 B25/B66 (TMO) (T-Mobile [P])	94	8' x 2" Mount Pipe (ATT)	82
Breakout Pendant (T-Mobile [P])	94	(3) HHR (ATT)	80
Breakout Pendant (T-Mobile [P])	94	Site Pro 1 F3P-12 (ATT)	79
Breakout Pendant (T-Mobile [P])	94	96" x 4" Tube Mount (Lighting)	76
Site Pro 1 RMQP-XXX-HK (w/o MP) (T-Mobile [P])	94	2' Stadium Light (Lighting)	76
Site Pro 1 RMQP-XXX-HK (w/o MP) (T-Mobile [P])	94	2' Stadium Light (Lighting)	76
8' x 2" Pipe (T-Mobile [P])	94	2' Stadium Light (Lighting)	76
8' x 2" Pipe (T-Mobile [P])	94	2' Stadium Light (Lighting)	76
8' x 2" Pipe (T-Mobile [P])	94	HHR (Lighting)	75
(3) HHR (T-Mobile [P])	92	96" x 4" Tube Mount (Lighting)	74
4' Lightning Rod	85	2' Stadium Light (Lighting)	74
Site Pro 1 F3P-HRK12 (ATT)	83	2' Stadium Light (Lighting)	74
(2) NNHH-65B-R4 w/ MP (ATT)	82	2' Stadium Light (Lighting)	74
(2) NNHH-65B-R4 w/ MP (ATT)	82	2' Stadium Light (Lighting)	74
(2) NNHH-65B-R4 w/ MP (ATT)	82	HHR (Lighting)	71
AEQK + AEQU (Stacked) w/ MP (ATT)	82	(3) HHR (Vacant)	64
AEQK + AEQU (Stacked) w/ MP (ATT)	82	(3) HHR (Vacant)	56
		Entry Port (ATT)	8
		(2) Entry Port (T-Mobile [P])	4

Kimley-Horn

Kimley-Horn and Associates, Inc.
421 Fayetteville Street, Suite 600
Raleigh, NC 27601
Phone: (919) 677-2000
FAX:

Job: DC0002-ERP+EDD	Project: KHA-3747 (77%)	Client: TowerCo	Drawn by: ryan.doolittle	App'd:
		Code: TIA-222-H	Date: 10/16/24	Scale: NTS
		Path: C:\Users\ryan.doolittle\OneDrive - KHD\Documents\LOCAL\20240415 - TCO Misc\DC0002\KHA-3747 (PSAR)\Models\ERP\DC0002-ERP.dwg		Dwg No. E-1

tnxTower	Job	DC0002-ERP+EDD	Page	1 of 12
Kimley-Horn and Associates, Inc. 421 Fayetteville Street, Suite 600 Raleigh, NC 27601 Phone: (919) 677-2000 FAX:	Project	KHA-3747 (77%)	Date	22:29:02 10/16/24
	Client	TowerCo	Designed by	ryan.doolittle

Tower Input Data

The tower is a monopole.

This tower is designed using the TIA-222-H standard.

The following design criteria apply:

Tower is located in District Of Columbia County, District Of Columbia.

Tower base elevation above sea level: 78.00 ft.

Basic wind speed of 113 mph.

Risk Category II.

Exposure Category C.

Simplified Topographic Factor Procedure for wind speed-up calculations is used.

Topographic Category: 1.

Crest Height: 0.00 ft.

Nominal ice thickness of 1.0000 in.

Ice thickness is considered to increase with height.

Ice density of 56 pcf.

A wind speed of 40 mph is used in combination with ice.

Temperature drop of 50 °F.

Deflections calculated using a wind speed of 60 mph.

Non-linear (P-delta) analysis was used.

Pressures are calculated at each section.

Stress ratio used in pole design is 1.

Tower analysis based on target reliabilities in accordance with Annex S.

Load Modification Factors used: $K_{\text{e}}(F_{\text{u}}) = 0.95$, $K_{\text{e}}(t) = 0.85$.

Maximum demand-capacity ratio is: 1.

Local bending stresses due to climbing loads, feed line supports, and appurtenance mounts are not considered.

Options

Consider Moments - Legs
Consider Moments - Horizontals
Consider Moments - Diagonals
Use Moment Magnification
Use Code Stress Ratios
Use Code Safety Factors - Guys
Escalate Ice
Always Use Max Kz
Kz In Exposure D Hurricane Region
Include Bolts In Member Capacity
Leg Bolts Are At Top Of Section
Secondary Horizontal Braces Leg
Use Diamond Inner Bracing (4 Sided)
SR Members Have Cut Ends
SR Members Are Concentric
Distribute Leg Loads As Uniform
Use Special Wind Profile

✓ Assume Legs Pinned
✓ Assume Rigid Index Plate
Use Clear Spans For Wind Area
Use Clear Spans For KL/r
Retention Guys To Initial Tension
✓ Bypass Mast Stability Checks
✓ Use Azimuth Dish Coefficients
✓ Project Wind Area of Appurtenances
Alternative Appurt. EPA Calculation
Autocode Torque Arm Areas
Add IBC .6D+W Combination
✓ Sort Capacity Reports By Component
Triangulate Diamond Inner Bracing
Treat Feed Line Bundles As Cylinder
Ignore KL/r For 60 Deg. Angle Legs
Use ASCE 10 X-Brace Ly Rules

Calculate Redundant Bracing Forces
Ignore Redundant Members in FEA
SR Leg Bolts Resist Compression
All Leg Panels Have Same Allowable
Offset Girt At Foundation
✓ Consider Feed Line Torque
Include Angle Block Shear Check
Use TIA-222-H Bracing Resist. Exemption
Use TIA-222-H Tension Splice Exemption
Poles
✓ Include Shear-Torsion Interaction
Always Use Sub-Critical Flow
Use Top Mounted Sockets
Pole Without Linear Attachments
Pole With Shroud Or No Appurtenances
Outside and Inside Corner Radii Are Known

Tapered Pole Section Geometry

tnxTower	Job	DC0002-ERP+EDD	Page	2 of 12
Kimley-Horn and Associates, Inc. 421 Fayetteville Street, Suite 600 Raleigh, NC 27601 Phone: (919) 677-2000 FAX:	Project	KHA-3747 (77%)	Date	22:29:02 10/16/24
	Client	TowerCo	Designed by	ryan.doolittle

Section	Elevation ft	Section Length ft	Splice Length ft	Number of Sides	Top Diameter in	Bottom Diameter in	Wall Thickness in	Bend Radius in	Pole Grade
L1	100.00-85.00	15.00	0.00	Round	14.0000	14.0000	0.2500		A500-42 (42 ksi)
L2	85.00-51.00	34.00	3.25	18	14.0000	23.5200	0.2500	1.0000	A572-65 (65 ksi)
L3	51.00-1.00	53.25		18	22.1100	37.0200	0.3750	1.5000	A572-65 (65 ksi)

Tapered Pole Properties

Section	Tip Dia. in	Area in ²	I in ⁴	r in	C in	I/C in ²	J in ⁴	It/Q in ²	w in	w/t
L1	14.0000	10.7992	255.3004	4.8622	7.0000	36.4715	510.6008	5.3964	0.0000	0
	14.0000	10.7992	255.3004	4.8622	7.0000	36.4715	510.6008	5.3964	0.0000	0
L2	14.1774	10.9106	260.6108	4.8812	7.1120	36.6438	521.5646	5.4563	2.0240	8.096
	23.8443	18.4647	1263.2041	8.2608	11.9482	105.7237	2528.0704	9.2341	3.6995	14.798
	23.3173	25.8701	1544.0259	7.7159	11.2319	137.4682	3090.0834	12.9375	3.2314	8.617
L3	37.5332	43.6167	7399.7972	13.0090	18.8062	393.4773	14809.3313	21.8125	5.8555	15.615

Tower Elevation ft	Gusset Area ft ²	Gusset Thickness in	Gusset Grade	Adjust. Factor <i>A_f</i>	Adjust. Factor <i>A_r</i>	Weight Mult.	Double Angle Stitch Bolt Spacing Diagonals in	Double Angle Stitch Bolt Spacing Horizontals in	Double Angle Stitch Bolt Spacing Redundants in
L1 100.00-85.00				1	1	1			
L2 85.00-51.00				1	1	1			
L3 51.00-1.00				1	1	1			

Feed Line/Linear Appurtenances - Entered As Round Or Flat

Description	Sector	Exclude From Torque Calculation	Component Type	Placement	Total Number	Number Per Row	Start/End Position	Width or Diameter in	Perimeter in	Weight plf
Safety Line 3/8	C	No	Surface Ar (CaAa)	85.00 - 10.00	1	1	0.000	0.3750		0.22
1.75" Hybrid	A	No	Surface Ar (CaAa)	94.00 - 92.00	1	1	0.000	1.7500		2.72
1.75" Hybrid	B	No	Surface Ar (CaAa)	94.00 - 92.00	1	1	0.000	1.7500		2.72
1.75" Hybrid	C	No	Surface Ar (CaAa)	94.00 - 92.00	1	1	0.000	1.7500		2.72
3/8" Fiber	A	No	Surface Ar (AT&T)	82.00 - 80.00	1	1	0.000	0.3750		0.03
3/8" Fiber	B	No	Surface Ar (AT&T)	82.00 - 80.00	1	1	0.000	0.3750		0.03
3/8" Fiber	C	No	Surface Ar (AT&T)	82.00 - 80.00	1	1	0.000	0.3750		0.03
3/4" Power	A	No	Surface Ar (CaAa)	82.00 - 80.00	3	3	0.000	0.7500		0.08
3/4" Power	B	No	Surface Ar (AT&T)	82.00 - 80.00	3	3	0.000	0.7500		0.08

tnxTower		Job	DC0002-ERP+EDD	Page	3 of 12
Kimley-Horn and Associates, Inc.		Project	KHA-3747 (77%)	Date	22:29:02 10/16/24
421 Fayetteville Street, Suite 600 Raleigh, NC 27601 Phone: (919) 677-2000 FAX:		Client	TowerCo	Designed by	ryan.doolittle

Description	Sector	Exclude From Torque Calculation	Component Type	Placement ft	Total Number	Number Per Row	Start/End Position	Width or Diameter in	Perimeter in	Weight plf
3/4" Power (AT&T)	C	No	Surface Ar (CaAa)	82.00 - 80.00	3	3	0.000	0.7500	0.08	
0.795" Power (Lighting)	A	No	Surface Ar (CaAa)	76.00 - 75.00	4	4	0.000	0.7950	0.08	
0.795" Power (Lighting)	A	No	Surface Ar (CaAa)	74.00 - 71.00	4	4	0.000	0.7950	0.08	

Feed Line/Linear Appurtenances - Entered As Area

Description	Face or Leg	Allow Shield	Exclude From Torque Calculation	Component Type	Placement ft	Total Number	$C_A A_4$	Weight
							ft^2/ft	plf
*** 1.75" Hybrid (T-Mobile [P])	C	No	No	Inside Pole	94.00 - 5.00	3	No Ice 0.00 1/2" Ice 0.00 1" Ice 0.00	2.72
*** 3/8" Fiber (AT&T)	B	No	No	Inside Pole	80.00 - 5.00	3	No Ice 0.00 1/2" Ice 0.00 1" Ice 0.00	0.03
3/4" Power (AT&T)	C	No	No	Inside Pole	80.00 - 5.00	9	No Ice 0.00 1/2" Ice 0.00 1" Ice 0.00	0.08
*** 0.795" Power (Lighting)	A	No	No	Inside Pole	75.00 - 5.00	4	No Ice 0.00 1/2" Ice 0.00 1" Ice 0.00	0.08
0.795" Power (Lighting)	A	No	No	Inside Pole	71.00 - 5.00	4	No Ice 0.00 1/2" Ice 0.00 1" Ice 0.00	0.08

Feed Line/Linear Appurtenances Section Areas

Tower Section	Tower Elevation ft	Face	A_R	A_F	$C_A A_4$	$C_A A_4$	Weight
			ft^2	ft^2	ft^2	ft^2	
L1	100.00-85.00	A	0.000	0.000	0.350	0.000	0.01
		B	0.000	0.000	0.350	0.000	0.01
		C	0.000	0.000	0.350	0.000	0.08
L2	85.00-51.00	A	0.000	0.000	1.797	0.000	0.02
		B	0.000	0.000	0.525	0.000	0.00
		C	0.000	0.000	1.800	0.000	0.31
L3	51.00-1.00	A	0.000	0.000	0.000	0.000	0.03
		B	0.000	0.000	0.000	0.000	0.00
		C	0.000	0.000	1.538	0.000	0.42

Feed Line/Linear Appurtenances Section Areas - With Ice

tnxTower		Job	DC0002-ERP+EDD	Page	4 of 12
Kimley-Horn and Associates, Inc.		Project	KHA-3747 (77%)	Date	22:29:02 10/16/24
421 Fayetteville Street, Suite 600 Raleigh, NC 27601 Phone: (919) 677-2000 FAX:		Client	TowerCo	Designed by	ryan.doolittle

Tower Section	Tower Elevation ft	Face or Leg	Ice Thickness in	A_R	A_F	$C_A A_4$ In Face ft^2	$C_A A_4$ Out Face ft^2	Weight K
L1	100.00-85.00	A	0.942	0.000	0.000	0.727	0.000	0.01
		B	0.000	0.000	0.000	0.727	0.000	0.01
		C	0.000	0.000	0.000	0.727	0.000	0.09
L2	85.00-51.00	A	0.912	0.000	0.000	3.960	0.000	0.04
		B	0.000	0.000	0.000	1.458	0.000	0.01
		C	0.000	0.000	0.000	8.936	0.000	0.36
L3	51.00-1.00	A	0.828	0.000	0.000	0.000	0.000	0.03
		B	0.000	0.000	0.000	0.000	0.000	0.00
		C	0.000	0.000	0.000	9.017	0.000	0.48

Feed Line Center of Pressure

Section	Elevation ft	CP_x in	CP_z in	CP_x Ice in	CP_z Ice in
L1	100.00-85.00	0.0000	0.0000	0.0000	0.0000
L2	85.00-51.00	-0.2293	0.1484	-0.2216	0.6810
L3	51.00-1.00	0.0000	0.2381	0.0000	0.7753

Note: For pole sections, center of pressure calculations do not consider feed line shielding.

Shielding Factor Ka

Tower Section	Feed Line Record No.	Description	Feed Line Segment Elev.	K_a No Ice	K_a Ice
L1	4	1.75" Hybrid	92.00 - 94.00	1.0000	1.0000
L1	5	1.75" Hybrid	92.00 - 94.00	1.0000	1.0000
L1	6	1.75" Hybrid	92.00 - 94.00	1.0000	1.0000
L2	1	Safety Line 3/8	51.00 - 85.00	1.0000	1.0000
L2	9	3/8" Fiber	80.00 - 82.00	1.0000	1.0000
L2	10	3/8" Fiber	80.00 - 82.00	1.0000	1.0000
L2	11	3/8" Fiber	80.00 - 82.00	1.0000	1.0000
L2	13	3/4" Power	80.00 - 82.00	1.0000	1.0000
L2	14	3/4" Power	80.00 - 82.00	1.0000	1.0000
L2	15	3/4" Power	80.00 - 82.00	1.0000	1.0000
L2	18	0.795" Power	75.00 - 76.00	1.0000	1.0000
L2	20	0.795" Power	71.00 - 74.00	1.0000	1.0000
L3	1	Safety Line 3/8	10.00 - 51.00	1.0000	1.0000

Discrete Tower Loads

tnxTower		Job	DC0002-ERP+EDD			Page	5 of 12
Kimley-Horn and Associates, Inc.		Project	KHA-3747 (77%)			Date	22:29:02 10/16/24
421 Fayetteville Street, Suite 600 Raleigh, NC 27601 Phone: (919) 677-2000 FAX:		Client	TowerCo			Designed by	ryan.doolittle

Description	Face or Leg	Offset Type	Offsets: Horz Lateral Vert ft ft ft	Azimuth Adjustment °	Placement ft	CsA ₄ Front ft ²	CsA ₄ Side ft ²	Weight K
4' Lightning Rod	C	From Leg	0.00 0.00 2.00	0.0000	85.00	No Ice 0.30 1/2" Ice 0.71 1" Ice 1.00	0.30 0.03 0.04	0.03
(3) HHR (T-Mobile [P])	C	None		0.0000	92.00	No Ice 0.00 1/2" Ice 0.00 1" Ice 0.00	0.00 0.00 0.00	
(3) HHR (AT&T)	C	None		0.0000	80.00	No Ice 0.00 1/2" Ice 0.00 1" Ice 0.00	0.00 0.00 0.00	
HHR (Lighting)	C	None		0.0000	75.00	No Ice 0.00 1/2" Ice 0.00 1" Ice 0.00	0.00 0.00 0.00	
HHR (Lighting)	C	None		0.0000	71.00	No Ice 0.00 1/2" Ice 0.00 1" Ice 0.00	0.00 0.00 0.00	
(3) HHR (Vacant)	C	None		0.0000	64.00	No Ice 0.00 1/2" Ice 0.00 1" Ice 0.00	0.00 0.00 0.00	
(3) HHR (Vacant)	C	None		0.0000	56.00	No Ice 0.00 1/2" Ice 0.00 1" Ice 0.00	0.00 0.00 0.00	
Entry Port (AT&T)	C	None		0.0000	8.00	No Ice 0.00 1/2" Ice 0.00 1" Ice 0.00	0.00 0.00 0.00	
(2) Entry Port (T-Mobile [P])	C	None		0.0000	4.00	No Ice 0.00 1/2" Ice 0.00 1" Ice 0.00	0.00 0.00 0.00	

APXVAALL24_43-U-NA20 w/ MP (T-Mobile [P])	A	From Leg	4.00 0.00	15.0000	94.00	No Ice 20.24 1/2" Ice 20.89 1" Ice 21.55	11.03 12.46 13.56	0.20 0.33 0.48
APXVAALL24_43-U-NA20 w/ MP (T-Mobile [P])	B	From Leg	4.00 0.00	15.0000	94.00	No Ice 20.24 1/2" Ice 20.89 1" Ice 21.55	11.03 12.46 13.56	0.20 0.33 0.48
APXVAALL24_43-U-NA20 w/ MP (T-Mobile [P])	C	From Leg	4.00 0.00	15.0000	94.00	No Ice 20.24 1/2" Ice 20.89 1" Ice 21.55	11.03 12.46 13.56	0.20 0.33 0.48
AIR 6419 B41 w/ MP (8') (T-Mobile [P])	A	From Leg	4.00 0.00	15.0000	94.00	No Ice 7.50 1/2" Ice 8.34 1" Ice 9.08	4.78 5.85 6.78	0.13 0.19 0.26
AIR 6419 B41 w/ MP (8') (T-Mobile [P])	B	From Leg	4.00 0.00	15.0000	94.00	No Ice 7.50 1/2" Ice 8.34 1" Ice 9.08	4.78 5.85 6.78	0.13 0.19 0.26
AIR 6419 B41 w/ MP (8') (T-Mobile [P])	C	From Leg	4.00 0.00	15.0000	94.00	No Ice 7.50 1/2" Ice 8.34 1" Ice 9.08	4.78 5.85 6.78	0.13 0.19 0.26
VV-65A-R1 w/ MP (T-Mobile [P])	A	From Leg	4.00 0.00	15.0000	94.00	No Ice 6.70 1/2" Ice 7.42 1" Ice 8.08	4.63 5.80 6.82	0.06 0.12 0.18
VV-65A-R1 w/ MP (T-Mobile [P])	B	From Leg	4.00 0.00	15.0000	94.00	No Ice 6.70 1/2" Ice 7.42 1" Ice 8.08	4.63 5.80 6.82	0.06 0.12 0.18
VV-65A-R1 w/ MP (T-Mobile [P])	C	From Leg	4.00 0.00	15.0000	94.00	No Ice 6.70 1/2" Ice 7.42 1" Ice 8.08	4.63 5.80 6.82	0.06 0.12 0.18
RADIO 4480 B71/B85 (TMO)	A	From Leg	3.00 0.00	15.0000	94.00	No Ice 2.88 1/2" Ice 3.09	1.40 1.56	0.08 0.10

tnxTower		Job	DC0002-ERP+EDD			Page	6 of 12
Kimley-Horn and Associates, Inc.		Project	KHA-3747 (77%)			Date	22:29:02 10/16/24
421 Fayetteville Street, Suite 600 Raleigh, NC 27601 Phone: (919) 677-2000 FAX:		Client	TowerCo			Designed by	ryan.doolittle

Description	Face or Leg	Offset Type	Offsets: Horz Lateral Vert ft ft ft	Azimuth Adjustment °	Placement ft	CsA ₄ Front ft ²	CsA ₄ Side ft ²	Weight K
(T-Mobile [P])								
RADIO 4480 B71/B85 (TMO)	B	From Leg	0.00 0.00	15.0000	94.00	1" Ice 3.31 No Ice 2.88	1.73 1.40	0.13 0.08
(T-Mobile [P])	C	From Leg	0.00 0.00	15.0000	94.00	1" Ice 3.31 No Ice 2.88	1.73 1.40	0.13 0.08
RADIO 4480 B71/B85 (TMO)	A	From Leg	3.00 0.00	15.0000	94.00	1" Ice 3.31 No Ice 2.14	1.73 1.69	0.13 0.11
(T-Mobile [P])	B	From Leg	3.00 0.00	15.0000	94.00	1" Ice 2.51 No Ice 2.14	2.02 1.69	0.16 0.11
RADIO 4460 B25/B66 (TMO)	C	From Leg	3.00 0.00	15.0000	94.00	1" Ice 2.51 No Ice 2.14	1.85 1.69	0.13 0.11
(T-Mobile [P])	A	From Leg	2.00 0.00	15.0000	94.00	1" Ice 2.51 No Ice 1.36	1.51 0.47	0.16 0.01
Breakout Pendant (T-Mobile [P])	A	From Leg	2.00 0.00	15.0000	94.00	1" Ice 1.67 No Ice 1.36	0.69 0.47	0.03 0.01
Breakout Pendant (T-Mobile [P])	B	From Leg	2.00 0.00	15.0000	94.00	1" Ice 1.67 No Ice 1.36	0.69 0.47	0.03 0.01
Breakout Pendant (T-Mobile [P])	C	From Leg	2.00 0.00	15.0000	94.00	1" Ice 1.67 No Ice 1.36	0.69 0.47	0.03 0.01
Site Pro 1 RMQP-XXX-HK (w/o MP)	C	None		0.0000	94.00	1" Ice 49.60 No Ice 1.90	42.04 1.90	2.33 0.03
(T-Mobile [P])	A	From Leg	3.50 0.00	15.0000	94.00	1" Ice 2.73 No Ice 2.73	2.73 2.73	0.04 0.04
(T-Mobile [P])	B	From Leg	3.50 0.00	15.0000	94.00	1" Ice 3.40 No Ice 1.90	3.40 1.90	0.06 0.03
(T-Mobile [P])	C	From Leg	3.50 0.00	15.0000	94.00	1" Ice 3.40 No Ice 1.90	3.40 1.90	0.06 0.03

(2) NNHH-65B-R4 w/ MP (AT&T)	A	From Leg	4.50 0.00	0.0000	82.00	No Ice 12.51 1/2" Ice 13.11	7.41 8.60	0.10 0.20
(2) NNHH-65B-R4 w/ MP (AT&T)	B	From Leg	4.50 0.00	0.0000	82.00	No Ice 12.51 1/2" Ice 13.11	7.41 8.60	0.10 0.20
(2) NNHH-65B-R4 w/ MP (AT&T)	C	From Leg	4.50 0.00	0.0000	82.00	No Ice 12.51 1/2" Ice 13.11	7.41 8.60	0.10 0.20
AEQK + AEQU (Stacked) w/ MP (AT&T)	A	From Leg	4.50 0.00	0.0000	82.00	No Ice 11.81 1/2" Ice 12.51	9.04 10.34	0.25 0.34
AEQK + AEQU (Stacked) w/ MP (AT&T)	B	From Leg	4.50 0.00	0.0000	82.00	No Ice 11.81 1/2" Ice 12.51	9.04 10.34	0.25 0.34
AEQK + AEQU (Stacked) w/ MP (AT&T)	C	From Leg	4.50 0.00	0.0000	82.00	No Ice 11.81 1/2" Ice 12.51	9.04 10.34	0.25 0.34
AHLBBA (AT&T)	A	From Leg	3.50 0.00	0.0000	82.00	1" Ice 13.12 No Ice 2.82	11.29 1.60	0.45 0.10

Job		DC0002-ERP+EDD		Page	
Project		KHA-3747 (77%)		7 of 12	
Client		TowerCo		Designed by ryan.doolittle	

Description	Face or Leg	Offset Type	Offsets: Horz Lateral	Azimuth Adjustment	Placement	CsA ₄ Front	CsA ₄ Side	Weight
			Vert ft ft ft	°	ft	ft ²	ft ²	K
(AT&T)			0.00		1/2" Iee	3.03	1.77	0.12
			0.00		1" Iee	3.26	1.95	0.15
AHLBBA (AT&T)	B	From Leg	3.50	0.0000	82.00	No Iee	2.82	1.60
(AT&T)			0.00		1/2" Iee	3.03	1.77	0.12
			0.00		1" Iee	3.26	1.95	0.15
AHLBBA (AT&T)	C	From Leg	3.50	0.0000	82.00	No Iee	2.82	1.60
(AT&T)			0.00		1/2" Iee	3.03	1.77	0.12
			0.00		1" Iee	3.26	1.95	0.15
AHFIB (AT&T)	A	From Leg	3.50	0.0000	82.00	No Iee	2.23	1.13
(AT&T)			0.00		1/2" Iee	2.42	1.28	0.10
			0.00		1" Iee	2.62	1.44	0.12
AHFIB (AT&T)	B	From Leg	3.50	0.0000	82.00	No Iee	2.23	1.13
(AT&T)			0.00		1/2" Iee	2.42	1.28	0.10
			0.00		1" Iee	2.62	1.44	0.12
AHFIB (AT&T)	C	From Leg	3.50	0.0000	82.00	No Iee	2.23	1.13
(AT&T)			0.00		1/2" Iee	2.42	1.28	0.10
			0.00		1" Iee	2.62	1.44	0.12
AHCA (AT&T)	A	From Leg	3.50	0.0000	82.00	No Iee	1.53	0.82
(AT&T)			0.00		1/2" Iee	1.69	0.95	0.05
			0.00		1" Iee	1.85	1.08	0.06
AHCA (AT&T)	B	From Leg	3.50	0.0000	82.00	No Iee	1.53	0.82
(AT&T)			0.00		1/2" Iee	1.69	0.95	0.05
			0.00		1" Iee	1.85	1.08	0.06
AHCA (AT&T)	C	From Leg	3.50	0.0000	82.00	No Iee	1.53	0.82
(AT&T)			0.00		1/2" Iee	1.69	0.95	0.05
			0.00		1" Iee	1.85	1.08	0.06
AHNA (AT&T)	A	From Leg	3.50	0.0000	82.00	No Iee	1.40	0.64
(AT&T)			0.00		1/2" Iee	1.54	0.75	0.05
			0.00		1" Iee	1.70	0.87	0.06
AHNA (AT&T)	B	From Leg	3.50	0.0000	82.00	No Iee	1.40	0.64
(AT&T)			0.00		1/2" Iee	1.54	0.75	0.05
			0.00		1" Iee	1.70	0.87	0.06
AHNA (AT&T)	C	From Leg	3.50	0.0000	82.00	No Iee	1.40	0.64
(AT&T)			0.00		1/2" Iee	1.54	0.75	0.05
			0.00		1" Iee	1.70	0.87	0.06
DC9-48-60-24-8C-EV	A	From Leg	2.00	0.0000	82.00	No Iee	2.74	4.78
(AT&T)			0.00		1/2" Iee	2.96	5.06	0.06
			0.00		1" Iee	3.20	5.35	0.10
DC9-48-60-24-8C-EV	B	From Leg	2.00	0.0000	82.00	No Iee	2.74	4.78
(AT&T)			0.00		1/2" Iee	2.96	5.06	0.06
			0.00		1" Iee	3.20	5.35	0.10
DC9-48-60-24-8C-EV	C	From Leg	2.00	0.0000	82.00	No Iee	2.74	4.78
(AT&T)			0.00		1/2" Iee	2.96	5.06	0.06
			0.00		1" Iee	3.20	5.35	0.10
5' x 2" Pipe (AT&T)	A	From Leg	2.00	0.0000	82.00	No Iee	1.19	1.19
			0.00		1/2" Iee	1.50	1.50	0.03
			0.00		1" Iee	1.81	1.81	0.04
5' x 2" Pipe (AT&T)	B	From Leg	2.00	0.0000	82.00	No Iee	1.19	1.19
			0.00		1/2" Iee	1.50	1.50	0.03
			0.00		1" Iee	1.81	1.81	0.04
5' x 2" Pipe (AT&T)	C	From Leg	2.00	0.0000	82.00	No Iee	1.19	1.19
			0.00		1/2" Iee	1.50	1.50	0.03
			0.00		1" Iee	1.81	1.81	0.04
Site Pro 1 F3P-HRK12	C	None	0.0000		83.00	No Iee	8.07	6.95
(AT&T)						1/2" Iee	10.84	9.53
						1" Iee	13.32	12.19
Site Pro 1 F3P-12	C	None	0.0000		79.00	No Iee	38.09	37.93
						2.00		

Job		DC0002-ERP+EDD		Page	
Project		KHA-3747 (77%)		8 of 12	
Client		TowerCo		Designed by ryan.doolittle	

Description	Face or Leg	Offset Type	Offsets: Horz Lateral	Azimuth Adjustment	Placement	CsA ₄ Front	CsA ₄ Side	Weight
			Vert ft ft ft	°	ft	ft ²	ft ²	K
(AT&T)			0.00		1/2" Iee	4.00	0.0000	82.00
			0.00		1" Iee	5.85	0.90	1.90
AHLBBA (AT&T)	B	From Leg	3.50	0.0000	82.00	No Iee	2.82	1.60
(AT&T)			0.00		1/2" Iee	3.03	1.77	0.12
			0.00		1" Iee	3.26	1.95	0.15
AHLBBA (AT&T)	C	From Leg	3.50	0.0000	82.00	No Iee	2.82	1.60
(AT&T)			0.00		1/2" Iee	3.03	1.77	0.12
			0.00		1" Iee	3.26	1.95	0.15
AHFIB (AT&T)	A	From Leg	3.50	0.0000	82.00	No Iee	2.23	1.13
(AT&T)			0.00		1/2" Iee	2.42	1.28	0.10
			0.00		1" Iee	2.62	1.44	0.12
AHFIB (AT&T)	B	From Leg	3.50	0.0000	82.00	No Iee	2.23	1.13
(AT&T)			0.00		1/2" Iee	2.42	1.28	0.10
			0.00		1" Iee	2.62	1.44	0.12
AHFIB (AT&T)	C	From Leg	3.50	0.0000	82.00	No Iee	2.23	1.13
(AT&T)			0.00		1/2" Iee	2.42	1.28	0.10
			0.00		1" Iee	2.62	1.44	0.12
AHCA (AT&T)	A	From Leg	3.50	0.0000	82.00	No Iee	1.53	0.82
(AT&T)			0.00		1/2" Iee	1.69	0.95	0.05
			0.00		1" Iee	1.85	1.08	0.06
AHCA (AT&T)	C	From Leg	3.50	0.0000	82.00	No Iee	1.53	0.82
(AT&T)			0.00		1/2" Iee	1.69	0.95	0.05
			0.00		1" Iee	1.85	1.08	0.06
AHNA (AT&T)	A	From Leg	3.50	0.0000	82.00	No Iee	1.40	0.64
(AT&T)			0.00		1/2" Iee	1.54	0.75	0.05
			0.00		1" Iee	1.70	0.87	0.06
AHNA (AT&T)	B	From Leg	3.50	0.0000	82.00	No Iee	1.40	0.64
(AT&T)			0.00		1/2" Iee	1.54	0.75	0.05
			0.00		1" Iee	1.70	0.87	0.06
AHNA (AT&T)	C	From Leg	3.50	0.0000	82.00	No Iee	1.40	0.64
(AT&T)			0.00		1/2" Iee	1.54	0.75	0.05
			0.00		1" Iee	1.70	0.87	0.06
DC9-48-60-24-8C-EV	A	From Leg	2.00	0.0000	82.00	No Iee	2.74	4.78
(AT&T)			0.00		1/2" Iee	2.96	5.06	0.06
			0.00		1" Iee	3.20	5.35	0.10
DC9-48-60-24-8C-EV	B	From Leg	2.00	0.0000	82.00	No Iee	2.74	4.78
(AT&T)			0.00		1/2" Iee	2.96	5.06	0.06
			0.00		1" Iee	3.20	5.35	0.10
DC9-48-60-24-8C-EV	C	From Leg	2.00	0.0000	82.00	No Iee	2.74	4.78
(AT&T)			0.00		1/2" Iee	2.96	5.06	0.06
			0.00		1" Iee	3.20	5.35	0.10
5' x 2" Pipe (AT&T)	A	From Leg	2.00	0.0000	82.00	No Iee	1.19	1.19
			0.00		1/2" Iee	1.50	1.50	0.03
			0.00		1" Iee	1.81	1.81	0.04
5' x 2" Pipe (AT&T)	B	From Leg	2.00	0.0000	82.00	No Iee	1.19	1.19
			0.00		1/2" Iee	1.50	1.50	0.03
			0.00		1" Iee	1.81	1.81	0.04
5' x 2" Pipe (AT&T)	C	From Leg	2.00	0.0000	82.00	No Iee	1.19	1.19
			0.00		1/2" Iee	1.50	1.50	0.03
			0.00		1" Iee	1.81	1.81	0.04
Site Pro 1 F3P-HRK12	C	None	0.0000		83.00	No Iee	8.07	6.95
(AT&T)						1/2" Iee	10.84	9.53
						1" Iee	13.32	12.19
Site Pro 1 F3P-12	C	None	0.0000		79.00	No Iee	38.09	37.93
						2.00		

Description	Face or Leg	Offset Type	Offsets: Horz Lateral	Azimuth Adjustment	Placement	CsA ₄ Front	CsA ₄ Side	Weight
			Vert ft ft ft	°	ft	ft ²	ft ²	K
(AT&T)			0.00		1/2" Iee	4.00	0.0000	82.00
			0.00		1" Iee	5.85	0.90	1.90
AHLBBA (AT&T)	B	From Leg	3.50	0.00				

tnxTower	Job	DC0002-ERP+EDD	Page	9 of 12
Kimley-Horn and Associates, Inc. 421 Fayetteville Street, Suite 600 Raleigh, NC 27601 Phone: (919) 677-2000 FAX:	Project	KHA-3747 (77%)	Date	22:29:02 10/16/24
	Client	TowerCo	Designed by	ryan.doolittle

Description	Face or Leg	Dish Type	Offset Type	Offsets: Horz Lateral Vert	Azimuth Adjustment	3 dB Beam Width	Elevation	Outside Diameter	Aperture Area	Weight
(Lighting)	Radome	Leg		4.00 0.00			ft	ft	ft ²	K

Load Combinations

Comb. No.	Description
1	Dead Only
2	1.2 Dead+1.0 Wind 0 deg - No Ice
3	0.9 Dead+1.0 Wind 0 deg - No Ice
4	1.2 Dead+1.0 Wind 30 deg - No Ice
5	0.9 Dead+1.0 Wind 30 deg - No Ice
6	1.2 Dead+1.0 Wind 60 deg - No Ice
7	0.9 Dead+1.0 Wind 60 deg - No Ice
8	1.2 Dead+1.0 Wind 90 deg - No Ice
9	0.9 Dead+1.0 Wind 90 deg - No Ice
10	1.2 Dead+1.0 Wind 120 deg - No Ice
11	0.9 Dead+1.0 Wind 120 deg - No Ice
12	1.2 Dead+1.0 Wind 150 deg - No Ice
13	0.9 Dead+1.0 Wind 150 deg - No Ice
14	1.2 Dead+1.0 Wind 180 deg - No Ice
15	0.9 Dead+1.0 Wind 180 deg - No Ice
16	1.2 Dead+1.0 Wind 210 deg - No Ice
17	0.9 Dead+1.0 Wind 210 deg - No Ice
18	1.2 Dead+1.0 Wind 240 deg - No Ice
19	0.9 Dead+1.0 Wind 240 deg - No Ice
20	1.2 Dead+1.0 Wind 270 deg - No Ice
21	0.9 Dead+1.0 Wind 270 deg - No Ice
22	1.2 Dead+1.0 Wind 300 deg - No Ice
23	0.9 Dead+1.0 Wind 300 deg - No Ice
24	1.2 Dead+1.0 Wind 330 deg - No Ice
25	0.9 Dead+1.0 Wind 330 deg - No Ice
26	1.2 Dead+1.0 Ice+1.0 Temp
27	1.2 Dead+1.0 Wind 0 deg+1.0 Ice+1.0 Temp
28	1.2 Dead+1.0 Wind 30 deg+1.0 Ice+1.0 Temp
29	1.2 Dead+1.0 Wind 60 deg+1.0 Ice+1.0 Temp
30	1.2 Dead+1.0 Wind 90 deg+1.0 Ice+1.0 Temp
31	1.2 Dead+1.0 Wind 120 deg+1.0 Ice+1.0 Temp
32	1.2 Dead+1.0 Wind 150 deg+1.0 Ice+1.0 Temp
33	1.2 Dead+1.0 Wind 180 deg+1.0 Ice+1.0 Temp
34	1.2 Dead+1.0 Wind 210 deg+1.0 Ice+1.0 Temp
35	1.2 Dead+1.0 Wind 240 deg+1.0 Ice+1.0 Temp
36	1.2 Dead+1.0 Wind 270 deg+1.0 Ice+1.0 Temp
37	1.2 Dead+1.0 Wind 300 deg+1.0 Ice+1.0 Temp
38	1.2 Dead+1.0 Wind 330 deg+1.0 Ice+1.0 Temp
39	Dead+Wind 0 deg - Service
40	Dead+Wind 30 deg - Service
41	Dead+Wind 60 deg - Service
42	Dead+Wind 90 deg - Service
43	Dead+Wind 120 deg - Service
44	Dead+Wind 150 deg - Service
45	Dead+Wind 180 deg - Service
46	Dead+Wind 210 deg - Service
47	Dead+Wind 240 deg - Service
48	Dead+Wind 270 deg - Service
49	Dead+Wind 300 deg - Service

tnxTower	Job	DC0002-ERP+EDD	Page	10 of 12
Kimley-Horn and Associates, Inc. 421 Fayetteville Street, Suite 600 Raleigh, NC 27601 Phone: (919) 677-2000 FAX:	Project	KHA-3747 (77%)	Date	22:29:02 10/16/24
	Client	TowerCo	Designed by	ryan.doolittle

Comb. No.	Description
50	Dead+Wind 330 deg - Service

Maximum Tower Deflections - Service Wind

Section No.	Elevation	Horz. Deflection	Gov. Load Comb.	Tilt	Twist
L1	100 - 85	19.017	47	1.7796	0.0360
L2	85 - 51	13.471	47	1.7122	0.0306
L3	54.25 - 1	4.762	47	0.9059	0.0078

Critical Deflections and Radius of Curvature - Service Wind

Elevation	Appurtenance	Gov. Load Comb.	Deflection	Tilt	Twist	Radius of Curvature
94.00	APXVAALL24_43-U-NA20 w/ MP	47	16.753	1.7732	0.0343	8341
92.00	(3) HHR	47	16.008	1.7671	0.0336	6255
85.00	4' Lightning Rod	47	13.471	1.7122	0.0306	3387
83.00	Site Pro 1 F3P-HRK12	47	12.774	1.6837	0.0295	3199
82.00	(2) NNHH-65B-R4 w/ MP	47	12.432	1.6671	0.0289	3133
80.00	(3) HHR	47	11.758	1.6299	0.0276	2999
79.00	Site Pro 1 F3P-12	47	11.427	1.6094	0.0269	2934
76.00	2' Stadium Light	47	10.459	1.5408	0.0247	2757
75.00	HHR	47	10.145	1.5159	0.0239	2702
74.00	2' Stadium Light	47	9.835	1.4901	0.0231	2650
71.00	HHR	47	8.934	1.4081	0.0207	2504
64.00	(3) HHR	47	7.003	1.1990	0.0150	2219
56.00	(3) HHR	47	5.123	0.9561	0.0089	1964
8.00	Entry Port	47	0.243	0.0807	0.0003	14565
4.00	(2) Entry Port	47	0.102	0.0344	0.0001	33984

Maximum Tower Deflections - Design Wind

Section No.	Elevation	Horz. Deflection	Gov. Load Comb.	Tilt	Twist
L1	100 - 85	72.184	18	6.7769	0.1388
L2	85 - 51	51.144	18	6.5196	0.1180
L3	54.25 - 1	18.080	18	3.4436	0.0291

Critical Deflections and Radius of Curvature - Design Wind

Elevation	Appurtenance	Gov. Load Comb.	Deflection	Tilt	Twist	Radius of Curvature
94.00	APXVAALL24_43-U-NA20 w/ MP	18	63.598	6.7526	0.1322	2246

<i>tnxTower</i> Kimley-Horn and Associates, Inc. 421 Fayetteville Street, Suite 600 Raleigh, NC 27601 Phone: (919) 677-2000 FAX:	Job DC0002-ERP+EDD	Page 11 of 12
Project	KHA-3747 (77%)	Date 22:29:02 10/16/24
Client	TowerCo	Designed by ryan.doolittle

Elevation ft	Appurtenance	Gov. Load Comb.	Deflection in	Tilt °	Twist °	Radius of Curvature ft
92.00	(3) HHR	18	60.770	6.7290	0.1297	1684
85.00	4' Lightning Rod	18	51.144	6.5196	0.1180	910
83.00	Site Pro 1 F3P-HRK12	18	48.500	6.4108	0.1136	858
82.00	(2) NNHH-65B-R4 w/ MP	18	47.200	6.3477	0.1113	840
80.00	(3) HHR	18	44.642	6.2056	0.1062	803
79.00	Site Pro 1 F3P-12	18	43.386	6.1272	0.1035	786
76.00	2' Stadium Light	18	39.712	5.8657	0.0949	738
75.00	HHR	18	38.520	5.7707	0.0920	723
74.00	2' Stadium Light	18	37.345	5.6723	0.0889	709
71.00	HHR	18	33.923	5.3593	0.0795	669
64.00	(3) HHR	18	26.591	4.5614	0.0571	590
56.00	(3) HHR	18	19.450	3.6350	0.0336	520
8.00	Entry Port	18	0.923	0.3058	0.0018	3835
4.00	(2) Entry Port	18	0.387	0.1302	0.0008	8948

Compression Checks

Pole Design Data

Section No.	Elevation	Size	L	L _u	Kl/r	A	P _u	ΦP _n	Ratio P _u /P _n
	ft		ft	ft		in ²	K	K	
L1	100 - 85 (1)	TP14x14x0.25	15.00	0.00	0.0	10,7992	-4.71	408.21	0.012
L2	85 - 51 (2)	TP23.52x14x0.25	34.00	0.00	0.0	17,7427	-12.90	1037.95	0.012
L3	51 - 1 (3)	TP37.02x22.11x0.375	53.25	0.00	0.0	33.0924	-16.35	1935.91	0.008

Pole Bending Design Data

Section No.	Elevation ft	Size	M_{ax} kip-ft	ΦM_{ax} kip-ft	Ratio $\frac{\Phi M_{ax}}{M_{ax}}$	M_{ay} kip-ft	ΦM_{ay} kip-ft	Ratio $\frac{\Phi M_{ay}}{M_{ay}}$
L1	100 - 85 (1)	TP14x14x0.25	50.80	144.21	0.352	0.00	144.21	0.000
L2	85 - 51 (2)	TP23.52x14x0.25	456.64	604.11	0.756	0.00	604.11	0.000
L3	51 - 1 (3)	TP37.02x22.11x0.375	792.92	1397.83	0.567	0.00	1397.83	0.000

Pole Shear Design Data

Section No.	Elevation ft	Size	Actual V_u K	ϕV_u K	Ratio V_u $\frac{\phi V_u}{V_u}$	Actual T_u kip-ft	ϕT_u kip-ft	Ratio T_u $\frac{\phi T_u}{T_u}$
L1	100 - 85 (1)	TP14x14x0.25	5.72	122.46	0.047	1.53	148.04	0.010
L2	85 - 51 (2)	TP23.52x14x0.25	15.08	311.38	0.048	2.65	609.74	0.004
L3	51 - 1 (3)	TP37.02x22.11x0.375	15.97	580.77	0.027	2.65	1414.08	0.002

<i>tnxTower</i> <i>Kimley-Horn and Associates, Inc.</i> 421 Fayetteville Street, Suite 600 Raleigh, NC 27601 Phone: (919) 677-2000 FAX:	Job DC0002-ERP+EDD	Page 12 of 12
	Project KHA-3747 (77%)	Date 22:29:02 10/16/24
	Client TowerCo	Designed by ryan.doolittle

Pole Interaction Design Data

Section No.	Elevation	Ratio	Ratio	Ratio	Ratio	Ratio	Comb. Stress Ratio	Allow. Stress Ratio	Criteria
		P_u	M_{ax}	M_{av}	V_u	T_u			
L1	100 - 85 (1)	0.012	0.352	0.000	0.047	0.010	0.367	1.000	✓
L2	85 - 51 (2)	0.012	0.756	0.000	0.048	0.004	0.771	1.000	✓
L3	51 - 1 (3)	0.008	0.567	0.000	0.027	0.002	0.577	1.000	✓

Section Capacity Table

Section No.	Elevation ft	Component Type	Size	Critical Element	P K	σ_{allow} K	% Capacity	Pass Fail
L1	100 - 85	Pole	TP14x14x0.25	1	-4.71	408.21	36.7	Pass
L2	85 - 51	Pole	TP23.5x21x0.25	2	-12.90	1037.95	77.1	Pass
L3	51 - 1	Pole	TP37.02x22.11x0.375	3	-16.35	1935.91	57.7	Pass
								Summary
								Pole (L2) 77.1 Pass
								RATING = 77.1

Program Version 8.3.0.5 - 9/19/2024 File:C:/Users/ryan.doolittle/OneDrive - KH/Documents/_LOCAL/20240415 - TCO Misc/DC0002/KHA-3747 (PSAR)/Models/ERP/DC0002-ERP.eri


Monopole Flange Plate Connection

Elevation = 84 ft.


Site #	DC0002
Site Name	Otis
JIRA #	KHRA-20552
TIA-222 Revision	H

Applied Loads	
Moment (kip-ft)	50.88
Axial Force (kips)	4.75
Shear Force (kips)	5.73

Top Plate - External



Bottom Plate - External



Connection Properties

Bolt Data

(8) 3/4" \varnothing bolts (A325 N; Fy=92 ksi, Fu=120 ksi) on 18" BC

Top Plate Data

21" OD x 1" Plate (A572-50; Fy=50 ksi, Fu=65 ksi)

Bottom Plate Data

21" OD x 1" Plate (A572-50; Fy=50 ksi, Fu=65 ksi)

Top Stiffener Data

N/A

Bottom Stiffener Data

N/A

Top Pole Data

14" x 0.25" round pole (A500-42; Fy=42 ksi, Fu=58 ksi)

Bottom Pole Data

14" x 0.25" 18-sided pole (A572-65; Fy=65 ksi, Fu=80 ksi)

Analysis Results

Bolt Capacity

Max Load (kips)	16.36
Allowable (kips)	30.04
Stress Rating:	54.4% Pass

Top Plate Capacity

Max Stress (ksi):	15.11	(Flexural)
Allowable Stress (ksi):	45.00	
Stress Rating:	33.6%	Pass
Tension Side Stress Rating:	17.8%	Pass

Bottom Plate Capacity


Max Stress (ksi):	15.11	(Flexural)
Allowable Stress (ksi):	45.00	
Stress Rating:	33.6%	Pass
Tension Side Stress Rating:	17.8%	Pass

Monopole Base Plate Connection

Site Info	
Site #	DC0002
Site Name	Otis
JIRA #	KHRAL-20552

Analysis Considerations	
TIA-222 Revision	H
Grout Considered:	No
l_{ar} (in)	2

Applied Loads	
Moment (kip-ft)	1316.23
Axial Force (kips)	22.16
Shear Force (kips)	17.24



Connection Properties

Anchor Rod Data

(10) 2-1/4" ϕ bolts (A615-75 N; Fy=75 ksi, Fu=100 ksi) on 43.25" BC

Base Plate Data

49" OD x 2" Plate (A572-50; Fy=50 ksi, Fu=65 ksi)

Stiffener Data

N/A

Pole Data

37.02" x 0.375" 18-sided pole (A572-65; Fy=65 ksi, Fu=80 ksi)

Analysis Results

Anchor Rod Summary	(units of kips, kip-in)	
$P_{u_t} = 143.7$	$\phi P_{n_t} = 243.75$	Stress Rating
$V_{u} = 1.72$	$\phi V_{n} = 149.1$	59.0%
$M_{u} = n/a$	$\phi M_{n} = n/a$	Pass

Base Plate Summary

Max Stress (ksi):	25.93	(Flexural)
Allowable Stress (ksi):	45	
Stress Rating:	57.6%	Pass

Drilled Pier Foundation

Site #:	DC0002
Site Name:	Otis
JIRA #:	KHRAL-20552
TIA-222 Revision:	H
Tower Type:	Monopole

Applied Loads		
	Comp.	Uplift
Moment (kip-ft)	1316	
Axial Force (kips)	22	
Shear Force (kips)	17	

Material Properties		
Concrete Strength, f'c:	4.5	ksi
Rebar Strength, Fy:	60	ksi
Tie Yield Strength, Fyt:	60	ksi

Pier Design Data		
Depth	22	ft
Ext. Above Grade	0.5	ft
Pier Section 1		
From 0.5' above grade to 22' below grade		
Pier Diameter	6	ft
Rebar Quantity	32	
Rebar Size	9	
Clear Cover to Ties	3	in
Tie Size	5	
Tie Spacing	10	in

[Rebar & Pier Options](#)

[Embedded Pole Inputs](#)

[Belled Pier Inputs](#)

Analysis Results			
Soil Lateral Check		Compression	Uplift
D _{v=0} (ft from TOC)	9.95	-	
Soil Safety Factor	3.93	-	
Max Moment (kip-ft)	1480.81	-	
Rating	33.9%	-	

Soil Vertical Check			
Soil Vertical Check		Compression	Uplift
Skin Friction (kips)	427.30	-	
End Bearing (kips)	636.17	-	
Weight of Concrete (kips)	114.51	-	
Total Capacity (kips)	1063.47	-	
Axial (kips)	136.51	-	
Rating	12.8%	-	

Reinforced Concrete Flexure			
Reinforced Concrete Flexure		Compression	Uplift
Critical Depth (ft from TOC)	9.89	-	
Critical Moment (kip-ft)	1480.78	-	
Critical Moment Capacity	4404.24	-	
Rating	33.6%	-	

Reinforced Concrete Shear			
Reinforced Concrete Shear		Compression	Uplift
Critical Depth (ft from TOC)	0.00	-	
Critical Shear (kip)	17.00	-	
Critical Shear Capacity	498.37	-	
Rating	3.4%	-	

Structural Foundation Rating	33.6%
Soil Interaction Rating	33.9%

Check Limitation	
Apply TIA-222-H Section 15.5:	<input type="checkbox"/>
N/A	<input type="checkbox"/>
Additional Longitudinal Rebar	
Input Effective Depths (else Actual):	<input checked="" type="checkbox"/>
Shear Design Options	
Check Shear along Depth of Pier:	<input type="checkbox"/>
N/A	<input type="checkbox"/>
N/A	<input type="checkbox"/>

[Go to Soil Calculations](#)

Soil Profile														
Layer	Top (ft)	Bottom (ft)	Thickness (ft)	γ _{soil} (pcf)	γ _{concrete} (pcf)	Cohesion (ksf)	Angle of Friction (degrees)	Calculated Ultimate Skin Friction Comp (ksf)	Calculated Ultimate Skin Friction Uplift (ksf)	Ultimate Skin Friction Comp Override (ksf)	Ultimate Skin Friction Uplift Override (ksf)	Ult. Gross Bearing Capacity (ksf)	SPT Blow Count	Soil Type
1	0	2	2	95	150			0.000	0.000	0.00	0.00			Cohesionless
2	2	8.5	6.5	115	150			0.000	0.000	0.00	0.00			Cohesionless
3	8.5	9	0.5	115	150		35	0.000	0.000	0.45	0.45			Cohesionless
4	9	14	5	125	150		39	0.000	0.000	1.20	1.20			Cohesionless
5	14	22	8	125	150	4.115		2.082	2.082	3.00	3.00	30		Cohesive

ASCE Hazards Report

Address:

No Address at This Location

Standard: ASCE/SEI 7-16



Risk Category: II

Soil Class: D - Stiff Soil

Latitude: 38.935538

Longitude: -76.977874

Elevation: 77.83610300256625 ft
(NAVD 88)



Wind

Results:

Wind Speed	113 Vmph
10-year MRI	75 Vmph
25-year MRI	84 Vmph
50-year MRI	89 Vmph
100-year MRI	95 Vmph

Data Source:

ASCE/SEI 7-16, Fig. 26.5-1B and Figs. CC.2-1–CC.2-4, and Section 26.5.2

Date Accessed:

Wed Oct 16 2024





Value provided is 3-second gust wind speeds at 33 ft above ground for Exposure C Category, based on linear interpolation between contours. Wind speeds are interpolated in accordance with the 7-16 Standard. Wind speeds correspond to approximately a 7% probability of exceedance in 50 years (annual exceedance probability = 0.00143, MRI = 700 years).

Site is not in a hurricane-prone region as defined in ASCE/SEI 7-16 Section 26.2.

Site Soil Class: D - Stiff Soil

Results:

S_s :	0.133	S_{D1} :	0.069
S_1 :	0.043	T_L :	8
F_a :	1.6	PGA :	0.068
F_v :	2.4	PGA_M :	0.11
S_{MS} :	0.212	F_{PGA} :	1.6
S_{M1} :	0.103	I_e :	1
S_{DS} :	0.141	C_v :	0.7



Data Accessed:

Wed Oct 16 2024

Date Source:

USGS Seismic Design Maps based on ASCE/SEI 7-16 and ASCE/SEI 7-16 Table 1.5-2. Additional data for site-specific ground motion procedures in accordance with ASCE/SEI 7-16 Ch. 21 are available from USGS.

Results:

Ice Thickness: 1.00 in.

Concurrent Temperature: 15 F

Gust Speed 40 mph

Data Source: Standard ASCE/SEI 7-16, Figs. 10-2 through 10-8

Date Accessed: Wed Oct 16 2024

Ice thicknesses on structures in exposed locations at elevations higher than the surrounding terrain and in valleys and gorges may exceed the mapped values.

Values provided are equivalent radial ice thicknesses due to freezing rain with concurrent 3-second gust speeds, for a 500-year mean recurrence interval, and temperatures concurrent with ice thicknesses due to freezing rain. Thicknesses for ice accretions caused by other sources shall be obtained from local meteorological studies. Ice thicknesses in exposed locations at elevations higher than the surrounding terrain and in valleys and gorges may exceed the mapped values.

The ASCE Hazard Tool is provided for your convenience, for informational purposes only, and is provided "as is" and without warranties of any kind. The location data included herein has been obtained from information developed, produced, and maintained by third party providers; or has been extrapolated from maps incorporated in the ASCE standard. While ASCE has made every effort to use data obtained from reliable sources or methodologies, ASCE does not make any representations or warranties as to the accuracy, completeness, reliability, currency, or quality of any data provided herein. Any third-party links provided by this Tool should not be construed as an endorsement, affiliation, relationship, or sponsorship of such third-party content by or from ASCE.

ASCE does not intend, nor should anyone interpret, the results provided by this Tool to replace the sound judgment of a competent professional, having knowledge and experience in the appropriate field(s) of practice, nor to substitute for the standard of care required of such professionals in interpreting and applying the contents of this Tool or the ASCE standard.

In using this Tool, you expressly assume all risks associated with your use. Under no circumstances shall ASCE or its officers, directors, employees, members, affiliates, or agents be liable to you or any other person for any direct, indirect, special, incidental, or consequential damages arising from or related to your use of, or reliance on, the Tool or any information obtained therein. To the fullest extent permitted by law, you agree to release and hold harmless ASCE from any and all liability of any nature arising out of or resulting from any use of data provided by the ASCE Hazard Tool.



TowerCo

Colocation Application

RETURN THIS APPLICATION TO: (E-MAIL IS PREFERRED)					Application Fee: (Please contact TowerCo)
TowerCo 5000 Valleystone Dr., Ste. 200 Cary, NC 27519 Attn: Colocation					06/17/2024
e-mail: colocation@towerco.com	Revision Dates:	Rev 07/03/2024			
office: 919-469-5559	TowerCo Site Name:	Otis			
fax: 919-469-5530	TowerCo Site Number:	DC0002			

TOWERCO SITE INFORMATION

Latitude:	38	56	7	7928	Existing Structure Type:	Monopole
Longitude:	76	58	40	1082	Existing Structure Height (ft. AGL):	85'(to be extended to 95')
Site Address: TowerCo to provide				County: Washington	State: DC	

APPLICANT INFORMATION

Applicant (Carrier): <u>T-Mobile</u>	Primary Contact Name: <u>Eric Lim</u>
Applicant Site Name: <u>Forced Relo - DC002 Dwight Mosley Park</u>	Company Name: <u>Site Link Wireless</u>
Applicant Site Number: <u>7WDC540A</u>	Primary Contact Number: <u>443.622.9386</u>
Req. Date For Receipt of Agreement: <u>TBD</u>	Primary Contact Fax:
Proposed Installation Date: <u>TBD</u>	Primary Contact Address: <u>3620 Commerce Drive, Suite 707 Baltimore, MD 21227</u>
Proposed ON AIR Date: <u>2025</u>	Primary Contact Email: <u>elim@sitelinkwireless.com</u>
Applicant Entity Name on SA: <u>T-Mobile Northeast LLC</u>	
Notice Address for Lease: <u>12920 SE 38th St. B</u>	
	<u>Bellevue, WA, 98006</u>
Billing Address: <u>Same as above</u>	

ADDITIONAL CARRIER INFORMATION

Leasing Contact Name/Number/Email	<u>Shaya Samuel / 301.728.0707 / shaya.samuel12@t-mobile.com</u>
RF Contact Name/Number/E mail	
Legal Review Contact Name/Number:	
Zoning Contact Name/Number:	
Construction Contact Name/Number:	
Site Tech Contact Name/Number:	
Emergency Contact Name/Number:	

ANTENNAS

	Sector 1	Sector 2	Sector 3	AUX /Other
Desired Rad Center (ft AGL)	94'	94'	94'	
Antenna Quantity	3	3	3	
Antenna Manufacturer	RFS, Ericsson, Commscope	RFS, Ericsson, Commscope	RFS, Ericsson, Commscope	
Antenna Model (Attach Spec Sheet)	APXVAALL24_43-U- NA20, AIR 6419 B41, VV- 65A- R1	APXVAALL24_43-U- NA20, AIR 6419 B41, VV- 65A- R1	APXVAALL24_43-U- NA20, AIR 6419 B41, VV- 65A- R1	
Antenna Weight (lbs per antenna)	136.00, 83.00, 24.70	136.00, 83.00, 24.70	136.00, 83.00, 24.70	
Antenna Dimensions (HxWxD) (in)	95.90 x 24.00 x 8.90, 35.20 x 20.90 x 7.00, 54.70 x 12.00 x 4.60	95.90 x 24.00 x 8.90, 35.20 x 20.90 x 7.00, 54.70 x 12.00 x 4.60	95.90 x 24.00 x 8.90, 35.20 x 20.90 x 7.00, 54.70 x 12.00 x 4.60	
ERP (watts)	1611	1611	1611	



Antenna Gain (dB)	TBD	TBD	TBD	
Orientation/Azimuth (Degrees)	15/135/255	15/135/255	15/135/255	
Mechanical Tilt	TBD	TBD	TBD	
RRU Quantity	2	2	2	
RRU Manufacturer & Model	Ericsson 4480 B71/B85, Ericsson 4460 B25/B66	Ericsson 4480 B71/B85, Ericsson 4460 B25/B66	Ericsson 4480 B71/B85, Ericsson 4460 B25/B66	
RRU Dimensions (HxWxD) (in)	21.80 x 15.70 x 7.50, 19.60 x 15.70 x 12.10	21.80 x 15.70 x 7.50, 19.60 x 15.70 x 12.10	21.80 x 15.70 x 7.50, 19.60 x 15.70 x 12.10	
RRU Weight	84.00, 109.00	84.00, 109.00	84.00, 109.00	
Surge Suppressor Quantity	NA	NA	NA	
Surge Suppressor Manufacturer & Model	NA	NA	NA	
Surge Suppressor Dimensions (HxWxD)	NA	NA	NA	
Surge Suppressor Weight	NA	NA	NA	
TMA Quantity	NA	NA	NA	
TMA Manufacturer & Model	NA	NA	NA	
TMA Dimensions (HxWxD)	NA	NA	NA	
TMA Weight	NA	NA	NA	
RET Quantity	NA	NA	NA	
RET Manufacturer and Model	NA	NA	NA	
RET Dimensions (HxWxD)	NA	NA	NA	
RET Weight	NA	NA	NA	
Mount Type /Mfg /Model (Attach spec sheet)	SitePro / RMQP- 496-HK			
Tower Mount Mounting Height	94'	94'	94'	
Coax Cables Quantity (Please specify "PER ANTENNA" or "PER SECTOR" for all coax / lines)	NA	NA	NA	
Diameter of Coax Cables (in)	NA	NA	NA	
Hybrid Fiber/Power Cables Quantity	1	1	1	
Diameter of Hybrid Fiber/Power Cables (in)	1.75	1.75	1.75	
RET Control Cable Quantity	NA	NA	NA	
RET Control Cable Diameter	NA	NA	NA	
Transmit Frequency (MHz)	1930-1945, 1965- 1970, 1970-1975, 2135-2140, 2140- 2145, 2145-2150, 2150-2155, 668-673, 673-678, 678-683, 683-688, 728-734, 2496-2690, 1990-1995	1930-1945, 1965- 1970, 1970-1975, 2135-2140, 2140- 2145, 2145-2150, 2150-2155, 668-673, 673-678, 678-683, 683-688, 728-734, 2496-2690, 1990-1995	1930-1945, 1965- 1970, 1970-1975, 2135-2140, 2140- 2145, 2145-2150, 2150-2155, 668-673, 673-678, 678-683, 683-688, 728-734, 2496-2690, 1990-1995	
Receive Frequency (MHz)	1850-1865, 1885- 1890, 1890-1895, 1735-1740, 1740- 1745, 1745-1750, 1750-1755, 622-627, 627-632, 632-637, 637-642, 698-704, 2496-2690, 1910-1915	1850-1865, 1885- 1890, 1890-1895, 1735-1740, 1740- 1745, 1745-1750, 1750-1755, 622-627, 627-632, 632-637, 637-642, 698-704, 2496-2690, 1910-1915	1850-1865, 1885- 1890, 1890-1895, 1735-1740, 1740- 1745, 1745-1750, 1750-1755, 622-627, 627-632, 632-637, 637-642, 698-704, 2496-2690, 1910-1915	



TowerCo

Colocation Application

Type of Service (i.e. LTE, CDMA,GSM)	5G	
Is FirstNet being added to this site? <input type="checkbox"/> YES <input type="checkbox"/> NO		
GROUND SPACE REQUIREMENTS		
Equipment Enclosure Type:	<input checked="" type="checkbox"/> BTS Cabinets/Number of BTS Cabinets: 2 <input type="checkbox"/> Outdoor Shelter <input type="checkbox"/> Other:	
Total Leased Area Dimensions (WxD) (ft)	10 x 20	
Cabinet/BTS/Shelter Dimensions (HxWxD)(ft):		
Concrete Pad Dimensions (WxD)(ft):	10 x 20	
Cabinet/Shelter Manufacturer/Model:	Ericsson	
POWER REQUIREMENTS		
AC Power: 240/120	Required Voltage and Total Amperage: 200	
GENERATOR INFORMATION		
Generator Ground Space Requirement (HxWxD) (ft):	83" x 38"	Fuel Type: <input type="checkbox"/> Propane <input checked="" type="checkbox"/> Diesel
Fuel Tank Size (Gallons):	130	Fuel Tank Location: Attached Separate None TBD
Capacity (KW):	125	
ADDITIONAL INFORMATION/COMMENTS		
<p>T-Mobile's RF requirements are RAD center of 94'. The tower will need to be extended to 99' to accommodate.</p>		

- Ground lessor consent may be required as a condition to the execution of your lease.
- Modifications to the tower site may be subject to local zoning approval.
- If available, attach manufacturer's equipment specifications for antennas, mounts, cabinets, shelters, etc.
- When requesting ground space, do not include a buffer around your desired physical footprint. TowerCo , at its sole discretion, will provide a non-exclusive buffer between your installation and other proposed and/or existing tenants to allow for access and maintenance