CHAPTER 1 INTRODUCTION TO MIXED-USE (MU) ZONES

100 GENERAL PROVISIONS

- 100.1 Subtitle G is to be read and applied in addition to the regulations included in:
 - (a) Subtitle A, Authority and Applicability;
 - (b) Subtitle B, Definitions, Rules of Measurement, and Use Categories;
 - (c) Subtitle C, General Rules;
 - (d) Subtitle H, Neighborhood Mixed-Use (NC) Zones; and
 - (e) Subtitle U, Use Permissions

The Mixed-Use (MU) zones provide for mixed-use developments that permit a broad range of commercial, institutional, and multiple dwelling unit residential development at varying densities.

- For those zones with a geographic identifier, the zone boundaries are described in Subtitle W, Specific Zone Boundaries and identified on the official Zoning Map. The MU zones are designed to provide facilities for housing, shopping, and business needs, including residential, office, service, and employment centers.
- In addition to the purpose statements of individual chapters, the purposes of the MU zones are to:
 - (a) Provide for the orderly development and use of land and structures in the MU zones, characterized by a mixture of land uses;
 - (b) Provide for a varied mix of residential, employment, retail, service, and other related uses at appropriate densities and scale throughout the city;
 - (c) Reflect a variety of building types, including, but not limited to, shop-front buildings which may include a vertical mixture of residential and non-residential uses, buildings made up entirely of residential uses, and buildings made up entirely of non-residential uses;
 - (d) Encourage safe and efficient conditions for pedestrian and motor vehicle movement;
 - (e) Ensure that infill development is compatible with the prevailing development pattern within the zone and surrounding areas;

- (f) Preserve and enhance existing commercial nodes and surroundings by providing an appropriate scale of development and range of shopping and service opportunities; and
- (g) Ensure that buildings and developments around fixed rail stations, transit hubs, and streetcar lines are oriented to support active use of public transportation and safety of public spaces.
- In the MU zones, buildings may be entirely **permitted** residential **uses**, or may be a mixture of **permitted** non-residential and residential uses.

101 PURPOSE AND INTENT DEVELOPMENT STANDARDS

- 101.1 The Mixed-Use (MU) zones provide for mixed-use developments that permit
 a broad range of commercial, institutional, and multiple dwelling residential
 development at varying densities. The bulk of structures in the MU zones shall
 be controlled through the combined general development standards of this
 subtitle, the zone specific development standards of this subtitle, and the
 requirements and standards of Subtitle C.
- 101.2 <u>The MU zones are designed to provide facilities for housing, shopping, and business needs, including residential, office, service, and employment centers.</u>

The development standards are intended to:

- (a) Control the bulk or volume of structures, including height, floor area ratio (FAR), and lot occupancy;
- (b) Control the location of building bulk in relation to adjacent lots and streets, by regulating rear yards, side yards, and the relationship of buildings to street lot lines;
- (c) Regulate the mixture of uses; and
- (d) Ensure the environmental performance of development.

101.3 The MU zones are intended to:

- (a) Provide for the orderly development and use of land and structures in the MU zones, characterized by a mixture of land uses;
- (b) Provide for a varied mix of residential, employment, retail, service, and other related uses at appropriate densities and scale throughout the city;
- (c) Reflect a variety of building types, including, but not limited to, shopfront buildings which may include a vertical mixture of residential and non-residential uses, buildings made up entirely of residential

uses, and buildings made up entirely of non-residential uses;

- (d) Encourage safe and efficient conditions for pedestrian and motor vehicle movement;
- (e) Ensure that infill development is compatible with the prevailing development pattern within the zone and surrounding areas;
- (f) Preserve and enhance existing commercial nodes and surroundings by providing an appropriate scale of development and range of shopping and service opportunities; and
- Ensure that buildings and developments around fixed rail stations, transit hubs, and streetcar lines are oriented to support active use of public transportation and safety of public spaces.

The development standards may include allowances for the provision of affordable housing consistent with the Inclusionary Zoning provisions of Subtitle C, Chapter 10 and will be so indicated by the letters "IZ" in the development standards table.

101.4 The purposes of the MU-1 and MU-2 zones are to:

- (a) Act as a buffer between adjoining non-residential and residential areas, and to ensure that new development is compatible in use, scale, and design with the transitional function of this zone;
- (b) Preserve and protect areas adjacent to non-residential uses or zones that contain a mix of row houses, apartments, offices, and institutions at a medium to high density, including buildings of historic and architectural merit; and
- (c) Permit new residential development at a higher density than new office or institutional developments.

The bulk of public buildings and structures in the MU zones shall be controlled through the development standards specified in Subtitle G, Chapter 10 and the regulations of this chapter.

101.5 The MU-1 zone is intended to permit moderate-density development in areas predominantly developed with residential buildings but also permitting non-residential buildings.

The development standards may be varied or waived by the Board of Zoning Adjustment as a variance or, when permitted in this title, as a special exception. Relief from the development standards for Height and FAR shall be required as a variance. Additional zone specific special exception criterion, if applicable, shall be considered by the Board and are referenced in this subtitle.

101.6 The MU-2 zone is intended to permit medium-density development in areas predominantly developed with residential buildings but also permitting non-residential buildings.

In addition to the development standards set forth in this subtitle, additional general regulations relevant to this Subtitle can be found in Subtitle C.

101.7 The MU-3 through MU-10 and the MU-15 zones are mixed-use zones that are intended to be applied throughout the city consistent with the density designation of the Comprehensive Plan. A zone may be applied to more than one (1) density designation.

101.8 The MU-3 zones are intended to:

- (a) Permit low-density mixed-use development; and
- (b) Provide convenient retail and personal service establishments for the day-to-day needs of a local neighborhood, as well as residential and limited community facilities with a minimum impact upon surrounding residential development.

101.9 The MU-4 zone is intended to:

- (a) Permit moderate-density mixed-use development;
- (b) Provide facilities for shopping and business needs, housing, and mixed uses for large segments of the District of Columbia outside of the central core; and
- (c) Be located in low- and moderate-density residential areas with access to main roadways or rapid transit stops, and include office employment centers, shopping centers, and moderate bulk mixed-use centers.

101.10 The MU-5 zones are intended to:

- (a) Permit medium-density, compact mixed-use development with an emphasis on residential use;
- (b) Provide facilities for shopping and business needs, housing, and mixed-uses for large segments of the District of Columbia outside of the central core; and
- (c) Be located on arterial streets, in uptown and regional centers, and at rapid transit stops.

101.11 The MU-6 zone is intended to:

- (a) Permit medium- to high-density mixed-use development with a focus on residential use; and
- (b) Provide facilities for shopping and business needs, housing, and mixed-uses for large segments of the District of Columbia outside of the central core.

101.12 The MU-7 zone is intended to:

- (a) Permit medium-density mixed-use development; and
- (b) Be located on arterial streets, in uptown and regional centers, and at rapid transit stops.

101.13 The MU-8 zone is intended to:

- (a) Permit medium-density mixed-use development with a focus on employment;
- (b) Be located in uptown locations, where a large component of development will be office-retail and other non-residential uses; and
- (c) Be located in or near the Central Employment Area, on arterial streets, in uptown and regional centers, and at rapid transit stops.

101.14 The MU-9 zone is intended to:

- (a) Permit high-density mixed-use development including office, retail, and housing, with a focus on employment; and
- (b) Be located in or near the Central Employment Area, on arterial streets, in uptown and regional centers, and at rapid transit stops.

101.15 The MU-10 zone is intended to:

- (a) Permit medium- to high-density mixed-use development with a balance of uses conducive to a higher quality of life and environment for residents, businesses, employees, and institutions;
- (b) Be applied to areas where a mixture of uses and building densities is intended to carry out elements of the Comprehensive Plan, small area plans, or framework plans, including goals in employment, population, transportation, housing, public facilities, and environmental quality;
- (c) Require a level of public space at the ground level; and

(d) Allow residential and non-residential bulk to be apportioned between two (2) or more lots in the same square

101.16 The MU-15 zone is intended to:

- (a) Permit high-density mixed-use development including office, retail, and housing, with a focus on employment; and
- (b) Be located in or near the downtown core that comprises the retail and office centers for both the District of Columbia and the metropolitan area.

102 USE PERMISSIONS

102.1 Use permissions for the MU zones are as specified in Subtitle U, Chapter 5.

103 PARKING

Parking requirements for the MU zones are as specified in Subtitle C, Chapters 7 and 8.

104 INCLUSIONARY ZONING

The Inclusionary Zoning (IZ) requirements, and the available IZ modifications and bonus density, shall apply to all MU zones, except for the portion of the MU-13 zone in the Georgetown Historic District and the MU-27 zone, as specified in Subtitle C, Chapter 10, Inclusionary Zoning, and in the zone-specific development standards of this subtitle; provided that new penthouse habitable space, as described in Subtitle C § 1500.11, that is located in the portion of the MU-13 zone in the Georgetown Historic District or in the MU-27 zone shall be subject to the IZ requirements.

105 102 PUBLIC SCHOOLS, PUBLIC RECREATION AND COMMUNITY CENTERS, AND PUBLIC LIBRARIES

- 105.1 102.1 Public recreation and community centers or public libraries in the MU zones shall be permitted subject to the conditions of Subtitle C, Chapter 16.
- 105.2 <u>102.2</u> Public schools in the MU zones shall be permitted subject to the conditions of Subtitle G, Chapter 49.
- 105.3 <u>102.3</u> Development standards not otherwise addressed by Subtitle C, Chapter 16, or Subtitle G, Chapter 49, shall be those development standards for the zone in which the buildings or structures is proposed.

CHAPTER 2 GENERAL PROVISIONS DEVELOPMENT STANDARDS FOR MU MIXED USE ZONES - MU-1 THROUGH MU-10 AND MU-15

200 DEVELOPMENT STANDARDS GENERAL PROVISIONS

- The provisions of this chapter apply to all MU zones except as may be modified or otherwise provided for in a specific zone. The <u>development</u> standards of this chapter shall apply to <u>all the MU-1 through MU-10 and the MU-15</u> Mixed Use (MU) zones except as modified by a specific zone, in which case the modified zone-specific standard shall apply. When only a <u>section or subsection portion</u> of a development standard is modified the remaining <u>sections or subsections</u> <u>portions</u> of the development standard shall still apply.
- When modified or otherwise provided for in the development standards for a specific zone, the modification or zone-specific standard shall apply. The development standards regulate the bulk of buildings and other structures and the spaces around them, including the following:
 - a. Height and number of stories;
 - b. Density and lot occupancy;
 - c. Yards and setbacks; and
 - d. **Environmental performance of development.**
- 200.3 Development standards may be varied by the Board of Zoning Adjustment as a variance or, when permitted in this title, as a special exception.

 Additional zone-specific special exception criterion, if applicable, are referenced in this subtitle and shall be considered by the Board.
- 200.4 The Inclusionary Zoning (IZ) requirements, and the available IZ

 modifications to certain development standards and bonus density, shall
 apply to the MU zones as specified in Subtitle C, Chapter 10, Inclusionary
 Zoning, except as provided in Subtitle G § 200.5.
- 200.5 Notwithstanding Subtitle G § 200.4, except for new penthouse habitable space as described in Subtitle C § 1500.11, the Inclusionary Zoning requirements and modifications to certain development standards and bonus density of Subtitle C, Chapter 10 shall not apply to the MU-4/NO zone.
- 201 DENSITY —FLOOR AREA RATIO (FAR)

For a building or structure in existence with a valid Certificate of Occupancy prior to November 17, 1978, or for which an application for a building permit was filed prior to November 17, 1978, a conversion of non-residential gross floor area GFA to residential GFA gross floor area, even if in excess of otherwise permitted floor area ratio FAR, shall be permitted.

201.2 Except as provided elsewhere in this title, the maximum permitted floor area ratio (FAR) shall be as set forth in the following table:

TABLE G § 201.2: MAXIMUM PERMITTED FLOOR AREA RATIO

	Maxi	Maximum FAR	
Zone	Total Permitted	<u>Maximum Non-</u> <u>Residential Use</u>	
<u>MU-1</u>	4.0 4.8 (IZ)	2.5	
<u>MU-2</u>	6.0 7.2 (IZ)	3.5	
MU-3A	1.0 1.2 (IZ)	1.0	
<u>MU-3B</u>	2.0 2.4 (IZ)	1.5	
<u>MU-4</u>	2.5 3.0 (IZ)	1.5	
MU-5A	3.5 4.2 (IZ)	1.5	
<u>MU-5B</u>	3.5 4.2 (IZ)	1.5	
<u>MU-6</u>	6.0 7.2 (IZ)	2.0	
<u>MU-7</u>	4.0 4.8 (IZ)	2.5	
<u>MU-8</u>	5.0 6.0 (IZ)	4.0	
<u>MU-9</u>	6.5 7.8 (IZ)	6.5	
<u>MU-10</u>	6.0 7.2 (IZ)	3.0	

In the MU-4 and MU-5 zones, an existing building on a lot with an area ten thousand square feet (10,000 sq. ft.) or less, may have a maximum density of 2.0 FAR for non-residential uses, provided the uses are located in the ground story and the story directly above the ground story. For new construction, any additional use is limited to 0.5 FAR.

- 201.4 In the MU-10 zone, combined lot development is permitted for the purposes of allocating gross floor area devoted to residential and non-residential uses in accordance with the provisions of Subtitle C, Chapter 12. Both lots shall be located within the same square and shall be zoned MU-10.
- 201.5 In the MU-15 zone, the maximum permitted FAR shall be as set forth in the following table, except as provided elsewhere in this title:

TABLE G § 201.5: MAXIMUM PERMITTED FLOOR AREA RATIO

	Maximum FAR	
MU-15 Zone Height	Total Permitted	<u>Maximum</u> <u>Non-Residential Use</u>
Buildings erected to a height of one hundred ten feet (110	<u>8.5</u>	9.5
ft.) or less	<u>10.2 (IZ)</u>	<u>8.5</u>
Buildings erected to a height in excess of one hundred ten	10.0	10.0
feet (110 ft.) as permitted in Subtitle G § 203.3	12.0 (IZ)	10.0

- 201.6 A public recreation and community center in a MU-1, MU-2 or MU-10 zone shall not exceed a gross floor area of forty thousand square feet (40,000 sq. ft.), unless approved by the Board of Zoning Adjustment as a special exception pursuant to the provisions of Subtitle X, Chapter 9.
- 201.7 A public recreation and community center shall not exceed a 1.8 FAR in the MU-1 and MU-2 zones.

202 COURTS [RESERVED]

202.1 A court is not required in an MU zone, but where it is provided, it shall have the following minimum dimensions:

TABLE G § 202.1: MINIMUM COURT DIMENSIONS

Type of Structure	Minimum Width Open Court	Minimum Width Closed Court	Minimum Area Closed Court
Residential, more than 3 units	4 in./ft. of height of court;	4 in./ft. of height of court;	Twice the square of the required width of court dimension;
	10 ft. minimum	15 ft. minimum	350 sq. ft. minimum
Non-Residential and Lodging	2.5 in./ft. of height of court;	2.5 in./ft. of height of court;	Twice the square of the required width of court dimension;
	6 ft. minimum	12 ft. minimum	250 sq. ft. minimum

203 PENTHOUSES

203.1 Penthouses shall be subject to the regulations of Subtitle C, Chapter 15 and the height and story limitations specified in each zone of this subtitle.

203 HEIGHT

- 203.1 Except as provided elsewhere in this title, the maximum permitted height of buildings or structures, not including the penthouse, and the maximum number of stories shall be as set forth in this section.
- 203.2 The maximum permitted height of buildings or structures and number of stories, except as provided in Subtitle G §§ 203.3 through 203.4, shall be as set forth in the following table:

TABLE G § 203.2: MAXIMUM HEIGHT AND NUMBER OF STORIES

Zone	Maximum Height, Not	Maximum Number of
	Including penthouse (ft.)	<u>Stories</u>
<u>MU-1</u>	<u>65</u>	N/A
	70 (IZ)	<u>N/A</u>
<u>MU-2</u>	90	<u>N/A</u>
<u>MU-3A</u>	40	<u>3</u>
<u>MU-3B</u>	50	4
<u>MU-4</u>	50	<u>N/A</u>
MU-5A	<u>65</u>	NI/A
	70 (IZ)	<u>N/A</u>
<u>MU-5B</u>	<u>75</u>	<u>N/A</u>
<u>MU-6</u>	90	N/A
	100 (IZ)	
<u>MU-7</u>	<u>65</u>	<u>N/A</u>
<u>MU-8</u>	<u>70</u>	<u>N/A</u>
<u>MU-9</u>	<u>90</u>	N/A
<u>MU-10</u>	100 (IZ)	<u>N/A</u>
<u>MU-15</u>	<u>110</u>	<u>N/A</u>

- 203.3 In the MU-15 zone, a building or other structure may be erected to a height not exceeding one hundred-thirty feet (130 ft.); provided, that the building or other structure shall face or abut a street not less than one hundred-ten feet (110 ft.) wide between building lines.
- 203.4 A public recreation and community center in a MU-1, MU-2 or MU-10 zone shall not exceed a height of forty-five feet (45 ft.)

204 TRANSITION SETBACK REQUIREMENTS

204.1 In the MU-3B zone the following transition setback requirements shall apply to any building or portion of a building within thirty feet (30 ft.) of a lot line directly abutting an R zone district:

- (a) A twenty-foot (20 ft.) minimum transition setback shall be provided from any lot line directly abutting an R zone district extended as a vertical plane parallel to each abutting lot line. No building or portion of a building may be constructed within the twenty-foot (20 ft.) transition setback; and
- (b) An additional upper-story transition setback of ten feet (10 ft.) minimum shall be provided above a building height of forty feet (40 ft.), or top of third story.
- 204.2 Any required transition setback area shall not be used for loading.
- 204.3 A minimum of six feet (6 ft.) of the transition setback area, measured in from the abutting residential lot line, shall be landscaped with evergreen trees subject to the following conditions:
 - (a) The trees shall be maintained in a healthy growing condition;
 - (b) The trees shall be a minimum of eight feet (8 ft.) high when planted; and
 - (c) Planting locations and soil preparation techniques shall be shown on a landscape plan submitted with the building permit application to the Department of Consumer and Regulatory Affairs for review and approval according to standards maintained by the Department's Soil Erosion and Storm Management Branch, which may require replacement of heavy or compacted soils with top and drainage mechanisms as necessary.
- A required transition setback may be inclusive of a required side or rear yard provided all conditions of each section are met.
- No residential communal outdoor recreation space shall be located within fifty feet (50 ft.) of any lot line directly abutting an R zone district extended as a vertical plane parallel to each abutting lot line.

205 PENTHOUSES

- 205.1 A penthouse on a single household dwelling or flat shall be permitted only in accordance with Subtitle C § 1500.4.
- 205.2 The maximum permitted height of a penthouse shall be as set forth in the following table:

TABLE G § 205.2: MAXIMUM PENTHOUSE HEIGHT AND STORIES

Zone	Maximum Penthouse	Maximum Penthouse Stories
	Height	

<u>MU-1</u>	12 ft., except 18 ft. 6 in. for penthouse mechanical space	1: Second story permitted for penthouse mechanical space
<u>MU-2</u>	20 ft.	1 plus mezzanine: Second story permitted for penthouse mechanical space
MU-3A MU-3B MU-4	12 ft., except 15 ft. for penthouse mechanical space	1: Second story permitted for penthouse mechanical space
MU-5A MU-7	12 ft., except 18 ft. 6 in. for penthouse mechanical space	1: Second story permitted for penthouse mechanical space
MU-5B MU-8	20 ft.	1: Second story permitted for penthouse mechanical space
MU-6 MU-9 MU-10 MU-15	<u>20 ft.</u>	1 plus mezzanine; Second story permitted for penthouse mechanical space

206 [RESERVED]

207 REAR YARD

- 207.1 Except as provided elsewhere in this title, the minimum required rear yard shall be as set forth in this section.
- 207.2 In all MU zones, where a lot does not abut an alley, the rear yard shall be measured from the rear lot line to the rear wall of the building or other structure.
- 207.3 In the MU-1 through MU-9 and the MU-15 zones, a horizontal plane may be established at twenty feet (20 ft.) above the mean finished grade at the middle of the rear of the structure for the purpose of measuring rear yards.
- 207.4 In the MU-1 and MU-2 zones a rear yard shall be established subject to the following conditions:
 - (a) A minimum rear yard of two and one-half inches (2.5 in.) per one foot (1 ft.) of vertical distance from the mean finished grade at the middle of the rear of the structure to the highest point of the main roof or parapet wall, but not less than twelve feet (12 ft.) shall be required above a horizontal plane as described in Subtitle G § 207.3;
 - (b) A rear yard is not required to be provided below a horizontal plane as described in Subtitle G § 207.3; and

- (c) Where a lot abuts an alley, the rear yard may be measured from the center line of the alley to the rear wall of the building or other structure.
- 207.5 In the MU-3 zone a minimum rear yard of twenty feet (20 ft.) shall be provided.
- 207.6 In the MU-4, MU-5, and MU-6 zones a minimum rear yard of fifteen feet (15 ft.) shall be provided.
- 207.7 In the MU-7, MU-8, MU-9, MU-10, and MU-15 zones a minimum rear yard of two and one-half inches (2.5 in.) per one foot (1 ft.) of vertical distance from the mean finished grade at the middle of the rear of the structure to the highest point of the main roof or parapet wall, but not less than twelve feet (12 ft.) shall be provided.
- 207.8 In the MU-3 MU-4, MU-5, MU-6, and MU-7 zones, where a lot abuts an alley rear yards shall be measured as follows:
 - (a) For that portion of the structure below a horizontal plane described in Subtitle G § 207.3 from the center line of the alley to the rear wall of the portion; and
 - (b) For that portion of the structure above the horizontal plane described in Subtitle G § 207.3, from the rear lot line to the rear wall of that portion immediately above the plane.
- 207.9 In the MU-8, MU-9, and MU-15 zones, a rear yard shall be established subject to the following conditions:
 - (a) A rear yard is not required to be provided below a horizontal plane as described in Subtitle G § 207.3; and
 - (b) Where a lot abuts an alley, the rear yard may be measured from the center line of the alley to the rear wall of the building or other structure.
- 207.10 In the MU-10 zone, rear yards are required only for residential uses and shall be established subject to the following conditions:
 - (a) A rear yard shall be established no lower than the first level of residential use; and
 - (b) Where a lot abuts an alley, the rear yard may be measured from the center line of the alley to the rear wall of the building or other structure.

- In the case of a through lot or a corner lot abutting three (3) or more streets, the depth of rear yard may be measured from the center line of the street abutting the lot at the rear of the building or other structure. Does not exist in ZR16 but did exist for all MU zones in ZR58 SP Zone § 534.4; CR Zone § 636.5; C Zone § 774.11
- 207.12 The Board of Zoning Adjustment may grant relief to the rear yard requirements of this subtitle as a special exception pursuant to Subtitle X, Chapter 9 provided:
 - (a) No apartment window shall be located within forty feet (40 ft.) directly in front of another building;
 - (b) No office window shall be located within thirty feet (30 ft.) directly in front of another office window, nor eighteen feet (18 ft.) in front of a blank wall;
 - (c) In buildings that are not parallel to the adjacent buildings, the angle of sight lines and the distance of penetration of sight lines into habitable rooms shall be considered in determining distances between windows and appropriate yards;
 - (d) Provision shall be included for service functions, including parking and loading access and adequate loading areas; and
 - (e) Upon receiving an application to waive rear yard requirements in the subject zone, the Board of Zoning Adjustment shall submit the application to the Office of Planning for coordination, review, report, and impact assessment, along with reviews in writing from all relevant District of Columbia departments and agencies, including the Department of Transportation, the District of Columbia Housing Authority and, if a historic district or historic landmark is involved, the Historic Preservation Office.

208 SIDE YARD

- 208.1 Except as provided elsewhere in this title, the minimum side yard shall be as set forth in this section.
- 208.2 In the MU-1 through MU-9 and MU-15 zones, no side yard is required for a building or structure other than a detached or semi-detached single household dwelling; however, if a side yard is provided, it shall be at least two inches (2 in.) wide for each one foot (1 ft.) of height of building, but no less than five feet (5 ft.).

- 208.3 In the MU-1 through MU-9 zones, a minimum side yard of eight feet (8 ft.) shall be provided for a detached or semi-detached single household dwelling.
- 208.4 In the MU-10 zone no side yard is required for a principal building;

 however, if a side yard is provided it shall be at least two inches (2 in.) wide
 for each one foot (1 ft.) of height of building but no less than five feet (5 ft.).
- 208.5 Any portion of a building set back from the side lot line shall be considered a side yard and not a court.

209 COURT

209.1 Courts are not required; however, where a court is provided, the court shall have the following minimum dimensions:

TABLE G § 209.1: MINIMUM COURT DIMENSIONS

Type of Structure	Minimum Width Open Court	Minimum Width Closed Court	Minimum Area Closed Court
Residential, more than 3 units	4 in./ft. of height of court;	4 in./ft. of height of court;	Twice the square of the required width of court dimension;
	10 ft. minimum	15 ft. minimum	350 sq. ft. minimum
All Other Structures	2.5 in./ft. of height of court;	2.5 in./ft. of height of court;	Twice the square of the required width of court dimension;
	6 ft. minimum	12 ft. minimum	250 sq. ft. minimum

210 LOT OCCUPANCY

210.1 Except as provided elsewhere in this title, the maximum permitted lot occupancy for a residential use shall be as set forth in the following table:

TABLE G § 210.1: MAXIMUM LOT OCCUPANCY

Zone	Maximum Lot Occupancy for Residential Use
<u>MU-1</u>	80 %
<u>MU-2</u>	80 % 90 % (IZ)
<u>MU-3A</u>	60 % 60 % (IZ)
<u>MU-3B</u>	60 % 60 % (IZ)
<u>MU-4</u>	60 % 75 % (IZ)

Zone	Maximum Lot Occupancy for Residential Use
<u>MU-5-A</u>	<u>80 %</u>
<u>MU-5-B</u>	80 % (IZ)
MILC	<u>75 %</u>
<u>MU-6</u>	80 % (IZ)
MILE	<u>75 %</u>
<u>MU-7</u>	80 % (IZ)
<u>MU-8</u>	100 %
<u>MU-9</u>	100 %
MIL 10	<u>75 %</u>
<u>MU-10</u>	80 % (IZ)
<u>MU-15</u>	<u>100 %</u>

- 210.2 In the MU-10 zone, the percentage of lot occupancy may be calculated on a horizontal plane located at the lowest level where residential uses begin.
- 210.3 In the MU-10 zone, for the purposes of this section, the phrase "residential uses" includes dwellings, flats, multiple dwellings, rooming and boarding houses, hospitals, and community-based residential facilities.
- 210.4 In the MU-1, MU-2, or MU-10 zone, a public recreation and community center shall not occupy more than twenty percent (20%) of the lot upon which it is located; except that it may occupy up to forty percent (40%) if approved by the Board of Zoning Adjustment as a special exception pursuant to Subtitle X, Chapter 9, provided that the agency shows that the increase is consistent with agency policy of preserving open space.
- 210.5 Notwithstanding Subtitle G § 210.1, lots 835 and 840 located on Square 5539 shall not exceed a sixty percent (60%) maximum lot occupancy for all residential and non-residential uses.

211 GREEN AREA RATIO (GAR)

211.1 The minimum required green area ratio shall be as set forth in the following table:

TABLE G § 211.1: MINIMUM GREEN AREA RATIO (GAR)

<u>Zone</u>	Minimum Green Area Ratio
MU-1, MU-2, MU-3, MU-4, MU-5, MU-6	0.30
MU-7, MU-8	0.25
MU-9, MU-10, MU-15	0.20

- 212 PLAZA
- 212.1 In the MU-10 zone, a plaza comprising eight percent (8%) of the lot area shall be provided for development on a lot of greater than ten thousand square feet (10,000 sq. ft.), in accordance with the provisions of Subtitle C, Chapter 17.
- Where preferred use space is required under this chapter and provided, the requirement to provide plaza space shall not apply.

213 SPECIAL EXCEPTION

213.1 Except for height and floor area ratio, exceptions to the development standards of this chapter shall be permitted as a special exception if approved by the Board of Zoning Adjustment under Subtitle X, Chapter 9, and subject to the provisions and limitations of Subtitle G, Chapter 52.

214 COMBINED LOT

- 214.1 The following combined lot development provision shall apply to the MU-10 zone only:
 - (a) The allowable residential and non-residential bulk of a MU-10 zone may be apportioned between two (2) or more lots in the same square, regardless of the limits on floor area; provided, that the aggregate residential and non-residential floor area may not exceed the zone limits;
 - (b) A covenant running with the land and applicable to all properties involved in the apportionment shall be executed by all of the owners of the properties and the District of Columbia government prior to the issuance of any building permits. The covenant shall be for the purpose of insuring that the aggregate residential and non-residential floor area does not exceed the limits applicable to residential and non-residential uses; and
 - (c) For the purposes of this section, the term "residential purposes" shall include dwellings, flats, multiple dwellings, rooming and boarding houses, community-based residential facilities, inns, and guest room areas and service areas within hotels.

CHAPTER 3 <u>DEVELOPMENT STANDARDS FOR MIXED-USE</u> <u>WATERFRONT ZONES - MU-1 AND MU-2 MU-11, MU-12, MU-13, AND MU-14</u>

300 PURPOSE AND INTENT

300.1	The purposes of the MU-1 and MU-2 zones are to:
	(a) Act as a buffer between adjoining non-residential and residential areas, and to ensure that new development is compatible in use, scale, and design with the transitional function of this zone;
	(b) Preserve and protect areas adjacent to non-residential uses or zones that contain a mix of row houses, apartments, offices, and institutions at a medium to high density, including buildings of historic and architectural merit; and
	(c) Permit new residential development at a higher density than new office or institutional developments.
300.2	The MU-1 zone is intended to permit moderate density areas predominantly developed with residential buildings but also permitting non-residential buildings.
300.3	The MU-2 zone is intended to permit medium-density areas predominantly developed with residential buildings but also permitting non-residential buildings.
300.1	The MU-11, MU-12, MU-13 and MU-14 zones are mixed-use zones that are
300.2	intended to be applied generally in the vicinity of the waterfront. The MU-11 zone is intended to:
	(a) Permit open space, park, and low-density and low-height waterfront- oriented retail and arts uses; and
	(b) Be applied in undeveloped waterfront areas.
300.3	The MU-12 zone is intended to permit moderate-density mixed-use development generally in the vicinity of the waterfront.
300.4	The MU-13 zone is intended to permit medium-density mixed-use
300.5	development generally in the vicinity of the waterfront. The MU-14 zone is intended to permit high-density mixed-use development generally in the vicinity of the waterfront.

301 DEVELOPMENT STANDARDS

- 301.1 The development standards of this chapter modify the general development standards in Subtitle G, Chapter 2 shall apply to the MU-11 through MU-14 Mixed Use (MU) Waterfront zones except as modified by a specific zone, in which case the modified zone-specific standard shall apply. When only a portion of a development standard is modified the remaining portions of the development standard shall still apply.
- 301.2 The development standards regulate the bulk of buildings and other structures and the spaces around them, including the following:
 - a. Height and number of stories;
 - b. Density and lot occupancy;
 - c. Yards and setbacks; and
 - d. Environmental performance of development.
- 301.3 Development standards may be varied by the Board of Zoning Adjustment as a variance or, when permitted in this title, as a special exception.

 Additional zone-specific special exception criterion, if applicable, are referenced in this subtitle and shall be considered by the Board.
- The Inclusionary Zoning (IZ) requirements, and the available IZ

 modifications to certain development standards and bonus density shall
 apply to the MU-11, MU-12 and MU-14 zones as specified in Subtitle C,
 Chapter 10, Inclusionary Zoning, except as provided in G § 301.5 and in the
 zone-specific development standards of this subtitle.
- 301.5 Notwithstanding Subtitle G § 301.4, except for new penthouse habitable space as described in Subtitle C § 1500.11, the IZ requirements and modifications to certain development standards and bonus density of Subtitle C, Chapter 10 shall not apply to the portion of the MU-13 zone in the Georgetown Historic District.

302 DENSITY – FLOOR AREA RATIO (FAR)

302.1 Except as provided elsewhere in this title, the maximum permitted floor area ratio (FAR) The maximum permitted FAR of buildings in the MU-1 and MU-2 zones shall be as set forth in the following table:

TABLE G § 302.1: MAXIMUM PERMITTED FLOOR AREA RATIO

	Maximum Permitted FAR	
Zone	Total Permitted	Maximum Non-
	10tai i eriintteu	Residential Use
MII 1	4.0	2.5
WIU I	4.8 (IZ)	2.3

MIL 2	6.0	3.5
WIU Z	7.2 (IZ)	5.5

	Maximum FAR	
Zone	Total Permitted	Maximum Non-Residential Use
MU-11	0.5	0.5
MU-12	2.5 3.0 (IZ)	1.0
MU-13	4.0 4.8 (IZ)	2.0
MU-14	6.0 7.2 (IZ)	- 5.0

- In the MU-11, MU-12, MU-13 and MU-14 zones, the guestroom areas and service areas within lodging uses may be charged against the "Total Permitted" floor area ratio.
- In the MU-11 zone, the density on a lot used exclusively for recreational use, marina, yacht club, or boathouse buildings and structures shall not exceed 0.75 FAR; and for the purposes of this subsection, FAR shall be the gross floor area of all buildings and structures located on land and any associated permanent structure located on, in, or over water, other than a floating home, divided by the total area of the lot.
- A public recreation and community center shall not exceed a gross floor area of forty thousand square feet (40,000 sq. ft.), unless approved by the Board of Zoning Adjustment as a special exception pursuant to the provisions of Subtitle X, Chapter 9.
- A public recreation and community center shall not exceed a 1.8 FAR in the MU-12, MU-13, and MU-14 zones.

303 HEIGHT

Except as provided elsewhere in this title, the maximum permitted height of buildings or structures, not including the penthouse, shall be as set forth in this section.

The maximum permitted building height, not including the penthouse, in the MU-1 and MU-2 zones shall be as set forth in the following table:

TABLE G § 303.1: MAXIMUM PERMITTED BUILDING HEIGHT

Zono	Maximum Haight
Zone	Widaming High and

	(Feet)
MII 1	65
MU-1	70 (IZ)
MU-2	90

303.2 The maximum permitted height of buildings or structures, except as provided in Subtitle G §§ 303.3 through 303.4, shall be as set forth in the following table:

TABLE G § 303.2: MAXIMUM HEIGHT

Zone	Maximum Height, Not Including Penthouse (ft.)
<u>MU-11</u>	40
<u>MU-12</u>	45 50 (IZ)
<u>MU-13</u>	<u>60</u>
<u>MU-14</u>	90 100 (IZ)

The maximum permitted height of a penthouse, except as prohibited on the roof of a detached dwelling, semi-detached dwelling, rowhouse, or flat in Subtitle C § 1500.4, shall be as set forth in the following table:

TABLE G \$ 303.2: MAXIMUM PERMITTED PENTHOUSE HEIGHT AND STORIES

ZONE	Maximum Penthouse	Maximum Penthouse
	Height	Stories -
	12 ft., except	1;
MU-1	18 ft. 6 in. for penthouse	Second story permitted for
	mechanical space	penthouse mechanical space
		1 plus mezzanine;
MU-2	20 ft.	Second story permitted for
		penthouse mechanical space

In the MU-11 zone, a building or structure located on, in, or over the water; or a watercraft, including a floating home shall have a maximum height of twenty-five feet (25 ft.). For the purposes of this subsection, the maximum height shall be measured from the mean high water level along the shore directly in front of the building, structure, or watercraft to the highest point of the building or structure, not including sailboat masts. ; and

Penthouses less than ten feet (10 ft.) in height above a roof or parapet wall of a structure on Kingman Island shall not be subject to the requirements of Subtitle G, Chapters 11 and 12 of this subtitle when the top of the penthouse is below maximum building height prescribed for the MU-11 zone.

A public recreation and community center in a MU-12, MU-13 or MU-14 zone shall not exceed a height of forty-five feet (45 ft.)

304 LOT OCCUPANCY [RESERVED]

The maximum permitted lot occupancy for residential use in the MU-1 and MU-2 zones shall be as set forth in the following table:

TABLE G § 304.1: MAXIMUM PERMITTED LOT OCCUPANCY FOR RESIDENTIAL USE

Zone	Maximum Lot Occupancy (Percentage)
MU-1	80
MILO	80
WIU Z	90 (IZ)

305 REAR YARD

- A minimum rear yard of two and one half inches (2.5 in.) per one foot (1 ft.) of vertical distance from the mean finished grade at the middle of the rear of the structure to the highest point of the main roof or parapet wall, but not less than twelve feet (12 ft.) shall be required above a horizontal place as described in Subtitle G § 305.2 in the MU-1 and MU-2 zones.
- A horizontal plane may be established at twenty feet (20 ft.) above the mean finished grade at the middle of the rear of the structure for the purposes of measuring rear yards.
- A rear yard is not required to be provided below a horizontal plane as described in Subtitle G § 305.2.
- Where a lot abuts an alley, the rear yard may be measured from the center line of the alley to the rear wall of the building or other structure.
- Where a lot does not abut an alley, the rear yard shall be measured from the rear lot line to the rear wall of the building or other structure.

305 PENTHOUSES

The maximum permitted height of a penthouse, except as prohibited on the roof of a single household dwelling or flat in Subtitle C § 1500.4, shall be as set forth in the following table:

TABLE G § 305.1: MAXIMUM PERMITTED PENTHOUSE HEIGHT AND STORIES

Zone	Maximum Penthouse Height	<u>Maximum Penthouse</u> <u>Stories</u>
<u>MU-11</u>	12 ft. except	<u>1;</u>

<u>MU-12</u>	15 ft. for penthouse mechanical space	Second story permitted for penthouse mechanical space
<u>MU-13</u>	12 ft. except 18 ft. 6in. for penthouse mechanical space	1: Second story permitted for penthouse mechanical space
<u>MU-14</u>	<u>20 ft.</u>	1 plus mezzanine; Second story permitted for penthouse mechanical space

In the MU-11 zone, penthouses less than ten feet (10 ft.) in height above a roof or parapet wall of a structure on Kingman Island shall not be subject to the requirements of Subtitle G, Chapters 11 and 12 Subtitle C, Chapter 15 when the top of the penthouse is below the maximum building height prescribed for the MU-11 zone.

306 SIDE YARD [RESERVED]

- No side yard is required for a building or structure other than a detached single dwelling unit or semi-detached single dwelling unit; however, if a side yard is provided, it shall be at least two inches (2 in.) wide for each one foot (1 ft.) of height of building, but no less than five feet (5 ft.).
- A minimum side yard of eight feet (8 ft.) shall be provided for a detached or semidetached dwelling.
- Any portion of a building set back from the side lot line shall be considered a side yard and not a court.

307 GREEN AREA RATIO (GAR)

307.1 The minimum required GAR for the MU-1 and MU-2 zones shall be 0.3.

307 REAR YARD

- 207.1 Except as provided elsewhere in this title, the minimum required rear yard shall be as set forth in this section.
- A rear yard is required only for residential uses and shall be established no lower than the first level of residential use.
- A minimum rear yard of twelve feet (12 ft.) shall be provided in the MU-11, MU-12, MU-13, and MU-14 zones.
- Where a lot abuts an alley, the rear yard may be measured from the center line of the alley to the rear wall of the building or other structure.

- Where a lot does not abut an alley, the rear yard shall be measured from the rear lot line to the rear wall of the building or other structure.
- 307.6 The Board of Zoning Adjustment may waive rear yard requirements as a special exception pursuant to Subtitle X, Chapter 9 and Subtitle G § 207.12.

308 SPECIAL EXCEPTION

Exceptions to the development standards of this chapter shall be permitted as a special exception, if approved by the Board of Zoning Adjustment under Subtitle X, Chapter 9, and subject to the provisions and limitations of Subtitle G, Chapter 12.

308 SIDE YARD

- 308.1 Except as provided elsewhere in this title, the minimum side yard shall be as set forth in this section.
- In the MU-11 zone, a side yard for any building or structure located in whole or in part on land, shall be no less than twelve feet (12 ft.).
- No side yard shall be required in the MU-12, MU-13, and MU-14 zones. If a side yard is provided, its minimum width shall be at least eight feet (8 ft.).
- Any portion of a building set back from the side lot line shall be considered a side yard and not a court.

309 [RESERVED]

310 LOT OCCUPANCY

310.1 The maximum permitted lot occupancy for a residential use shall be as set forth in the following table:

TABLE G § 310.1: MAXIMUM PERMITTED LOT OCCUPANCY

Zone	Maximum Lot Occupancy for Residential Use
<u>MU-11</u>	<u>25%</u>
<u>MU-12</u>	80% 80% (IZ)
<u>MU-13</u>	75% 75% (IZ)
<u>MU-14</u>	75% 80% (IZ)

- 310.2 Within the MU-11 zone, no building or portion of a building, including accessory buildings, shall occupy greater than twenty-five percent (25%) of the lot upon which it is located, provided that:
 - (a) The lot occupancy on a lot used exclusively for a recreational use, marina, yacht club, or boathouse buildings and structures shall not exceed fifty percent (50%); and
 - (b) For the purposes of this section, the lot occupancy shall be the total area occupied by all buildings and structures located on land and by any associated permanent structure located on, in, or over water, other than a floating home, divided by the total area of the lot.
- In the MU-11, MU-12, MU-13 or MU-14 zone, a public recreation and community center shall not occupy more than twenty percent (20%) of the lot upon which it is located; except that it may occupy up to forty percent (40%) if approved by the Board of Zoning Adjustment as a special exception pursuant to Subtitle X, Chapter 9, provided that the agency shows that the increase is consistent with agency policy of preserving open space.
- 311 GREEN AREA RATIO (GAR)
- 311.1 The minimum required GAR for the MU-12, MU-13 and MU-14 zones shall be 0.3.
- 312 WATERFRONT SETBACK
- 312.1 In the MU-11, MU-12, MU-13 and MU-14 zones a waterfront setback shall be provided in accordance with the provisions of Subtitle C, Chapter 11.
- 312.2 In addition to the requirements of Subtitle C, Chapter 11, in the MU-11 zone, a waterfront setback of not less than one hundred feet (100 ft.) to any building or structure shall be provided.
- 313 SPECIAL EXCEPTION
- Standards of this chapter shall be permitted as a special exception if approved by the Board of Zoning Adjustment under Subtitle X, Chapter 9, and subject to a demonstration by the applicant that conditions relating to the application for a special exception are not in conflict with the criteria of Subtitle C, Chapter 11.

CHAPTER 4 MIXED-USE ZONES MU-3, MU-4, MU-5, MU-6, MU-7, MU-8, MU-9, MU-10, AND MU30

400 PURPOSE AND INTENT

- The MU-3 through MU-10 and the MU-30 zones are mixed-use zones that are intended to be applied throughout the city consistent with the density designation of the Comprehensive Plan. A zone may be applied to more than one (1) density designation.
- 400.2 The MU-3 zones are intended to:
 - (a) Permit low-density mixed-use development; and
 - (b) Provide convenient retail and personal service establishments for the day-to-day needs of a local neighborhood, as well as residential and limited community facilities with a minimum impact upon surrounding residential development.
- 400.3 The MU-4 zone is intended to:
 - (c) Permit moderate-density mixed-use development;
 - (d) Provide facilities for shopping and business needs, housing, and mixed uses for large segments of the District of Columbia outside of the central core; and
 - <u>(e)</u> Be located in low- and moderate density residential areas with access to main roadways or rapid transit stops, and include office employment centers, shopping centers, and moderate bulk mixed-use centers.
- 400.4 The MU-5 zones are intended to:
 - (a) Permit medium density, compact mixed use development with an emphasis on residential use;
 - (b) Provide facilities for shopping and business needs, housing, and mixeduses for large segments of the District of Columbia outside of the central core; and
 - (c) Be located on arterial streets, in uptown and regional centers, and at rapid transit stops.
- 400.5 The MU-6 zone is intended to:
 - (a) Permit medium- to high-density mixed-use development with a focus on residential use: and

- **(b)** Provide facilities for shopping and business needs, housing, and mixeduses for large segments of the District of Columbia outside of the central 400.6 The MU-7 zone is intended to: Permit medium-density mixed-use development; and (a) **(b)** Be located on arterial streets, in uptown and regional centers, and at rapid transit stops. 400.7 The MU-8 zone is intended to: (a) Permit medium-density mixed use development with a focus on employment; **(b)** Be located in uptown locations, where a large component of development will be office-retail and other non-residential uses; and **(c)** Be located in or near the Central Employment Area, on arterial streets, in uptown and regional centers, and at rapid transit stops. 400.8 The MU-9 zone is intended to: Permit high-density mixed-use development including office, retail, and (a) housing, with a focus on employment; and **(b)** Be located in or near the Central Employment Area, on arterial streets, in uptown and regional centers, and at rapid transit stops. 400.9 The MU-10 zone is intended to: (a) Permit medium- to high-density mixed-use development with a balance of uses conducive to a higher quality of life and environment for residents, businesses, employees, and institutions; Be applied to areas where a mixture of uses and building densities is **(b)** intended to carry out elements of the Comprehensive Plan, small area plans, or framework plans, including goals in employment, population, transportation, housing, public facilities, and environmental quality;
- 400.10 The MU-30 zone is intended to:

(c)

(d)

(a) Permit high density mixed use development including office, retail, and housing, with a focus on employment; and

Allow residential and non-residential bulk to be apportioned between two

Require a level of public space at the ground level; and

(2) or more lots in the same square.

(b) Be located in or near the downtown core that comprises the retail and office centers for both the District of Columbia and the metropolitan area.

401 DEVELOPMENT STANDARDS

401.1 The development standards of this chapter modify the general development standards in Subtitle G, Chapter 2.

402 DENSITY FLOOR AREA RATIO (FAR)

402.1 The maximum permitted FAR in the MU-3 through MU-10 zones shall be as set forth in the following table:

TABLE G § 402.1: MAXIMUM PERMITTED FLOOR AREA RATIO

-	Maximum FAR	
Zone	Total Permitted	Maximum Non-Residential Use
MU-3A	1.0	1.0
WC 371	1.2 (IZ)	1.0
MU-3B	2.0	1.5
WIO 3B	2.4 (IZ)	1.3
MU-4	2.5	· 1.5
	3.0 (IZ)	1.5
MU 5 A	3.5	1.5
MU 5 B	4.2 (IZ)	1.3
MU-6	6.0	2.0
WO 0	7.2 (IZ)	2.0
MU 7	4.0	2.5
WO 7	4.8 (IZ)	2.3
MU-8	5.0	4.0
WIU 8	6.0 (IZ)	4.0
MU-9	6.5	6.5
- 10 /	7.8 (IZ)	0.5
MU-10	6.0	3.0
MU 10 	7.2 (IZ)	3.0

In the MU-4 and MU-5 zones, an existing building on a lot with an area ten thousand square feet (10,000 sq. ft.) or less, may have a maximum density of 2.0 FAR for non-residential uses, provided the uses are located in the ground story and the story directly above the ground story. For new construction, any additional use is limited to 0.5 FAR.

In the MU-10 zone, combined lot development is permitted for the purposes of allocating gross floor area devoted to residential and non-residential uses in accordance with the provisions of Subtitle C Chapter 12. Both lots shall be located within the same square, and shall be zoned MU-10.

402.4 In the MU-30 zone, the maximum permitted FAR shall be as set forth in the following table:

TABLE G § 402.4: MAXIMUM PERMITTED FAR

	Maximum FAR	
MU-30 Zone Height	Total Permitted	Maximum Non-Residential Use
Buildings erected to a height of one hundred ten feet (110	8.5	8.5
ft.) or less	10.2 (IZ)	0.0
Buildings erected to a height in excess of one hundred ten	10.0	10.0
feet (110 ft.) as permitted in Subtitle G § 403.2	12.0 (IZ)	10.0

403 HEIGHT

403.1 The maximum permitted building height and number of stories, not including the penthouse, in the MU-3 through MU-10 zones and the MU-30 zone shall be as set forth in the following table, except as provided in Subtitle G § 403.2:

TABLE G § 403.1: MAXIMUM PERMITTED HEIGHT/STORIES

Zone	Maximum Height (Feet)	Maximum Stories
MU 3A	40	3
MU 3B	50	4
MU-4	50	N/A
MU 5 A	65	NI/A
	70 (IZ)	N/A
MU 5 B	75	N/A
MU-6	90 100(IZ)	N/A
MU 7	65	N/A
MU-8	70	N/A
MU-9	90	N/A
MU-10	100 (IZ)	19//1
MU-30	110	NA

In the MU-30 zone, a building or other structure may be erected to a height not exceeding one hundred thirty feet (130 ft.); provided, that the building or other structure shall face or abut a street not less than one hundred ten feet (110 ft.) wide between building lines.

The maximum permitted height of a penthouse, except as prohibited on the roof of a detached dwelling, semi-detached dwelling, rowhouse, or flat in Subtitle C § 1500.4, shall be as set forth in the following table:

TABLE G § 403.3: MAXIMUM PERMITTED PENTHOUSE HEIGHT AND—STORIES

Zone	Maximum Penthouse Height	Maximum Penthouse Stories
MU-3A	12 ft. except	1;
MU-3B	15 ft. for penthouse	Second story permitted for
MU-4	mechanical space	penthouse mechanical space
MU 5 A MU 7	12 ft., except 18 ft. 6 in. for penthouse mechanical space	1; Second story permitted for penthouse mechanical space
MU 5B MU 8	20 ft.	1; Second story permitted for penthouse mechanical space
MU 6 MU 9 MU-10 MU 30	20 ft.	1 plus mezzanine; Second story permitted for penthouse mechanical space

404 LOT OCCUPANCY

The maximum permitted lot occupancy for residential use in the MU-3 through MU-10 zones and the MU-30 zone shall be as set forth in the following table:

TABLE G § 404.1: MAXIMUM PERMITTED LOT OCCUPANCY

Zone	Maximum Lot Occupancy for Residential Use
MU-3A MU-3B	60
MU 4	60 75 (IZ)
MU-5-A MU-5-B	80
MU 6 MU 7	7 5 80 (IZ)
MU 8 MU 9	N/A
MU-10	75 80 (IZ)
MU-30	N/A

Notwithstanding Subtitle G § 404.1, lots 835 and 840 located on Square 5539 shall not exceed a sixty percent (60 %) maximum lot occupancy for all residential and non-residential uses.

405 REAR YARD

- 405.1 A minimum rear yard of twenty feet (20 ft.) shall be provided in the MU-3 zone.
- 405.2 A minimum rear yard of fifteen feet (15 ft.) shall be provided in the MU-4, MU-5, and MU-6 zones.

- A minimum rear yard of two and one-half inches (2.5 in.) per one foot (1 ft.) of vertical distance from the mean finished grade at the middle of the rear of the structure to the highest point of the main roof or parapet wall, but not less than twelve feet (12 ft.) shall be provided in the MU-7, MU-8, MU-9, MU-10, and MU-30 zones.
- 405.4 In the MU-3 through MU-9 zones, a horizontal plane may be established at twenty feet (20 ft.) above the mean finished grade at the middle of the rear of the structure for the purpose of measuring rear yards.
- 405.5 In the MU-3 through MU-7 zones, rear yards shall be measured as follows:
 - (a) Where a lot abuts an alley:
 - (1) For that portion of the structure below a horizontal plane described in Subtitle G § 405.4 from the center line of the alley to the rear wall of the portion; and
 - (2) For that portion of the structure above the horizontal plane described in Subtitle G § 405.4, from the rear lot line to the rear wall of that portion immediately above the plane; and
 - (b) Where a lot does not abut an alley, the rear yard shall be measured from the rear lot line to the rear wall of the building or other structure.
- 405.6 In the MU-8, MU-9, and MU-30 zones, rear yard shall be established subject to the following conditions:
 - (a) A rear yard is not required to be provided below a horizontal plane as described in Subtitle G § 405.4;
 - (b) Where a lot abuts an alley, the rear yard may be measured from the center line of the alley to the rear wall of the building or other structure; and
 - (c) Where a lot does not abut an alley, the rear yard shall be measured from the rear lot line to the rear wall of the building or other structure.
- 405.7 In the MU-10 zone, rear yards are required only for residential uses and shall be established subject to the following conditions:
 - (a) A rear yard shall be established no lower than the first level of residential use:
 - (b) Where a lot abuts an alley, the rear yard may be measured from the center line of the alley to the rear wall of the building or other structure; and
 - (c) Where a lot does not abut an alley, the rear yard shall be measured from the rear lot line to the rear wall of the building or other structure.

406 SIDE YARD

- 406.1 No side yard is required for a building or structure other than a detached single dwelling unit or semi-detached single dwelling unit; however, if a side yard is provided it shall be at least two inches (2 in.) wide for each one foot (1 ft.) of height of building but no less than five feet (5 ft.).
- 406.2 A minimum side yard of eight feet (8 ft.) shall be provided for a detached single dwelling unit or semi-detached single dwelling unit.
- 406.3 Any portion of a building set back from the side lot line shall be considered a side yard and not a court.

407 GREEN AREA RATIO (GAR)

- 407.1 The minimum required GAR for the MU-3 through MU-6 zones shall be 0.3.
- 407.2 The minimum required GAR for the MU 7 and MU 8 zones shall be 0.25.
- 407.3 The minimum required GAR for the MU-9, MU-10, and MU-30 zones shall be 0.20.

408 PLAZA

- 408.1 In the MU-10 zone, a plaza comprising eight percent (8%) of the lot area shall be provided for development on a lot of greater than ten thousand square feet (10,000 sq. ft.), in accordance with the provisions of Subtitle C, Chapter 17.
- Where preferred use space is required under this chapter and provided, the requirement to provide plaza space shall not apply.

409 SPECIAL EXCEPTION

Exceptions to the development standards of this chapter shall be permitted as a special exception if approved by the Board of Zoning Adjustment under Subtitle X, Chapter 9, and subject to the provisions and limitations of Subtitle G, Chapter 12.

410 COMBINED LOT

- 410.1 The following combined lot development provision shall apply to the MU-10 zone only:
 - (a) The allowable residential and non-residential bulk of a MU-10 zone may be apportioned between two (2) or more lots in the same square, regardless of the limits on floor area; provided, that the aggregate residential and non-residential floor area may not exceed the zone limits;
 - (b) A covenant running with the land and applicable to all properties involved in the apportionment shall be executed by all of the owners of the properties and the District of Columbia government prior to the issuance of any building permits. The covenant shall be for the purpose of insuring that the aggregate residential and non-residential floor area does not exceed the limits applicable to residential and non-residential uses; and

(c) For the purposes of this section, the term "residential purposes" shall include dwellings, flats, multiple dwellings, rooming and boarding houses, community based residential facilities, inns, and guest room areas and service areas within hotels.

411 TRANSITION SETBACK REQUIREMENTS

- 411.1 In the MU-3B zone the following transition setback requirements shall apply to any building or portion of a building within thirty feet (30 ft.) of a lot line directly abutting an R zone district:
 - (a) A twenty foot (20 ft.) minimum transition setback shall be provided from any lot line directly abutting an R zone district extended as a vertical plane parallel to each abutting lot line. No building or portion of a building may be constructed within the 20-foot transition setback; and
 - (b) An additional upper-story transition setback of 10 feet minimum shall be provided above a building height of 40 feet, or top of third story.
- 411.2 Any required transition setback area shall not be used for loading.
- 411.3 A minimum of six feet (6 ft.) of the transition setback area, measured in from the abutting residential lot line, shall be landscaped with evergreen trees subject to the following conditions:
 - (a) The trees shall be maintained in a healthy growing condition;
 - (b) The trees shall be a minimum of eight feet (8 ft.) high when planted; and
 - (c) Planting locations and soil preparation techniques shall be shown on a landscape plan submitted with the building permit application to the Department of Consumer and Regulatory Affairs for review and approval according to standards maintained by the Department's Soil Erosion and Storm Management Branch, which may require replacement of heavy or compacted soils with top and drainage mechanisms as necessary.
- 411.4 A required transition setback may be inclusive of a required side or rear yard provided all conditions of each section are met.
- 411.5 No residential communal outdoor recreation space shall be located within 50 feet of any lot line directly abutting an R zone district extended as a vertical plane parallel to each abutting lot line.

CHAPTER 5 MIXED-USE ZONES MU-11, MU-12, MU-13, AND MU-14

500 PURPOSE AND INTENT

- The MU-11 through MU-14 zones are mixed use zones that are intended to be applied generally in the vicinity of the waterfront.
- 500.2 The MU-11 zone is intended to:
 - (a) Permit open space, park, and low-density and low-height waterfrontoriented retail and arts uses: and
 - (b) Be applied in undeveloped waterfront areas.
- The MU-12 zone is intended to permit moderate density mixed use development generally in the vicinity of the waterfront.
- The MU-13 zone is intended to permit medium-density mixed-use development generally in the vicinity of the waterfront.
- The MU-14 zone is intended to permit high-density mixed-use development generally in the vicinity of the waterfront.

501 DEVELOPMENT STANDARDS

The development standards of this chapter modify the general development standards in Subtitle G, Chapter 2.

502 DENSITY - FLOOR AREA RATIO (FAR)

The maximum permitted FAR of buildings, incorporating the IZ bonus density authorized by Subtitle C § 1002.3, in the MU-11 through MU-14 zones shall be as set forth in the following table, except as provided in Subtitle G §§ 502.2 and 502.3:

TABLE G § 502.1: MAXIMUM PERMITTED FLOOR AREA RATIO

	Maximum FAR	
Zone	Total Permitted	Maximum Non-Residential Use
MU-11	0.5	0.5
MU 12	2.5 3.0 (IZ)	1.0
MU-13	4.0	2.0
MU-14	6.0 7.2 (IZ)	5.0

In the MU-11 through MU-14 zones, the guestroom areas and service areas within lodging uses may be charged against the "Total Permitted" floor area ratio.

In the MU-11 zone, the density on a lot used exclusively for recreational use, marina, yacht club, or boathouse buildings and structures shall not exceed 0.75 FAR; and for the purposes of this subsection, FAR shall be the gross floor area of all buildings and structures located on land and any associated permanent structure located on, in, or over water, other than a floating home, divided by the total area of the lot.

503 HEIGHT

The maximum permitted building height, not including the penthouse, in the MU-11 through MU-14 zones shall be as set forth in the following table, except as provided in Subtitle G § 503.3:

TABLE G § 503.1: MAXIMUM PERMITTED BUILDING HEIGHT

Zone	Maximum Height (Feet)
MU-11	40
MU 12	4 5 50 (IZ)
MU-13	60
MU-14	90 100 (IZ)

The maximum permitted height of a penthouse, except as prohibited on the roof of a detached dwelling, semi-detached dwelling, rowhouse, or flat in Subtitle C § 1500.4, shall be as set forth in the following table:

TABLE G § 503,2: MAXIMUM PERMITTED PENTHOUSE HEIGHT AND STORIES

Zone	Maximum Penthouse Height	Maximum Penthouse Stories
MU-11 MU-12	12 ft. except 15 ft. for penthouse mechanical space	1; Second story permitted for penthouse mechanical space
MU-13	12 ft. except 18 ft. 6in. for penthouse mechanical space	1; Second story permitted for penthouse mechanical space
MU-14	20 ft.	1 plus mezzanine; Second story permitted for penthouse mechanical space

503.3 In the MU-11 zone, the following conditions apply:

(a) A building or structure located on, in, or over the water; or a watercraft, including a floating home shall have a maximum height of twenty-five feet (25 ft.). For the purposes of this subsection, the maximum height shall be measured from the mean high water level along the shore directly in front of the building, structure, or watercraft to the highest point of the building or structure, not including sailboat masts; and

(b) Penthouses less than ten feet (10 ft.) in height above a roof or parapet wall of a structure on Kingman Island shall not be subject to the requirements of Subtitle G, Chapters 11 and 12 of this subtitle when the top of the penthouse is below maximum building height prescribed for the MU-11 zone.

504 LOT OCCUPANCY

The maximum permitted lot occupancy for residential use of buildings in the MU-11 through MU-14 zones shall be as set forth in the following table:

TABLE G § 504.1: MAXIMUM PERMITTED LOT OCCPUANCY

Zone	Maximum Lot Occupancy for Residential Use (Percentage)
MU 11	25
MU 12	80
MU-13	75
MU 14	75 80 (IZ)

- 504.2 Within the MU-11 zone, no building or portion of a building, including accessory buildings, shall occupy greater than twenty five percent (25%) of the lot upon which it is located, provided that:
 - (a) The lot occupancy on a lot used exclusively for a recreational use, marina, yacht club, or boathouse buildings and structures shall not exceed fifty percent (50%); and
 - (b) For the purposes of this section, the lot occupancy shall be the total area occupied by all buildings and structures located on land and by any associated permanent structure located on, in, or over water, other than a floating home, divided by the total area of the lot.
- 504.3 Except for new penthouse habitable space as described in Subtitle C § 1500.11, the Inclusionary Zoning requirements and modifications of Subtitle C, Chapter 10, shall not apply to the portion of the MU-13 zone in the Georgetown Historic District.

505 REAR YARD

- Rear yard are required only for residential uses and shall be established no lower than the first level of residential use.
- A minimum rear yard of twelve feet (12 ft.) shall be provided in the MU-11, MU-12, MU-13, and MU-14 zones.

- Where a lot abuts an alley, the rear yard may be measured from the center line of the alley to the rear wall of the building or other structure.
- Where a lot does not abut an alley, the rear yard shall be measured from the rear lot line to the rear wall of the building or other structure.
- The Board of Zoning Adjustment may waive rear yard requirements pursuant to Subtitle X, Chapter 9 and Subtitle G, Chapter 12.

506 SIDE YARD

- In the MU-11 zone, a side yard for any building or structure located in whole or in part on land, shall be no less than twelve feet (12 ft.).
- No side yard shall be required in the MU-12, MU-13, and MU-14 zones. If a side yard is provided, its minimum width shall be at least eight (8) feet.
- Any portion of a building set back from the side lot line shall be considered a side yard and not a court.

507 GREEN AREA RATIO (GAR)

507.1 The minimum required GAR for the MU-12 through MU-14 zones shall be 0.3.

508 WATERFRONT SETBACK

- 508.1 A waterfront setback shall be provided in accordance with the provisions of Subtitle C, Chapter 11.
- In the MU-11 zone, a waterfront setback of not less than one hundred feet (100 ft.) to any building or structure shall be provided.

509 SPECIAL EXCEPTION

Exceptions to the development standards of this chapter shall be permitted as a special exception if approved by the Board of Zoning Adjustment under Subtitle X, Chapter 9, and subject to a demonstration by the applicant that conditions relating to the application for a special exception are not in conflict with the criteria of Subtitle C, Chapter 11.

CHAPTER 4 DUPONT CIRCLE MIXED-USE ZONES – MU-15, MU-16, MU-17, MU-18, MU-19, MU-20, MU-21, AND MU-22 MU-1/DC, MU-2/DC, MU-4/DC, MU-5A/DC, MU-6/DC, MU-8/DC, MU-9/DC AND MU-10/DC

600–400 PURPOSE AND INTENT

- The development standards in Subtitle G, Chapter 2 shall apply to the MU-1/DC, MU-2/DC, MU-4/DC, MU-5A/DC, MU-6/DC, MU-8/DC, MU-9/DC, and MU-10/DC zones except as specifically modified by this chapter. In the event of a conflict between the provisions of this chapter and other regulations of this subtitle, the provisions of this chapter shall control.
- The <u>In addition to the purposes of the MU zones, the</u> purposes of the Dupont Circle Mixed-Use zones (MU-15 through MU-22) are to:
 - (a) Require a scale of development consistent with the nature and character of the Dupont Circle area in height and bulk and ensure a general compatibility in the scale of new buildings with older, low-scale buildings;
 - (b) Enhance the residential character of the area by maintaining existing residential uses and controlling the scale, location, and density of commercial and residential development;
 - (c) Protect the integrity of "contributing buildings", as that term is defined by the Historic Landmark and Historic District Protection Act of 1978;
 - (d) Preserve areas planned as open gardens and backyards and protect the light, air, and privacy that they provide;
 - (e) Enhance the streetscape by maintaining the public space in front of buildings as landscaped green spaces and limited curb cuts on Connecticut Avenue; and
 - (f) Encourage greater use of public transportation and the free circulation of vehicles through public streets and alleys.
- The MU-15 zone is intended to permit moderate-density areas predominantly developed with residential buildings.
- The MU-16 zone is intended to permit medium density areas predominantly developed with residential buildings.
- The MU-17 zone is intended to permit moderate density mixed use development.
- The MU-18 zone is intended to permit medium-density, compact mixed-use development with an emphasis on residential development.

- The MU-19 zone is intended to permit medium-density mixed-use development with a focus on residential use.
- The MU-20 zone is intended to permit medium-density mixed-use development with a focus on employment.
- The MU-21 zone is intended to permit high-density mixed-use development with a focus on employment.
- The MU-22 zone is intended to permit medium to high-density mixed-use development with a balance of uses conducive to a higher quality of life and environment for residents, businesses, employees, and institutions.
- No driveway providing access to required parking spaces or loading berths shall be permitted along Connecticut Avenue from N Street, N.W., to Florida Avenue, N.W.

401 PLANNED UNIT DEVELOPMENT DEVELOPMENT STANDARDS

401.1 The matter-of-right building height, floor area ratio, and penthouse height limits shall serve as the maximum permitted building height, floor area ratio, and penthouse height for a planned unit development.

The development standards of this chapter modify the general development standards in Subtitle G, Chapter 2.

402 MISCELLANEOUS

402.1 No driveway providing access to required parking spaces or loading berths
shall be permitted along Connecticut Avenue from N Street, N.W., to Florida
Avenue, N.W.

602 DENSITY - FLOOR AREA RATIO (FAR)

The maximum permitted FAR of buildings in the MU-15 through MU-22 zones shall be as set forth in the following table:

TABLE G § 602.1: MAXIMUM PERMITTED FLOOR AREA RATIO

	Maximun	FAR
Zone	Total Permitted	Maximum Non-Residential Use
MU-15	4.0	2.5
₩10-13	4 .8 (IZ)	2.3
MU-16	6.0	3.5

	7.2 (IZ)	
MU 17	2.5	1.5
WIO 17	3.0 (IZ)	1.5
MU-18	3.5	1.5
WIU 10	4.2 (IZ)	1.3
MU-19	6.0	2.0
MU-19	7.2 (IZ)	2.0
MU-20	5.0	4.0
	6.0 (IZ)	4.U
MU 21	6.5	
	7.8 (IZ)	6.5
MILOO	6.0	2.0
MU-22	7.2 (IZ)	3.0

- In the MU-17 and MU-18 zones, an existing building on a lot with an area ten thousand square feet (10,000 sq. ft.) or less, may have a maximum density of 2.0 FAR for non residential uses, provided the uses are located in the ground story and the story directly above the ground story.
- In the MU-22 zone, combined lot development is permitted for the purposes of allocating gross floor area devoted to residential and non-residential uses in accordance with the provisions of Subtitle G § 100.4. Both lots shall be located within the same square, and shall be zoned MU-22.

603 HEIGHT

The maximum permitted building height, not including the penthouse, in the MU-15 through MU-22 zones shall be as set forth in the following table:

TABLE G § 603.1: MAXIMUM PERMITTED BUILDING HEIGHT

Zone	Maximum Height (Feet)
MU-15	65
WIO 13	70 (IZ)
MU-16	90
MU-17	50
MU-18	65
	70 (IZ)
MU-19	90
MU-20	70
MU-21	90
) (II) (I	90
MU-22	100 (IZ)

The maximum permitted height of a penthouse, except as prohibited on the roof of a detached dwelling, semi-detached dwelling, rowhouse, or flat in Subtitle C § 1500.4, shall be as set forth in the following table:

TABLE G § 603.2: MAXIMUM PERMITTED PENTHOUSE HEIGHT AND STORIES

Zone	Maximum Penthouse Height	Maximum Penthouse Stories
MU 17,	12 ft. except 15 ft. for penthouse mechanical space	1; Second story permitted for penthouse mechanical space
MU 15 MU 18	12 ft. except 18 ft. 6 in. for penthouse mechanical space	1; Second story permitted for penthouse mechanical space
MU-20	20 ft.	1; Second story permitted for penthouse mechanical space
MU-16 MU-19 MU-21 MU-22	20 ft.	1 plus mezzanine; Second story permitted for penthouse mechanical space

604 LOT OCCUPANCY

The maximum permitted lot occupancy for residential use in the MU-15 through MU-22 zones shall be as set forth in the following table:

TABLE G § 604.1: MAXIMUM PERMITTED LOT OCCUPANCY

Zone	Maximum Lot Occupancy for Residential Use
MU-15	80%
MU-16	80% 90% (IZ)
MU-17	60% 75% (IZ)
MU-18	80%
MU-19	80% 90% (IZ)
MU-20	100%
MU 21	100%
MU-22	75% 80% (IZ)

605 REAR YARD

- A minimum rear yard of twelve feet (12 ft.) shall be provided in the MU-15 and MU-16 zones.
- A minimum rear yard of fifteen feet (15 ft.) shall be provided in the MU-17, MU-18, and MU-19 zones.

- A minimum rear yard of two and one-half inches (2.5 in.) per one foot (1 ft.) of vertical distance from the mean finished grade at the middle of the rear of the structure to the highest point of the main roof or parapet wall, but not less than twelve feet (12 ft.) shall be yard in the MU-20, MU-21, and MU-22 zones.
- In the MU-15 and MU-16 zones, rear yards shall be measured as follows:
 - (a) Where a lot abuts an alley, the rear yard may be measured from the center line of the alley to the rear wall of the building or other structure; and
 - (b) Where a lot does not abut an alley, the rear yard shall be measured from the rear lot line to the rear wall of the building or other structure.
- In the MU-17 through MU-21 zones, a horizontal plane may be established at twenty-five feet (25 ft.) above the mean finished grade at the middle of the rear of the structure for the purpose of measuring rear yard.
- In the MU-17 through MU-19 zones, rear yards shall be measured as follows:
 - (a) Where a lot abuts an alley:
 - (1) For that portion of the structure below a horizontal plane described in Subtitle G § 605.5 from the center line of the alley to the rear wall of the portion; and
 - (2) For that portion of the structure above the horizontal plane described in Subtitle G § 605.5, from the rear lot line to the rear wall of that portion immediately above the plane; and
 - (b) Where a lot does not abut an alley, the rear yard shall be measured from the rear lot line to the rear wall of the building or other structure.
- In the MU-20 and MU-21 zones, rear yards shall be established subject to the following conditions:
 - (a) A rear yard is not required to be provided below a horizontal plane as described in Subtitle G § 605.5;
 - (b) Where a lot abuts an alley, the rear yard may be measured from the center line of the alley to the rear wall of the building or other structure; and
 - (c) Where a lot does not abut an alley, the rear yard shall be measured from the rear lot line to the rear wall of the building or other structure.
- In the MU-22 zone, rear yards are required only for residential uses and shall be established subject to the following conditions:
 - (a) A rear yard shall be established no lower than the first level of residential use;

- (b) Where a lot abuts an alley, the rear yard may be measured from the center line of the alley to the rear wall of the building or other structure; and
- (c) Where a lot does not abut an alley, the rear yard shall be measured from the rear lot line to the rear wall of the building or other structure.

606 SIDE YARD

- In the MU-15, MU-16, and MU-22 zones, no side yard is required; however, if a side yard is provided it shall be at least two inches (2 in.) wide for each one foot (1 ft.) of height of building, but no less than five feet (5 ft.).
- In the MU-17, MU-18, MU-19, MU-20, and MU-21 zones, no side yard is required for a building or structure other than a detached single dwelling unit or semi-detached single dwelling unit; however, if a side yard is provided it shall be at least two inches (2 in.) wide for each one foot (1 ft.) of height of building but no less than five feet (5 ft.).
- A side yard for a detached single dwelling unit or semi-detached single dwelling unit shall be a minimum of eight feet (8 ft.).
- Any portion of a building set back from the side lot line shall be considered a side yard and not a court.

607 GREEN AREA RATIO (GAR)

- The minimum required GAR for the MU-15 through MU-19 zones shall be 0.3.
- The minimum required GAR for the MU-20 and MU-21 zones shall be 0.2.
- The minimum required GAR for the MU-22 zone shall be 0.2.

608 PLAZA

- Within the MU-22 zone, a plaza comprising eight percent (8%) of the lot area shall be provided for development on a lot of greater than ten thousand square feet (10,000 sq. ft.), in accordance with the provisions of Subtitle C, Chapter 17.
- Where preferred use space is required under this chapter and provided, the requirement to provide plaza space shall not apply.

609 SPECIAL EXCEPTION

The special exception criteria of Subtitle G, Chapter 12 shall apply to all MU-15 through MU-22 zones.

CHAPTER 7 CHAPTER 5 CAPITOL INTEREST AND CAPITOL HILL COMMERCIAL MIXED-USE ZONES - MU-23, MU-24, MU-25 AND MU-26—MU-2/CAP, MU-4/CAP, MU-4/CHC, AND MU-4/CAP/CHC

700 500 PURPOSE AND INTENT

- The development standards in Subtitle G, Chapter 2 shall apply to the MU-2/CAP, MU-4/CAP, MU-4/CHC, and MU-4/CAP/CHC zones except as specifically modified by this chapter. In the event of a conflict between the provisions of this chapter and other regulations of this subtitle, the provisions of this chapter shall control.
- 700.1 500.2 The In addition to the purposes of the MU zones, the purposes of the Capitol Interest Mixed-Use zones (MU-23, MU-24 and MU-26) (MU-2/CAP, MU-4/CAP, MU-4/CAP/CHC) are to:
 - (a) Promote and protect the public health, safety, and general welfare of the U.S. Capitol precinct and the area adjacent to this jurisdiction, in a manner consistent with the goals and mandates of the United States Congress in Title V of the Legislative Branch Appropriation Act, 1976 (Master Plan for Future Development of the Capitol Grounds and Related Areas), approved July 25, 1975 (Pub. L. No. 94-59, 89 Stat. 288), and in accordance with the plan submitted to the Congress pursuant to the Act;
 - (b) Respect the importance of and provide sufficient controls for the area adjacent to the U.S. Capitol;
 - (c) Provide particular controls adjacent to properties having a well-recognized general public interest; and
 - (d) Restrict some of the permitted uses to reduce the possibility of harming the site, building, or district to be protected.
- 700.2 The MU-23 zone is intended to permit medium density areas predominantly developed with residential buildings consistent with the purposes of Subtitle G § 700.1.
- The MU-24 zone is intended to permit moderate-density mixed-use development consistent with the purposes of Subtitle G § 700.1.
- 700.4 500.3 In addition to the purposes of the MU zone, the purposes of the The-Capitol Hill Commercial Mixed-Use zones include the MU-25 and MU-26 (MU-4/CHC) and MU-4/CAP/CHC) zones and are intended to:
 - (a) Encourage the adaptive use and reuse of existing buildings, many of which are located in the Capitol Hill Historic District, particularly with respect to the portions of the buildings that exceed the commercial floor area ratio

- permitted in the underlying zone districts;
- (b) Concentrate non-residential uses in commercial zone districts in certain areas of Capitol Hill, thereby enhancing and protecting the residential character of the areas surrounding the commercial zone districts and relieving pressure to use properties zoned residential for commercial uses; and
- (c) Provide appropriate incentives for new infill construction that is compatible with the Capitol Hill Historic District and its predominance of low-scale row house structures.
- The MU-25 zone is intended to permit moderate-density mixed-use development consistent with the purpose of Subtitle G § 700.4.
- The MU-26 zone is intended to permit moderate-density mixed-use development consistent with the purposes of Subtitle G §§ 700.1 and 700.4.

701 DEVELOPMENT STANDARDS

701.1 The development standards of this chapter modify the general development standards in Subtitle G, Chapter 2.

702 501 DENSITY —FLOOR AREA RATIO (FAR)

702.1 501.1 The maximum permitted FAR of buildings in the MU-23 through MU-26 MU-2/CAP, MU-4/CAP, MU-4/CHC and MU-4/CAP/CHC zones shall be as set forth in the following table:

TABLE G § 702.1 501.1: MAXIMUM PERMITTED FLOOR AREA RATIO

Maximum FAR		mum FAR
Zone	Total Permitted	Maximum Non-Residential Use
MU-23 MU-2/CAP	1.8	1.8 N/A
WIG 23 MIC-2/CAI	2.16 (IZ)	1.0 N/A
MU-24 MU-4/CAP	1.8	1 5
	2.16 (IZ)	1.5
MIL 25 MIL A/CHC	3.0	3.0
MU-25 MU-4/CHC	3.0 (IZ)	3.0
MIL 26 MIL A/CAD/CHC	2.5	2.5
MU-26 MU-4/CAP/CHC	2.5 (IZ)	2.5

702.2 501.2 In the MU-24 MU-4/CAP zone, an existing building on a lot with an area ten thousand square feet (10,000 sq. ft.) or less may have a maximum density of 1.8

FAR for non-residential uses, provided the uses are located in the ground story and the story directly above the ground story.

702.3 501.3 In the MU 25 and MU 26 MU-4/CHC and MU-4/CAP/CHC zones, an existing building on a lot with an area ten thousand square feet (10,000 sq. ft.) or less may have a maximum density of 2.0 FAR for non-residential uses, provided the uses are located in the ground story and the story directly above the ground story.

703 5<u>02</u> HEIGHT

- The maximum building height, not including the penthouse, in the MU-23, MU-24, and MU-26 MU-2/CAP, MU-4/CAP and MU-4/CAP/CHC zones shall be forty feet (40 ft.) and three (3) stories.
- 703.2 The maximum height in the MU-25 zone shall be fifty feet (50 ft.).

503 PENTHOUSES

- The In the MU-2/CAP, MU-4/CAP and MU-4/CAP/CHC zones, the maximum permitted height of a penthouse, except as prohibited on the roof of a detached dwelling, semi-detached dwelling, rowhouse single household dwelling or flat in Subtitle C § 1500.4, shall be ten feet (10 ft.), and the maximum number of stories within the penthouse shall be one (1) in the MU-23, MU-24, and MU-26 zones.
- The maximum permitted height of a penthouse, except as prohibited on the roof of a detached dwelling, semi-detached dwelling, rowhouse, or flat in Subtitle C § 1500.4, shall be twelve feet (12 ft.), except fifteen feet (15 ft.) shall be permitted for penthouse mechanical space, and the maximum number of stories within the penthouse shall be one (1), except a second story shall be permitted for penthouse mechanical space in the MU-25 zone.

704 LOT OCCUPANCY

The maximum permitted lot occupancy for residential use in the MU-23 through MU-26 zones shall be as set forth in the following table:

TABLE G § 704.1 504.1: MAXIMUM PERMITTED LOT OCCUPANCY

Zone	Maximum Lot Occupancy for	
	Residential Use	
MU-23	80%	
	90% (IZ)	
MU-24	60%	
MU-25	75% (IZ)	
MU-26		

705 REAR YARD

- 705.1 A minimum rear yard of twelve feet (12 ft.) shall be provided in the MU-23 zone.
- 705.2 In the MU-23 zone, rear yards shall be measured as follows:
 - (a) Where a lot abuts an alley, the rear yard may be measured from the center line of the alley to the rear wall of the building or other structure; and
 - (b) Where a lot does not abut an alley, the rear yard shall be measured from the rear lot line to the rear wall of the building or other structure.
- 705.3 A minimum rear yard of fifteen feet (15 ft.) shall be provided in the MU-24 through MU-26 zones.
- In the MU-24 through MU-26 zones, a horizontal plane may be established at twenty-five feet (25 ft.) above the mean finished grade at the middle of the rear of the structure for the purpose of measuring rear yards.
- 705.5 In the MU-24 through MU-26 zones, rear yards shall be measured as follows:
 - (a) Where a lot abuts an alley:
 - (1) For that portion of the structure below a horizontal plane described in Subtitle G § 705.4 from the center line of the alley to the rear wall of the portion; and
 - (2) For that portion of the structure above the horizontal plane described in Subtitle G § 705.4, from the rear lot line to the rear wall of that portion immediately above the plane; and
 - (b) Where a lot does not abut an alley, the rear yard shall be measured from the rear lot line to the rear wall of the building or other structure.

706 — SIDE YARD

No side yard is required for a principal building other than a detached single dwelling unit or semi detached single dwelling unit; however, if a side yard is

provided, it shall be at least two inches (2 in.) wide for each one foot (1 ft.) of height of building, but no less than five feet (5 ft.).

- A side yard for a detached single dwelling unit or semi-detached single dwelling unit shall be a minimum of eight feet (8 ft.).
- Any portion of a building set back from the side lot line shall be considered a side yard and not a court.

707 GREEN AREA RATIO (GAR)

707.1 The minimum required GAR for the MU-23 through MU-26 zones shall be 0.3.

708 <u>504</u> SPECIAL EXCEPTION <u>CRITERIA CAPITOL INTEREST</u> <u>MIXED USE ZONE (CAP)</u>

- 708.1 The special exception criteria of Subtitle G, Chapter 12 shall apply to all MU-23 through MU-26 zones.
- In addition to the special exception criteria of Subtitle G, Chapter 12 Chapter 52, and Subtitle X, Chapter 9 any special exception application in the MU-23, MU-24, or MU-26 MU-2/CAP, MU-4/CAP and MU-4/CAP/CHC zone shall be subject to the following conditions in addition to any conditions relative to the specific special exception:
 - (a) Compatible with the present and proposed development of the neighborhood;
 - (b) Consistent with the goals and mandates of the United States Congress in Title V of the Legislative Branch Appropriation Act, 1976 (Master Plan for Future Development of the Capitol Grounds and Related Areas), approved July 25, 1975 (Pub. L. No. 94-59, 89 Stat. 288); and
 - (c) In accordance with the plan promulgated under the Act.
- 708.3 504.2 Upon receipt of the application, the Board of Zoning Adjustment shall submit the application to the Office of Planning for coordination, review, report, and impact assessment, along with reviews in writing of all relevant District departments and agencies, including the Departments of Transportation, Housing and Community Development, and, if a historic district or historic landmark is involved, the Historic Preservation Office.
- 708.4 504.3 Upon receipt of the application, the Board of Zoning Adjustment shall submit the application to the Architect of the Capitol for review and report.
- 708.5 504.4 The Board of Zoning Adjustment may require special treatment and impose reasonable conditions as it deems necessary to mitigate any adverse impacts identified in the consideration of the application.

<u>CHAPTER 8 CHAPTER 6 NAVAL OBSERVATORY MIXED-USE ZONE - MU-27 MU-4/NO</u>

800 600 PURPOSE AND INTENT

- The development standards in Subtitle G, Chapter 2 shall apply to the MU
 4/NO zone except as specifically modified by this chapter. In the event of a

 conflict between the provisions of this chapter and other regulations of this
 subtitle, the provisions of this chapter shall control.
- 600.2 Except for new penthouse habitable space as described in Subtitle C §

 1500.11, the Inclusionary Zoning requirements and modifications of Subtitle
 C, Chapter 10 shall not apply to the MU-4/NO zone.
- 800.1 600.3 The In addition to the purposes of the MU zones, the purposes of the Naval Observatory Mixed-Use zone (MU-27 MU-4/NO) are to:
 - (a) Permit moderate density mixed use development;
 - (b) (a) Promote the public health, safety, and general welfare on land adjacent to or in close proximity to the highly sensitive and historically important Naval Observatory, in keeping with the goals and policies of the Federal and District elements of the Comprehensive Plan and the adopted Master Plan for that facility;
 - (e) (b) Ensure that public land within the zone shall be used in a manner consistent with the historic or ceremonial importance and special mission of the Naval Observatory;
 - (d) (c) Reflect the importance of the Naval Observatory to the District of Columbia and the Nation;
 - (e) (d) Reduce or eliminate any possible harm or restrictions on the mission of the Federal establishment within the zone; and
 - (f) (e) Provide additional controls on private land, in order to protect Federal interest concerns, including the critical scientific mission performed at the Naval Observatory and the security needs of the Vice President's residence.
 - (g) The <u>MU-27</u> zone is intended to permit moderate-density mixed-use development.
- 801 601 PLANNED UNIT DEVELOPMENT DEVELOPMENT STANDARDS

801.2 601.1 The provisions of Subtitle X, Chapter 3 shall not operate to permit a planned unit development in the MU-27 MU-4/NO zone to exceed either the limits of Subtitle G § 802.2 602 or the area, bulk, and yard standards that apply as a matter of right in the MU-27 MU-4/NO zone.

The development standards of this chapter modify the general development standards in Subtitle G, Chapter 2.

802 DENSITY – FLOOR AREA RATIO (FAR)

- The maximum permitted FAR in the MU-27 zone shall be 2.5 FAR with a maximum density of 1.5 FAR for non-residential use.
- In the MU-27 zone, an existing building on a lot with an area ten thousand square feet (10,000 sq. ft.) or less may have a maximum density of 2.0 FAR for non-residential uses, provided the uses are located in the ground story and the story directly above the ground story.

803 602 HEIGHT

- The maximum permitted building height, not including the penthouse, in the <u>MU-27 MU-4/NO</u> zone shall be forty feet (40 ft.), measured as follows:
 - (a) The height of a building shall be the vertical distance measured from the level of the curb opposite the middle of the front of the building to the highest point of the roof or parapet; and
 - (b) The curb elevation opposite the middle of the front of the building shall be determined as the average elevation of the lot from its front line to its rear lot line.
- The maximum permitted height of a penthouse, except as prohibited on the roof of a detached dwelling, semi-detached dwelling, rowhouse, or flat in Subtitle C § 1500.4, shall be twelve feet (12 ft.) except fifteen feet (15 ft.) shall be permitted for penthouse mechanical space, and the maximum number of stories within the penthouse shall be one (1).
- A penthouse permitted by this section shall contain no form of habitable space, other than ancillary space associated with a rooftop deck, to a maximum area of twenty percent (20%) of the building roof area dedicated to rooftop deck, terrace, or recreation space.

804 LOT OCCUPANCY

The maximum permitted lot occupancy for residential use in the MU-2_7 zone shall be sixty percent (60%).

804.2 Except for new penthouse habitable space as described in Subtitle C § 1500.11, the Inclusionary Zoning requirements and modifications of Subtitle C, Chapter 10 shall not apply to the MU-27 zone.

603 PENTHOUSES

- The maximum permitted height of a penthouse, except as prohibited on the roof of a single household dwelling or flat in Subtitle C § 1500.4, shall be twelve feet (12 ft.) except fifteen feet (15 ft.) shall be permitted for penthouse mechanical space, and the maximum number of stories within the penthouse shall be one (1).
- A penthouse permitted shall contain no form of habitable space, other than ancillary space associated with a rooftop deck, to a maximum area of twenty percent (20%) of the building roof area dedicated to rooftop deck, terrace, or recreation space.

805 REAR YARD

- A minimum rear yard of fifteen feet (15 ft.) shall be provided in the MU-27 zone.
- A horizontal plane may be established at twenty-five feet (25 ft.) above the mean finished grade at the middle of the rear of the structure for the purpose of measuring rear yards.
- Rear yards shall be measured as follows:
 - (a) Where a lot abuts an alley:
 - (1) For that portion of the structure below a horizontal plane described in Subtitle G § 805.2 from the center line of the alley to the rear wall of the portion; and
 - (2) For that portion of the structure above the horizontal plane described in Subtitle G § 805.2, from the rear lot line to the rear wall of that portion immediately above the plane; and
 - (b) Where a lot does not abut an alley, the rear yard shall be measured from the rear lot line to the rear wall of the building or other structure.

806 SIDE YARD

No side yard is required for a principal building other than a detached single dwelling unit or semi detached single dwelling unit; however, if a side yard is provided it shall be at least two inches (2 in.) wide for each one foot (1 ft.) of height of building but no less than five feet (5 ft.).

- A minimum side yard of eight feet (8 ft.) shall be provided for a detached single dwelling unit or semi-detached single dwelling unit.
- Any portion of a building set back from the side lot line shall be considered a side yard and not a court.

604 SPECIAL EXCEPTION NAVAL OBSERVATORY ZONES (NO)

- 604.1 In consideration of a special exception in the MU-27 MU-4/NO zone, in addition to any other criteria of this title, the following conditions shall apply:
 - (a) The Board of Zoning Adjustment shall consider whether the proposed development is compatible with the:
 - (1) Present and proposed development within and adjacent to the MU-27 MU-4/NO zone;
 - (2) Goals, objectives, and policies pertaining to Federal facilities, as found in the Comprehensive Plan and the Master Plans for the Federal facilities within the MU-27 MU-4/NO zone; and
 - (3) Role, mission, and functions of the Federal facilities within the MU-27 MU-4/NO zone, considering the effect that the proposed development would have on such facilities;
 - (b) Upon receipt of the application, the Board of Zoning Adjustment shall submit the application to the Office of Planning for coordination, review, report, and impact assessment along with reviews in writing from all relevant District departments and agencies including the Departments of Transportation, Housing and Community Development, and, if a historic district or historic landmark is involved, the Historic Preservation Office;
 - (c) Upon receipt of the application, the Board of Zoning Adjustment shall refer the application upon receipt to the National Capital Planning Commission for review and report; and
 - (d) The Board of Zoning Adjustment may require special treatment and impose reasonable conditions as it deems necessary to mitigate any adverse impacts identified in the consideration of the application.

CHAPTER 9 CHAPTER 7 FORT TOTTEN MIXED-USE ZONE - MU-28 AND MU-29 MU-7/FT AND MU-10/FT

900 700 PURPOSE AND INTENT

- 700.1 The development standards in Subtitle G, Chapter 2 shall apply to the MU7/FT AND MU-10/FT zones except as specifically modified by this chapter.
 In the event of a conflict between the provisions of this chapter and other regulations of this subtitle, the provisions of this chapter shall control.
- 900.1 700.2 The In addition to the purposes of the MU zones, the purposes of the Fort Totten Mixed-Use zones (MU-28 and MU-29 MU-7/FT and MU-10/FT) are to:
 - (a) Encourage future residential and commercial development while enabling existing industries to remain in the District; and
 - (b) Protect surrounding residential areas from the adverse impacts of existing industrial support uses by means of the buffering standards.
- The MU-28 zone is intended to permit medium density mixed use development with a focus on employment.
- The MU-29 zone is intended to permit medium to high-density development with a balance of uses conducive to a higher quality of life and environment for residents, businesses, employees, and institutions.

901 DEVELOPMENT STANDARDS

The development standards of this chapter modify the general development standards in Subtitle G, Chapter 2.

902 701 DENSITY —FLOOR AREA RATIO (FAR)

701.1 The maximum permitted FAR of buildings in the MU-28 and MU-29 MU-7/FT and MU-10/FT zones shall be as set forth in the following table:

TABLE G § 902.1 701.1: MAXIMUM PERMITTED FLOOR AREA RATIO

	Maximum FAR	
Zone	Total Permitted	Maximum Non-Residential Use
MU-28 MU-7/FT	4.0 4.8 (IZ)	2.5
MU 29 MU-10/FT	5.0 6.0 (IZ)	3.0

- 902.2 701.2 Density may be increased in the MU-28MU-7/FT and MU-29MU-10/FT zones in an existing building on a lot with an area ten thousand square feet (10,000 sq. ft.) or less, and it may have a maximum density of 2.0 FAR for non-residential uses, provided the uses are located in the ground story and the story directly above the ground story.
- 902.3 701.3 In the MU-29 MU-10/FT zone, combined lot development is permitted for the purposes of allocating gross floor area devoted to residential and non-residential uses in accordance with the provisions of Subtitle G § 100.4 G § 214. Both lots shall be located within the same square and shall be zoned MU-29 MU-10/FT.

903-702 **HEIGHT**

The maximum building height, not including the penthouse, in the MU-28 and 903.1 **702.1** MU-29 MU-7/FT and MU-10/FT zones shall be as set forth in the following table:

TABLE G § 903.1 702.1: MAXIMUM BUILDING HEIGHT

Zone	Maximum Height, Not Including the Penthouse (ft.)
MIL 20 MIL FIETE	65
MU-28 MU-7/FT	65 (IZ)
MIL 20 MIL 10/ET	80
MU-29 MU-10/FT	90 (IZ)

703 **PENTHOUSES**

The maximum permitted height of a penthouse, except as prohibited on the roof 903.2 **703.1** of a detached dwelling, semi-detached dwelling, rowhouse, single household **dwelling** or flat in Subtitle C § 1500.4, shall be as set forth in the following table:

TABLE G § 903.2 703.1: MAXIMUM PERMITTED PENTHOUSE HEIGHT AND STORIES

Zone	Maximum Penthouse Height	Maximum Penthouse Stories
MU 28 MU-7/FT	12 ft. except 18 ft. 6 in. for penthouse mechanical space	1; Second story permitted for penthouse mechanical space
MU-29 MU-10/FT	A penthouse shall be included within the maximum permitted building height	1

903.3 **703.2** Buildings proposed to have a height in excess of sixty-five feet (65 ft.) shall provide special architectural features, roof parapet detailing, and design consideration of roof top and penthouse structures to ensure that the views and vistas from the historic fortification of Fort Totten are not degraded or obstructed.

903.4 703.3 The Office of Planning shall review and provide a report with recommendation to the Zoning Administrator prior to the issuance of a building permit.

904 704 LOT OCCUPANCY

The maximum permitted lot occupancy for residential use in the MU-28 MU-7/FT and MU-29 MU-10/FT zones shall be as set forth in the following table:

TABLE G § 904.1: MAXIMUM PERMITTED LOT OCCUPANCY

Zone	Maximum Lot Occupancy for Residential Use (Percentage)
MU-28-MU-7/FT	75
MC 20 MC-7/1 1	80 (IZ)
MU 29 MU-10/FT	75
WIU 29 WIU-10/F I	75 (IZ)

905 REAR YARD

- A minimum rear yard of two and one-half inches (2.5 in.) per one foot (1 ft.) of vertical distance from the mean finished grade at the middle of the rear of the structure to the highest point of the main roof or parapet wall, but not less than twelve feet (12 ft.) shall be provided in the MU-28 and MU-29 zones.
- 905.2 In the MU 28 zone, a horizontal plane may be established at twenty five feet (25 ft.) above the mean finished grade at the middle of the rear of the structure for the purpose of measuring rear yards.
- 905.3 In the MU-28 zone, rear yards shall be measured as follows:
 - (a) Where a lot abuts an alley:
 - (a) For that portion of the structure below a horizontal plane described in Subtitle G § 905.2 from the center line of the alley to the rear wall of the portion; and
 - (b) For that portion of the structure above the horizontal plane described in Subtitle G § 905.2, from the rear lot line to the rear wall of that portion immediately above the plane; and
 - (b) Where a lot does not abut an alley, the rear yard shall be measured from the rear lot line to the rear wall of the building or other structure.
- 905.4 In the MU-29 zone, rear yards are required only for residential uses and shall be established subject to the following conditions:
 - (a) A rear yard shall be established no lower than the first level of residential

use;

- (b) Where a lot abuts an alley, the rear yard may be measured from the center line of the alley to the rear wall of the building or other structure; and
- (c) Where a lot does not abut an alley, the rear yard shall be measured from the rear lot line to the rear wall of the building or other structure.

906 SIDE YARD

- No side yard is required for a principal building; however, if a side yard is provided it shall be at least two inches (2 in.) wide for each one foot (1 ft.) of height of building but no less than five feet (5 ft.).
- Any portion of a building set back from the side lot line shall be considered a side yard and not a court.

907 GREEN AREA RATIO (GAR)

907.1 The minimum required GAR shall be 0.25 for the MU-28 zone and 0.2 for the MU-29 zone.

908 705 SETBACKS AND SCREENING

- 908.1 705.1 A business or industrial use that expands consistent with the development standards of this chapter shall comply with the setback and screening standards.
- 908.2 705.2 If the lot line of the lot being developed coincides with the lot line of a property in a residential zone, or is separated only by a street or alley from a property in a residential zone, where the property is not owned by a business or industrial user, and the property is not being used for residential purposes, the following standards shall apply:
 - (a) A setback of twenty-five feet (25 ft.) shall be provided on the portion of the lot adjacent to the residential zone; provided, that the following requirements are met:
 - (a) (1) Where there is a street or an alley between the residential lot and the lot subject to the MU-28 MU-7/FT, PDR-6, or PDR-7 zones, the required setback shall be fifteen feet (15 ft.) measured from the lot line;
 - (b) (2) The yard shall not be used for parking, loading, or accessory uses;
 - (e) (3) The yard shall be landscaped with evergreen trees in a healthy growing condition which shall be a minimum of six feet to eight feet (6 ft. to 8 ft.) in height when planted; and

- (d) (4) Planting locations and soil preparation techniques shall be shown on a landscape plan submitted with the building permit application to the Department of Consumer and Regulatory Affairs for review and approval according to standards maintained by the Department's Soil Erosion and Storm Management Branch, which may require replacement of heavy or compacted soils with top soil and drainage mechanisms as necessary; and
- (b) A fence or wall shall be erected as a buffer between the residential lot(s) not owned by a business or industrial user that abut a lot affected by this zone; provided, that the fence or wall shall be no less than eight feet (8 ft.) and no more than ten feet (10 ft.) in height, and shall be either a solid, wood, board-on-board fence, or a brick or stone wall.

909 PLAZA

- 909.1 Within the MU-29 zone, a plaza comprising eight percent (8%) of the lot area shall be provided for development on a lot of greater than ten thousand square feet (10,000 sq. ft.), in accordance with the provisions of Subtitle C, Chapter 17.
- Where preferred use space is required under this chapter and provided, the requirement to provide plaza space shall not apply.

910 SPECIAL EXCEPTION

910.1 The special exception criteria of Subtitle G, Chapter 12 shall apply to all the MU-28 and MU-29 zones.

CHAPTER 8 REED-COOKE MIXED-USE ZONES -RC-2 MU-4/RC AND RC-3 MU-5A/RC

PURPOSE AND INTENT

- The development standards in Subtitle G, Chapter 2 shall apply to the MU-4/RC and MU-5A/RC zones except as specifically modified by this chapter.

 In the event of a conflict between the provisions of this chapter and other regulations of this subtitle, the provisions of this chapter shall control.
- 800.2 In addition to the purposes of the MU zones, the purposes of the Reed-Cooke Mixed-Use zones are to:
 - (a) Protect current housing and provide for the development of new housing:
 - (b) Maintain heights and densities at appropriate levels;
 - (c) Encourage small-scale business development that will not adversely affect the residential community;
 - (d) Ensure that new nonresidential uses serve the local community by providing retail goods, personal services, and other activities that contribute to the satisfaction of unmet social, service, and employment needs in the Reed-Cooke and Adams Morgan community;
 - (e) Protect adjacent and nearby residences from damaging traffic, parking, environmental, social, and aesthetic impacts; and
 - (f) Ensure the preservation and adaptive reuse of the First Church of Christ Scientist building, located on Lot 872 of Square 2560, through a planned unit development process.

801 DEVELOPMENT STANDARDS

- 801.1 In addition to other applicable provisions of this title, the requirements of this chapter shall apply to:
 - (a) All new construction;
 - (b) All additions, alterations, or repairs that, within any eighteen (18) month period, exceed in cost fifty percent (50%) of the assessed value of the structure as set forth in the records of the Office of Tax and Revenue on the date of the application for a building permit;
 - (c) Any use that requires a change in the use listed on the owner's or lessee's certificate of occupancy; and

- (d) Any existing use that requires a new permit from the Alcoholic Beverage Control Board.
- 801.2 If there is a dispute between the property owner and the Zoning Administrator about the cost pursuant to Subtitle G § 801.1(b), the cost shall be determined by the average of the estimates furnished by three (3) independent qualified contractors selected in the following manner:
 - (a) The first shall be selected by the owner;
 - (b) The second shall be selected by the Zoning Administrator; and
 - (c) The third shall be selected by the first two (2) contractors.
- 801.3 The estimates provided for by Subtitle G § 801.2 shall be prepared and submitted according to a standard procedure and format established by the Zoning Administrator.

802 HEIGHT

802.1 The maximum permitted building height, not including the penthouse, in the MU-4/RC and MU-5A/RC zones shall be as set forth in the following table:

TABLE G § 802.1: MAXIMUM BUILDING HEIGHT AND STORIES

Zone	Maximum Height, Not	Maximum Number of
	Including penthouse (ft.)	<u>Stories</u>
RC-2 MU-4/RC	40	<u>N/A</u>
RC-3 MU-5A/RC	40 50 (IZ)	<u>N/A</u>

802.2 In the RC-3 MU-5A/RC zone, a building shall be permitted a maximum height of fifty feet (50 ft.), not including the penthouse, provided fifty percent (50%) of the additional gross floor area made possible by the height bonus is devoted to low and moderate income household units, as defined in Subtitle B, Chapter 2.

803 PENTHOUSES

803.1 The maximum permitted height of a penthouse, except as prohibited on the roof of a single household dwelling or flat in Subtitle C § 1500.4, shall be as set forth in the following table:

TABLE G § 803.1: MAXIMUM PENTHOUSE HEIGHT AND STORIES

Zone	Maximum Penthouse Height	Maximum Penthouse Stories
RC-2 MU-4/RC	15 ft. for penthouse mechanical space	1
RC-3 MU-5A/RC	12 ft., except	<u>1;</u>

18 ft. 6 in. for penthouse mechanical	Second story permitted for
space	penthouse mechanical space

804 PLANNED UNIT DEVELOPMENTS

- 804.1 The provisions of Subtitle X, Chapter 3 shall not operate to permit a planned unit development in the RC zones to exceed the floor area ratio standards of Subtitle G § 201 and the height standards of Subtitle G § 802.
- 804.2 Notwithstanding Subtitle G § 804.1, the Zoning Commission, as part of a planned unit development permitting a hotel integrating the First Church Christ Scientist building on a new lot created by combining Lots 872, 875, and 127 of Square 2560, may permit a building height on former Lots 875 and 127 not to exceed seventy-two feet (72 ft.) measured from Euclid Street, and an overall building density not to exceed 3.99 FAR.

805 RELIEF FROM DEVELOPMENT STANDARDS (RC)

- 805.1 An exception from the requirements of this chapter the Reed Cooke (RC)

 zones shall be permitted by special exception if approved by the Board of

 Zoning Adjustment under Subtitle X, and subject to the following conditions:
 - (a) The use, building, or feature at the size, intensity, and location proposed will substantially advance the stated purposes of the RC zones;
 - (b) Vehicular ingress and egress shall be designed and located so as to minimize conflict with pedestrian ways, to function efficiently, and to create no dangerous or otherwise objectionable traffic condition;
 - (c) Adequate off-street parking shall be provided for employees and for trucks and other service vehicles;
 - (d) Noise associated with the operation of a proposed use will not adversely affect adjacent or nearby residences;
 - (e) No outdoor storage of materials, nor outdoor processing, fabricating, or repair shall be permitted; and
 - (f) If located within a MU-5A/RC zone, the use shall not be within twenty-five feet (25 ft.) of a residentially zoned property, unless separated there from by a street or alley.
- 805.2 The use, building, or feature at the size, intensity, and location proposed will not adversely affect adjacent and nearby property or be detrimental to the

<u>health, safety, convenience, or general welfare of persons living, working, or visiting in the area.</u>

CHAPTER 10 DEVELOPMENT STANDARDS FOR PUBLIC EDUCATION BUILDINGS AND STRUCTURES, PUBLIC RECREATION AND COMMUNITY CENTERS, AND PUBLIC LIBRARIES FOR MU ZONES

1000 GENERAL PROVISIONS

- 1000.1 Public education buildings and structures, public recreation and community centers, or public libraries in the MU zones shall be permitted subject to the conditions of Subtitle C, Chapter 16.
- Development standards not otherwise addressed by Subtitle C, Chapter 16 shall be those development standards for the zone in which the buildings or structures is proposed.

CHAPTER 9 through 48 [RESERVED]

CHAPTER 49 PUBLIC SCHOOLS

4900 GENERAL PROVISIONS

4900.1 The provisions of this chapter control certain height and bulk of public schools.

4901 DEVELOPMENT STANDARDS

4901.1 The specific standards of this chapter shall govern public schools; in the absence of specific standards, the development standards for the zone in which the building or structure is proposed shall apply.

4902 DENSITY

4902.1 Public schools shall be permitted a maximum floor area ratio as set forth in the following table:

TABLE G § 4902.1: MAXIMUM FLOOR AREA RATIO (FAR) FOR PUBLIC SCHOOLS

Zone	Maximum FAR
All MU-1, MU-2, MU-10, zones MU-15, MU-16, MU-22, MU-23, MU-29	3.0
All MU-3 zones	1.8
All other MU zones	As permitted for residential (non-IZ) uses by zone

4903 PENTHOUSES

4903.1 Penthouses shall be subject to the regulations of Subtitle C, Chapter 15, and to the height and story limitations specified in each zone of this subtitle; provided that public school buildings shall be permitted a mechanical penthouse to a maximum height of eighteen feet six inches (18 ft. 6 in.) or the permitted mechanical penthouse height in the zone, whichever is greater.

4904 REAR YARD

A minimum rear yard shall be provided as required by the zone within which the lot is located; provided that no rear yard shall be required for a lot that abuts or adjoins along the rear lot line a public open space, recreation area, or reservation.

4905 SIDE YARD

In the case of a lot that abuts or adjoins a public open space, recreation area, or reservation on a side lot line, the required side yard shall not be required.

4906 SPECIAL EXCEPTION

Exceptions to the development standards of this chapter for public schools shall be permitted as a special exception if approved by the Board of Zoning Adjustment under Subtitle X, Chapter 9.

CHAPTER 50 [RESERVED]

CHAPTER 44 51 ALLEY LOT REGULATIONS FOR MU ZONES

[ZC CASE 19-13 ALLEY LOT PENDING]

1100 5100 GENERAL PROVISIONS

- 1100.1 5100.1 All alley lots must be recorded in the records of the Office of the Surveyor, District of Columbia, as a record lot.
- 1100.2 5100.2 New alley lots may be created as provided in Subtitle C, Chapter 3.

1101 5101 DEVELOPMENT STANDARDS

1101.1 5101.1 The development standards in Subtitle G §§ 1102 through 1106 shall apply to buildings on alley lots in MU zones.

1102 5102 HEIGHT

- 1102.1 5102.1 The maximum height and stories of the building in MU-6, MU-8, MU-9, MU-10, MU-19, MU-20, MU-21, MU-22, and MU-29 zones shall be thirty feet (30 ft.) and three (3) stories, including the penthouse.
- 1102.2 5102.2 The maximum height and stories of the building in all other MU zones shall be twenty feet (20 ft.) and two (2) stories, including the penthouse.

1103 5103 REAR YARD

1103.1 5103.1 A minimum rear yard of five feet (5 ft.) shall be provided from any lot line of all abutting non-alley lots.

1104 5104 SIDE YARD

1104.1 5104.1 A minimum side yard of five feet (5 ft.) shall be provided from any lot line of all abutting non-alley lots.

1105 5105 ALLEY CENTERLINE SETBACK

1105.1 5105.1 A required twelve foot (12 ft.) setback from the centerline of all alleys to which the alley lot abuts shall be provided.

1106 5106 GREEN AREA RATIO (GAR)

1106.1 5106.1 The minimum required GAR shall be as required by the zone.

CHAPTER 12-52 RELIEF FROM <u>REQUIRED</u> DEVELOPMENT STANDARDS (MU ZONES)

[ZC CASE 19-14 NONCONFORMING STRUCTURES PENDING]

1200 5200 GENERAL PROVISIONS

- 1200.1 5200.1 The Board of Zoning Adjustment may grant special exception relief to the development standards of this subtitle subject to any applicable conditions of this chapter.
- 5200.2 Except as provided elsewhere in this title relief from the development standards for height and floor area ratio shall be required as a variance.
- 1200.2 5200.3 As set forth in this chapter, specific conditions or criteria may be applicable in the consideration of relief and shall be considered in combination with the conditions of Subtitle X, Chapter 9.
- 4200.3 5200.4 Requested relief that does not comply with the applicable conditions or limitations for a special exception as set out in this subtitle shall be processed as a variance.
- 1200.4 5200.5 Relief may be granted as a special exception by the Board of Zoning Adjustment to the development standards and regulations of this subtitle, except for height and floor-area-ratio, where, in the judgment of the Board, the special exception:
 - (a) Will be in harmony with the general purpose and intent of the MU zone, the Zoning Regulations, and Zoning Maps;
 - (b) Will not tend to affect adversely the use of neighboring property, in accordance with the Zoning Regulations and Zoning Maps; and
 - (c) Is subject in each case to any applicable conditions specified in this chapter.

1201 SPECIAL EXCEPTION CRITERIA REAR YARD RELIEF

- The Board of Zoning Adjustment may grant relief to the rear yard requirements of this subtitle as a special exception pursuant to Subtitle X, provided:
 - (a) No apartment window shall be located within forty feet (40 ft.) directly in front of another building;
 - (b) No office window shall be located within thirty feet (30 ft.) directly in front of another office window, nor eighteen feet (18 ft.) in front of a blank wall:

- (c) In buildings that are not parallel to the adjacent buildings, the angle of sight lines and the distance of penetration of sight lines into habitable rooms shall be considered in determining distances between windows and appropriate yards;
- (d) Provision shall be included for service functions, including parking and loading access and adequate loading areas; and
- (e) Upon receiving an application to waive rear yard requirements in the subject zone, the Board of Zoning Adjustment shall submit the application to the Office of Planning for coordination, review, report, and impact assessment, along with reviews in writing from all relevant District of Columbia departments and agencies, including the Department of Transportation, the District of Columbia Housing Authority and, if a historic district or historic landmark is involved, the Historic Preservation Office.

1202 SPECIAL EXCEPTION CRITERIA NAVAL OBSERVATORY ZONES (MU-27 MU-4/NO)

- 1202.1 In consideration of a special exception in the MU-27 MU-4/NO zone, in addition to any other criteria of this title, the following conditions shall apply:
 - (a) The Board of Zoning Adjustment shall consider whether the proposed development is compatible with the:
 - (1) Present and proposed development within and adjacent to the MU-27 MU-4/NO zone;
 - (2) Goals, objectives, and policies pertaining to Federal facilities, as found in the Comprehensive Plan and the Master Plans for the Federal facilities within the MU-27 MU-4/NO zone; and
 - (3) Role, mission, and functions of the Federal facilities within the MU 27 MU-4/NO zone, considering the effect that the proposed development would have on such facilities;
 - (b) Upon receipt of the application, the Board of Zoning Adjustment shall submit the application to the Office of Planning for coordination, review, report, and impact assessment along with reviews in writing from all relevant District departments and agencies including the Departments of Transportation, Housing and Community Development, and, if a historic district or historic landmark is involved, the Historic Preservation Office;
 - (c) Upon receipt of the application, the Board of Zoning Adjustment shall refer the application upon receipt to the National Capital Planning Commission for review and report; and
 - (d) The Board of Zoning Adjustment may require special treatment and impose reasonable conditions as it deems necessary to mitigate any adverse impacts identified in the consideration of the application.

SUBTITLE C CHAPTER 16 PUBLIC EDUCATION, RECREATION OR LIBRARY BUILDINGS OR STRUCTURES is deleted in its entirety.

[ZC CASE 19-27 REORGANIZATION OF 11 DCMR TEXT - PENDING]

SUBTITLE K CHAPTER 7 REED-COOKE ZONES is deleted in its entirety [ZC CASE 19-27 REORGANIZATION OF 11 DCMR TEXT - PENDING]

SUBTITLE U USES, CHAPTER 4 is amended as follows:

CHAPTER 4 USE PERMISSIONS RESIDENTIAL APARTMENT (RA) ZONES is amended to add a new § 401.3 to Section 401 MATTER OF RIGHT USES (RA).

- 401 MATTER-OF-RIGHT USES (RA)
- 401.3 In the RA-2/RC zone, the uses of this section shall be permitted as a matter-of-right unless not permitted in Subtitle U § 514.2.

CHAPTER 4 USE PERMISSIONS RESIDENTIAL APARTMENT (RA) ZONES is amended to add a new § 410.2 to Section 410 ACCESSORY USES (RA) as follows:

410 ACCESSORY USES (RA)

410.1 ...

410.2 In the RA-2/RC zone a drive-through accessory to any use shall not be permitted.

CHAPTER 4 USE PERMISSIONS RESIDENTIAL APARTMENT (RA) ZONES is amended to add a new § 420.1 to Section 420 SPECIAL EXCEPTION USES (RA) as follows:

- 420 SPECIAL EXCEPTION USES (RA)
- 420.1 The following uses shall be permitted as a special exception if approved by the Board of Zoning Adjustment under Subtitle X, Chapter 9, subject to any applicable provisions of each section:

- (a) . . .
- (h) . . .
- Before taking final action on an application for the use, the Board of Zoning Adjustment shall submit the application to the D.C.
 Department of Transportation for review and report; and
- (i) In the RA-1 and RA-6 zones, a continuing care retirement community subject to the conditions of Subtitle U § 203.1(f), except for 203.1(f)(3)-3 and
- (j) In the RA-2/RC zone, the uses of this section shall be permitted as a special exception unless not permitted in Subtitle U §514.2.

CHAPTER 5 USE PERMISSIONS MIXED USE (MU) ZONES is amended to add a new § 512.2 to Section 512 MATTER OF RIGHT USES (MU).

- 512 MATTER-OF-RIGHT USES (MU USE GROUP E)
- 512.1 ...
- 512.2 In the MU-4/RC and MU-5A/RC zones, the uses of this section shall be permitted as a matter-of-right unless not permitted in Subtitle U §514.2.

CHAPTER 5 USE PERMISSIONS MIXED USE (MU) ZONES is amended to add a new § 513.2 to Section **513 SPECIAL EXCEPTION USES (MU)** as follows:

- 513 SPECIAL EXCEPTION USES (MU USE GROUP E)
- 513.1 ...
- 513.2 In the MU-4/RC and MU-5A/RC zones, the uses of this section shall be permitted as a special exception unless not permitted in Subtitle U §514.2.

CHAPTER 5 USE PERMISSIONS MIXED USE (MU) ZONES is amended to add a new § is amended to add a new Section 514.2 to Section 514 PROHIBITED USES (MU-USE GROUP E) as follows:

- 514 PROHIBITED USES (MU USE GROUP E)
- 514.1 ...

514.2 In the RC zones, the following uses shall not be permitted either as a matter-of-right or by special exception:

- (a) Antenna tower in excess of twenty feet (20 ft.) in height;
- (b) Any use not permitted in the MU-10 zone, except a parking lot as permitted by Subtitle U § 203.1 (j);
- (c) Assembly hall, auditorium, or public hall;
- (d) Automobile laundry;
- (e) Automobile or truck sales;
- (f) Automobile rental agency that stores or services automobiles within an RC zone;
- (g) Bar or cocktail lounge;
- (h) Billiard parlor or pool hall;
- (i) Boat or other marine sales;
- (j) Bowling alley;
- (k) Bus passenger depot;
- (l) Drive-through;
- (m) Funeral mortuary or other similar establishment;
- (n) Gasoline service station or repair garage;
- (o) Hotel;
- (p) Motorcycle sales or repair;
- (q) Movie theater;
- (r) Off-premises alcoholic beverage sales, except that the off-premises beer and wine sales accessory use in the grocery store located in Square 2572,

 Lot 36 may continue as a matter of right provided that it shall not occupy more than 2,078 square feet of the store's gross floor area;
- (s) On-premises dry cleaning establishment;
- (t) Parcel delivery service establishment other than one exclusively dedicated to serving a sound stage or a movie, video, or television production facility that existed on April 26, 1991;
- (u) Restaurant or fast food establishment;
- (v) Satellite reception dish greater than fifteen feet (15 ft.) in diameter;
- (w) Transient accommodations that are not home occupations;
- (x) Veterinary hospital; and
- (y) Video game parlor.